

"h2o"

March 29, 2018

R topics documented:

| | |
|----------------------------------|----|
| h2o-package | 7 |
| aaa | 8 |
| apply | 8 |
| as.character.H2OFrame | 9 |
| as.data.frame.H2OFrame | 9 |
| as.factor | 10 |
| as.h2o | 11 |
| as.matrix.H2OFrame | 12 |
| as.numeric | 13 |
| as.vector.H2OFrame | 13 |
| australia | 14 |
| colnames | 14 |
| dim.H2OFrame | 15 |
| dimnames.H2OFrame | 15 |
| h2o.abs | 16 |
| h2o.acos | 17 |
| h2o.aggregated_frame | 17 |
| h2o.aggregator | 18 |
| h2o.aic | 19 |
| h2o.all | 20 |
| h2o.anomaly | 20 |
| h2o.any | 21 |
| h2o.anyFactor | 21 |
| h2o.arrange | 22 |
| h2o.ascharacter | 22 |
| h2o.asfactor | 23 |
| h2o.asnumeric | 23 |
| h2o.assign | 24 |
| h2o.as_date | 24 |
| h2o.auc | 25 |
| h2o.automl | 25 |
| h2o.betweenss | 27 |
| h2o.biases | 28 |
| h2o.bottomN | 28 |
| h2o.cbind | 29 |
| h2o.ceiling | 29 |
| h2o.centers | 30 |

| | |
|--|----|
| h2o.centersSTD | 30 |
| h2o.centroid_stats | 30 |
| h2o.clearLog | 31 |
| h2o.clusterInfo | 31 |
| h2o.clusterIsUp | 32 |
| h2o.clusterStatus | 32 |
| h2o.cluster_sizes | 33 |
| h2o.coef | 33 |
| h2o.coef_norm | 34 |
| h2o.colnames | 34 |
| h2o.columns_by_type | 35 |
| h2o.computeGram | 35 |
| h2o.confusionMatrix | 36 |
| h2o.connect | 37 |
| h2o.cor | 38 |
| h2o.cos | 39 |
| h2o.cosh | 39 |
| h2o.coxph | 40 |
| h2o.createFrame | 41 |
| h2o.cross_validation_fold_assignment | 42 |
| h2o.cross_validation_holdout_predictions | 43 |
| h2o.cross_validation_models | 43 |
| h2o.cross_validation_predictions | 44 |
| h2o.cummax | 44 |
| h2o.cummin | 45 |
| h2o.cumprod | 45 |
| h2o.cumsum | 46 |
| h2o.cut | 46 |
| h2o.day | 47 |
| h2o.dayOfWeek | 48 |
| h2o.dct | 48 |
| h2o.ddply | 49 |
| h2o.decryptionSetup | 50 |
| h2o.deepfeatures | 51 |
| h2o.deeplearning | 52 |
| h2o.deepwater | 58 |
| h2o.deepwater.available | 62 |
| h2o.describe | 62 |
| h2o.diffflag1 | 63 |
| h2o.dim | 63 |
| h2o.dimnames | 64 |
| h2o.distance | 64 |
| h2o.downloadAllLogs | 65 |
| h2o.downloadCSV | 65 |
| h2o.download_mojo | 66 |
| h2o.download_pojo | 67 |
| h2o.entropy | 68 |
| h2o.exp | 68 |
| h2o.exportFile | 69 |
| h2o.exportHDFS | 70 |
| h2o.fillna | 70 |
| h2o.filterNACols | 71 |

| | |
|--|-----|
| h2o.findSynonyms | 71 |
| h2o.find_row_by_threshold | 72 |
| h2o.find_threshold_by_max_metric | 72 |
| h2o.floor | 73 |
| h2o.flow | 73 |
| h2o.gainsLift | 73 |
| h2o.gbm | 74 |
| h2o.getConnection | 78 |
| h2o.getFrame | 79 |
| h2o.getFutureModel | 79 |
| h2o.getGLMFullRegularizationPath | 79 |
| h2o.getGrid | 80 |
| h2o.getId | 80 |
| h2o.getModel | 81 |
| h2o.getTimezone | 81 |
| h2o.getTypes | 82 |
| h2o.getVersion | 82 |
| h2o.giniCoef | 82 |
| h2o.glm | 83 |
| h2o.glm | 87 |
| h2o.grep | 90 |
| h2o.grid | 91 |
| h2o.group_by | 92 |
| h2o.gsub | 93 |
| h2o.head | 94 |
| h2o.hist | 94 |
| h2o.hit_ratio_table | 95 |
| h2o.hour | 95 |
| h2o.ifelse | 96 |
| h2o.importFile | 97 |
| h2o.import_sql_select | 98 |
| h2o.import_sql_table | 99 |
| h2o.impute | 100 |
| h2o.init | 101 |
| h2o.insertMissingValues | 103 |
| h2o.interaction | 104 |
| h2o.isax | 105 |
| h2o.ischaracter | 106 |
| h2o.isfactor | 106 |
| h2o.isnumeric | 107 |
| h2o.is_client | 107 |
| h2o.kfold_column | 107 |
| h2o.killMinus3 | 108 |
| h2o.kmeans | 108 |
| h2o.kurtosis | 110 |
| h2o.levels | 110 |
| h2o.listTimezones | 111 |
| h2o.list_all_extensions | 111 |
| h2o.list_api_extensions | 111 |
| h2o.list_core_extensions | 112 |
| h2o.loadModel | 112 |
| h2o.log | 113 |

| | |
|----------------------------|-----|
| h2o.log10 | 113 |
| h2o.log1p | 114 |
| h2o.log2 | 114 |
| h2o.logAndEcho | 115 |
| h2o.logloss | 115 |
| h2o.ls | 116 |
| h2o.lstrip | 116 |
| h2o.mae | 117 |
| h2o.makeGLMModel | 117 |
| h2o.make_metrics | 118 |
| h2o.match | 118 |
| h2o.max | 119 |
| h2o.mean | 120 |
| h2o.mean_per_class_error | 121 |
| h2o.mean_residual_deviance | 122 |
| h2o.median | 122 |
| h2o.merge | 123 |
| h2o.metric | 124 |
| h2o.min | 126 |
| h2o.mktime | 126 |
| h2o.month | 127 |
| h2o.mse | 127 |
| h2o.nacnt | 128 |
| h2o.naiveBayes | 129 |
| h2o.names | 131 |
| h2o.na_omit | 131 |
| h2o.nchar | 132 |
| h2o.ncol | 132 |
| h2o.networkTest | 133 |
| h2o.nlevels | 133 |
| h2o.no_progress | 133 |
| h2o.nrow | 134 |
| h2o.null_deviance | 134 |
| h2o.null_dof | 135 |
| h2o.num_iterations | 135 |
| h2o.num_valid_substrings | 136 |
| h2o.openLog | 136 |
| h2o.parseRaw | 137 |
| h2o.parseSetup | 138 |
| h2o.partialPlot | 139 |
| h2o.performance | 140 |
| h2o.pivot | 141 |
| h2o.prcomp | 141 |
| h2o.predict_json | 143 |
| h2o.print | 144 |
| h2o.prod | 144 |
| h2o.proj_archetypes | 145 |
| h2o.quantile | 146 |
| h2o.r2 | 147 |
| h2o.randomForest | 147 |
| h2o.range | 151 |
| h2o.rbind | 151 |

| | |
|--------------------------|-----|
| h2o.reconstruct | 152 |
| h2o.relevel | 153 |
| h2o.removeAll | 153 |
| h2o.removeVecs | 154 |
| h2o.rep_len | 154 |
| h2o.residual_deviance | 155 |
| h2o.residual_dof | 155 |
| h2o.rm | 156 |
| h2o.rmse | 156 |
| h2o.rmsle | 157 |
| h2o.round | 158 |
| h2o.rstrip | 158 |
| h2o.runif | 159 |
| h2o.saveModel | 159 |
| h2o.saveModelDetails | 160 |
| h2o.saveMojo | 161 |
| h2o.scale | 162 |
| h2o.scoreHistory | 162 |
| h2o.sd | 163 |
| h2o.sdev | 163 |
| h2o.setLevels | 164 |
| h2o.setTimezone | 164 |
| h2o.show_progress | 165 |
| h2o.shutdown | 165 |
| h2o.signif | 166 |
| h2o.sin | 166 |
| h2o.skewness | 167 |
| h2o.splitFrame | 167 |
| h2o.sqrt | 168 |
| h2o.stackedEnsemble | 169 |
| h2o.startLogging | 170 |
| h2o.std_coef_plot | 171 |
| h2o.stopLogging | 171 |
| h2o.str | 172 |
| h2o.stringdist | 172 |
| h2o.strsplit | 173 |
| h2o.sub | 173 |
| h2o.substring | 174 |
| h2o.sum | 175 |
| h2o.summary | 175 |
| h2o.svd | 176 |
| h2o.table | 178 |
| h2o.tabulate | 178 |
| h2o.tan | 179 |
| h2o.tanh | 180 |
| h2o.target_encode_apply | 180 |
| h2o.target_encode_create | 181 |
| h2o.toFrame | 182 |
| h2o.tokenize | 183 |
| h2o.tolower | 184 |
| h2o.topN | 184 |
| h2o.totss | 185 |

| | |
|---|-----|
| h2o.tot_withinss | 185 |
| h2o.toupper | 186 |
| h2o.transform | 186 |
| h2o.trim | 187 |
| h2o.trunc | 187 |
| h2o.unique | 188 |
| h2o.var | 188 |
| h2o.varimp | 189 |
| h2o.varimp_plot | 189 |
| h2o.week | 190 |
| h2o.weights | 191 |
| h2o.which | 191 |
| h2o.which_max | 192 |
| h2o.which_min | 192 |
| h2o.withinss | 193 |
| h2o.word2vec | 193 |
| h2o.xgboost | 194 |
| h2o.xgboost.available | 197 |
| h2o.year | 198 |
| H2OAutoML-class | 198 |
| H2OClusteringModel-class | 199 |
| H2OConnection-class | 199 |
| H2OConnectionMutableState | 200 |
| H2OCoxPHModel-class | 200 |
| H2OCoxPHModelSummary-class | 201 |
| H2OFrame-class | 201 |
| H2OFrame-Extract | 201 |
| H2OGrid-class | 202 |
| H2OModel-class | 203 |
| H2OModelFuture-class | 203 |
| H2OModelMetrics-class | 204 |
| housevotes | 204 |
| iris | 205 |
| is.character | 205 |
| is.factor | 206 |
| is.h2o | 206 |
| is.numeric | 206 |
| Logical-or | 207 |
| ModelAccessors | 207 |
| names.H2OFrame | 208 |
| Ops.H2OFrame | 208 |
| plot.H2OModel | 210 |
| plot.H2OTabulate | 211 |
| predict.H2OAutoML | 212 |
| predict.H2OModel | 212 |
| predict_leaf_node_assignment.H2OModel | 213 |
| print.H2OFrame | 214 |
| print.H2OTable | 214 |
| prostate | 215 |
| range.H2OFrame | 215 |
| show,H2OCoxPHModelSummary-method | 216 |
| str.H2OFrame | 216 |

| | |
|--|-----|
| summary,H2OCoxPHModel-method | 217 |
| summary,H2OGrid-method | 217 |
| summary,H2OModel-method | 218 |
| use.package | 218 |
| walking | 219 |
| zzz | 219 |
| && | 220 |

| | |
|--------------|------------|
| Index | 221 |
|--------------|------------|

| | |
|-------------|------------------------|
| h2o-package | <i>H2O R Interface</i> |
|-------------|------------------------|

Description

This is a package for running H2O via its REST API from within R. To communicate with a H2O instance, the version of the R package must match the version of H2O. When connecting to a new H2O cluster, it is necessary to re-run the initializer.

Details

```

Package: h2o
Type: Package
Version: 3.18.0.5
Branch: rel-wolpert
Date: Thu Mar 29 01:03:49 UTC 2018
License: Apache License (== 2.0)
Depends: R (>= 2.13.0), RCurl, jsonlite, statmod, tools, methods, utils

```

This package allows the user to run basic H2O commands using R commands. In order to use it, you must first have H2O running. To run H2O on your local machine, call `h2o.init` without any arguments, and H2O will be automatically launched at `localhost:54321`, where the IP is "127.0.0.1" and the port is 54321. If H2O is running on a cluster, you must provide the IP and port of the remote machine as arguments to the `h2o.init()` call.

H2O supports a number of standard statistical models, such as GLM, K-means, and Random Forest. For example, to run GLM, call `h2o.glm` with the H2O parsed data and parameters (response variable, error distribution, etc...) as arguments. (The operation will be done on the server associated with the data object where H2O is running, not within the R environment).

Note that no actual data is stored in the R workspace; and no actual work is carried out by R. R only saves the named objects, which uniquely identify the data set, model, etc on the server. When the user makes a request, R queries the server via the REST API, which returns a JSON file with the relevant information that R then displays in the console.

If you are using an older version of H2O, use the following porting guide to update your scripts:
[Porting Scripts](#)

Author(s)

Maintainer: The H2O.ai team <tomk@0xdata.com>

References

- [H2O.ai Homepage](#)
- [H2O Documentation](#)
- [H2O on GitHub](#)

 aaa

Starting H2O For examples

Description

Starting H2O For examples

Examples

```
if(Sys.info()['sysname'] == "Darwin" && Sys.info()['release'] == '13.4.0'){
  quit(save="no")
}else{
  h2o.init(nthreads = 2)
}
```

 apply

Apply on H2O Datasets

Description

Method for apply on H2OFrame objects.

Usage

```
apply(X, MARGIN, FUN, ...)
```

Arguments

| | |
|--------|--|
| X | an H2OFrame object on which apply will operate. |
| MARGIN | the vector on which the function will be applied over, either 1 for rows or 2 for columns. |
| FUN | the function to be applied. |
| ... | optional arguments to FUN. |

Value

Produces a new H2OFrame of the output of the applied function. The output is stored in H2O so that it can be used in subsequent H2O processes.

See Also

[apply](#) for the base generic

Examples

```
h2o.init()
irisPath <- system.file("extdata", "iris.csv", package="h2o")
iris.hex <- h2o.importFile(path = irisPath, destination_frame = "iris.hex")
summary(apply(iris.hex, 2, sum))
```

as.character.H2OFrame *Convert an H2OFrame to a String*

Description

Convert an H2OFrame to a String

Usage

```
## S3 method for class 'H2OFrame'
as.character(x, ...)
```

Arguments

x An H2OFrame object
 ... Further arguments to be passed from or to other methods.

Examples

```
h2o.init()
pretrained.frame <- as.h2o(data.frame(
  C1 = c("a", "b"), C2 = c(0, 1), C3 = c(1, 0), C4 = c(0.2, 0.8),
  stringsAsFactors = FALSE))
pretrained.w2v <- h2o.word2vec(pre_trained = pretrained.frame, vec_size = 3)
words <- as.character(as.h2o(c("b", "a", "c", NA, "a")))
vecs <- h2o.transform(pretrained.w2v, words = words)
```

as.data.frame.H2OFrame

Converts parsed H2O data into an R data frame

Description

Downloads the H2O data and then scans it in to an R data frame.

Usage

```
## S3 method for class 'H2OFrame'
as.data.frame(x, ...)
```

Arguments

- x An H2OFrame object.
- ... Further arguments to be passed down from other methods.

Details

Method `as.data.frame.H2OFrame` will use `fread` if `data.table` package is installed in required version.

See Also

[use.package](#)

Examples

```
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
as.data.frame(prostate.hex)
```

as.factor

Convert H2O Data to Factors

Description

Convert a column into a factor column.

Usage

```
as.factor(x)
```

Arguments

- x a column from an H2OFrame data set.

See Also

[as.factor.](#)

Examples

```
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
prostate.hex[,2] <- as.factor(prostate.hex[,2])
summary(prostate.hex)
```

`as.h2o`*Create H2OFrame*

Description

Import R object to the H2O cloud.

Usage

```
as.h2o(x, destination_frame = "", ...)  
  
## Default S3 method:  
as.h2o(x, destination_frame = "", ...)  
  
## S3 method for class 'H2OFrame'  
as.h2o(x, destination_frame = "", ...)  
  
## S3 method for class 'data.frame'  
as.h2o(x, destination_frame = "", ...)  
  
## S3 method for class 'Matrix'  
as.h2o(x, destination_frame = "", ...)
```

Arguments

| | |
|--------------------------------|--|
| <code>x</code> | An R object. |
| <code>destination_frame</code> | A string with the desired name for the H2OFrame. |
| <code>...</code> | arguments passed to method arguments. |

Details

Method `as.h2o.data.frame` will use `fwrite` if `data.table` package is installed in required version.

To speedup execution time for large sparse matrices, use `h2o.datatable`. Make sure you have installed and imported `data.table` and `slam` packages. Turn on `h2o.datatable` by options(`"h2o.use.data.table"`=TRUE)

References

<http://blog.h2o.ai/2016/04/fast-csv-writing-for-r/>

See Also

[use.package](#)

Examples

```
h2o.init()  
hi <- as.h2o(iris)  
he <- as.h2o(euro)  
hl <- as.h2o(letters)  
hm <- as.h2o(state.x77)
```

```

hh <- as.h2o(hi)
stopifnot(is.h2o(hi), dim(hi)==dim(iris),
          is.h2o(he), dim(he)==c(length(euro),1L),
          is.h2o(hl), dim(hl)==c(length(letters),1L),
          is.h2o(hm), dim(hm)==dim(state.x77),
          is.h2o(hh), dim(hh)==dim(hi))
if (requireNamespace("Matrix", quietly=TRUE)) {
  data <- rep(0, 100)
  data[(1:10)^2] <- 1:10 * pi
  m <- matrix(data, ncol = 20, byrow = TRUE)
  m <- Matrix::Matrix(m, sparse = TRUE)
  hs <- as.h2o(m)
  stopifnot(is.h2o(hs), dim(hs)==dim(m))
}

```

as.matrix.H2OFrame *Convert an H2OFrame to a matrix*

Description

Convert an H2OFrame to a matrix

Usage

```

## S3 method for class 'H2OFrame'
as.matrix(x, ...)

```

Arguments

| | |
|-----|---|
| x | An H2OFrame object |
| ... | Further arguments to be passed down from other methods. |

Examples

```

h2o.init()
irisPath <- system.file("extdata", "iris.csv", package="h2o")
iris <- h2o.uploadFile(path = irisPath)
iris.hex <- as.h2o(iris)
describe <- h2o.describe(iris.hex)
mins = as.matrix(apply(iris.hex, 2, min))
print(mins)

```

| | |
|------------|------------------------------------|
| as.numeric | <i>Convert H2O Data to Numeric</i> |
|------------|------------------------------------|

Description

Converts an H2O column into a numeric value column.

Usage

```
as.numeric(x)
```

Arguments

| | |
|-----|--|
| x | a column from an H2OFrame data set. |
| ... | Further arguments to be passed from or to other methods. |

Examples

```
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
prostate.hex[,2] <- as.factor (prostate.hex[,2])
prostate.hex[,2] <- as.numeric(prostate.hex[,2])
```

| | |
|--------------------|--|
| as.vector.H2OFrame | <i>Convert an H2OFrame to a vector</i> |
|--------------------|--|

Description

Convert an H2OFrame to a vector

Usage

```
## S3 method for class 'H2OFrame'
as.vector(x,mode)
```

Arguments

| | |
|------|--------------------------|
| x | An H2OFrame object |
| mode | Mode to coerce vector to |

Examples

```

h2o.init()
irisPath <- system.file("extdata", "iris.csv", package="h2o")
iris <- h2o.uploadFile(path = irisPath)
hex <- as.h2o(iris)
cor_R <- cor(as.matrix(iris[,1]))
cor_h2o <- cor(hex[,1])
iris_Rcor <- cor(iris[,1:4])
iris_H2Ocor <- as.data.frame(cor(hex[,1:4]))
h2o_vec <- as.vector(unlist(iris_H2Ocor))
r_vec <- as.vector(unlist(iris_Rcor))

```

| | |
|-----------|-------------------------------|
| australia | <i>Australia Coastal Data</i> |
|-----------|-------------------------------|

Description

Temperature, soil moisture, runoff, and other environmental measurements from the Australia coast. The data is available from <http://cs.colby.edu/courses/S11/cs251/labs/lab07/AustraliaSubset.csv>.

Format

A data frame with 251 rows and 8 columns

| | |
|----------|--|
| colnames | <i>Returns the column names of an H2OFrame</i> |
|----------|--|

Description

Returns the column names of an H2OFrame

Usage

```
colnames(x, do.NULL = TRUE, prefix = "col")
```

Arguments

| | |
|---------|--|
| x | An H2OFrame object. |
| do.NULL | logical. If FALSE and names are NULL, names are created. |
| prefix | for created names. |

Examples

```

h2o.init()
iris.hex <- as.h2o(iris)
colnames(iris) # Returns "Sepal.Length" "Sepal.Width" "Petal.Length" "Petal.Width" "Species"

```

| | |
|--------------|--|
| dim.H2OFrame | <i>Returns the Dimensions of an H2OFrame</i> |
|--------------|--|

Description

Returns the number of rows and columns for an H2OFrame object.

Usage

```
## S3 method for class 'H2OFrame'  
dim(x)
```

Arguments

x An H2OFrame object.

See Also

[dim](#) for the base R method.

Examples

```
h2o.init()  
iris.hex <- as.h2o(iris)  
dim(iris.hex)
```

| | |
|-------------------|------------------------------------|
| dimnames.H2OFrame | <i>Column names of an H2OFrame</i> |
|-------------------|------------------------------------|

Description

Set column names of an H2O Frame

Usage

```
## S3 method for class 'H2OFrame'  
dimnames(x)
```

Arguments

x An H2OFrame

Examples

```

h2o.init()
n <- 2000
# Generate variables V1, ... V10
X <- matrix(rnorm(10*n), n, 10)
# y = +1 if sum_i x_{ij}^2 > chisq median on 10 df
y <- rep(-1, n)
y[apply(X*X, 1, sum) > qchisq(.5, 10)] <- 1
# Assign names to the columns of X:
dimnames(X)[[2]] <- c("V1", "V2", "V3", "V4", "V5", "V6", "V7", "V8", "V9", "V10")

```

h2o.abs

Compute the absolute value of x

Description

Compute the absolute value of x

Usage

```
h2o.abs(x)
```

Arguments

x An H2OFrame object.

See Also

[abs](#) for the base R implementation.

Examples

```

h2o.init()
url <- "https://s3.amazonaws.com/h2o-public-test-data/smalldata/gbm_test/smtrees.csv"
smtreesH2O <- h2o.importFile(url)
smtreesR <- read.csv("https://s3.amazonaws.com/h2o-public-test-data/smalldata/gbm_test/smtrees.csv")
fith2o <- h2o.gbm(x=c("girth", "height"), y="vol", ntrees=3, max_depth=1, distribution="gaussian",
                 min_rows=2, learn_rate=.1, training_frame=smtreesH2O)
pred <- as.data.frame(predict(fith2o, newdata=smtreesH2O))
diff <- pred-smtreesR[,4]
diff_abs <- abs(diff)
print(diff_abs)

```

| | |
|----------|------------------------------------|
| h2o.acos | <i>Compute the arc cosine of x</i> |
|----------|------------------------------------|

Description

Compute the arc cosine of x

Usage

```
h2o.acos(x)
```

Arguments

x An H2OFrame object.

See Also

[acos](#) for the base R implementation.

Examples

```
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
h2o.acos(prostate.hex[,2])
```

| | |
|----------------------|--|
| h2o.aggregated_frame | <i>Retrieve an aggregated frame from an Aggregator model</i> |
|----------------------|--|

Description

Retrieve an aggregated frame from the Aggregator model and use it to create a new frame.

Usage

```
h2o.aggregated_frame(model)
```

Arguments

model an [H2OClusteringModel](#) corresponding from a h2o.aggregator call.

Examples

```

library(h2o)
h2o.init()
df <- h2o.createFrame(rows=100, cols=5, categorical_fraction=0.6, integer_fraction=0,
                      binary_fraction=0, real_range=100, integer_range=100, missing_fraction=0)
target_num_exemplars=1000
rel_tol_num_exemplars=0.5
encoding="Eigen"
agg <- h2o.agggregator(training_frame=df,
                       target_num_exemplars=target_num_exemplars,
                       rel_tol_num_exemplars=rel_tol_num_exemplars,
                       categorical_encoding=encoding)
# Use the aggregated frame to create a new dataframe
new_df <- h2o.aggregated_frame(agg)

```

h2o.agggregator

*Build an Aggregated Frame***Description**

Builds an Aggregated Frame of an H2OFrame.

Usage

```

h2o.agggregator(training_frame, x, model_id = NULL, ignore_const_cols = TRUE,
                target_num_exemplars = 5000, rel_tol_num_exemplars = 0.5,
                transform = c("NONE", "STANDARDIZE", "NORMALIZE", "DEMEAN", "DESCALE"),
                categorical_encoding = c("AUTO", "Enum", "OneHotInternal", "OneHotExplicit",
                "Binary", "Eigen", "LabelEncoder", "SortByResponse", "EnumLimited"),
                save_mapping_frame = FALSE)

```

Arguments

| | |
|-----------------------|--|
| training_frame | Id of the training data frame. |
| x | A vector containing the character names of the predictors in the model. |
| model_id | Destination id for this model; auto-generated if not specified. |
| ignore_const_cols | Logical. Ignore constant columns. Defaults to TRUE. |
| target_num_exemplars | Targeted number of exemplars Defaults to 5000. |
| rel_tol_num_exemplars | Relative tolerance for number of exemplars (e.g. 0.5 is +/- 50 percents) Defaults to 0.5. |
| transform | Transformation of training data Must be one of: "NONE", "STANDARDIZE", "NORMALIZE", "DEMEAN", "DESCALE". Defaults to NORMALIZE. |
| categorical_encoding | Encoding scheme for categorical features Must be one of: "AUTO", "Enum", "OneHotInternal", "OneHotExplicit", "Binary", "Eigen", "LabelEncoder", "SortByResponse", "EnumLimited". Defaults to AUTO. |

save_mapping_frame

Logical. Whether to export the mapping of the aggregated frame Defaults to FALSE.

Examples

```
library(h2o)
h2o.init()
df <- h2o.createFrame(rows=100, cols=5, categorical_fraction=0.6, integer_fraction=0,
binary_fraction=0, real_range=100, integer_range=100, missing_fraction=0)
target_num_exemplars=1000
rel_tol_num_exemplars=0.5
encoding="Eigen"
agg <- h2o.agggregator(training_frame=df,
target_num_exemplars=target_num_exemplars,
rel_tol_num_exemplars=rel_tol_num_exemplars,
categorical_encoding=encoding)
```

h2o.aic

Retrieve the Akaike information criterion (AIC) value

Description

Retrieves the AIC value. If "train", "valid", and "xval" parameters are FALSE (default), then the training AIC value is returned. If more than one parameter is set to TRUE, then a named vector of AICs are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.aic(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|--|
| object | An H2OModel or H2OModelMetrics . |
| train | Retrieve the training AIC |
| valid | Retrieve the validation AIC |
| xval | Retrieve the cross-validation AIC |

Examples

```
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
p.sid <- h2o.runif(prostate.hex)
prostate.train <- h2o.assign(prostate.hex[p.sid > .2,], "prostate.train")
prostate.glm <- h2o.glm(x=3:7, y=2, training_frame=prostate.train)
aic.basic <- h2o.aic(prostate.glm)
print(aic.basic)
```

| | |
|---------|--|
| h2o.all | <i>Given a set of logical vectors, are all of the values true?</i> |
|---------|--|

Description

Given a set of logical vectors, are all of the values true?

Usage

```
h2o.all(x)
```

Arguments

| | |
|---|---------------------|
| x | An H2OFrame object. |
|---|---------------------|

See Also

[all](#) for the base R implementation.

| | |
|-------------|--|
| h2o.anomaly | <i>Anomaly Detection via H2O Deep Learning Model</i> |
|-------------|--|

Description

Detect anomalies in an H2O dataset using an H2O deep learning model with auto-encoding.

Usage

```
h2o.anomaly(object, data, per_feature = FALSE)
```

Arguments

| | |
|-------------|---|
| object | An H2OAutoEncoderModel object that represents the model to be used for anomaly detection. |
| data | An H2OFrame object. |
| per_feature | Whether to return the per-feature squared reconstruction error |

Value

Returns an H2OFrame object containing the reconstruction MSE or the per-feature squared error.

See Also

[h2o.deeplearning](#) for making an H2OAutoEncoderModel.

Examples

```
library(h2o)
h2o.init()
prosPath = system.file("extdata", "prostate.csv", package = "h2o")
prostate.hex = h2o.importFile(path = prosPath)
prostate.dl = h2o.deeplearning(x = 3:9, training_frame = prostate.hex, autoencoder = TRUE,
                             hidden = c(10, 10), epochs = 5)
prostate.anon = h2o.anomaly(prostate.dl, prostate.hex)
head(prostate.anon)
prostate.anon.per.feature = h2o.anomaly(prostate.dl, prostate.hex, per_feature=TRUE)
head(prostate.anon.per.feature)
```

h2o.any

Given a set of logical vectors, is at least one of the values true?

Description

Given a set of logical vectors, is at least one of the values true?

Usage

```
h2o.any(x)
```

Arguments

x An H2OFrame object.

See Also

[all](#) for the base R implementation.

h2o.anyFactor

Check H2OFrame columns for factors

Description

Determines if any column of an H2OFrame object contains categorical data.

Usage

```
h2o.anyFactor(x)
```

Arguments

x An H2OFrame object.

Value

Returns a logical value indicating whether any of the columns in x are factors.

Examples

```
library(h2o)
h2o.init()
irisPath <- system.file("extdata", "iris_wheader.csv", package="h2o")
iris.hex <- h2o.importFile(path = irisPath)
h2o.anyFactor(iris.hex)
```

| | |
|-------------|--------------------------------------|
| h2o.arrange | <i>Sorts an H2O frame by columns</i> |
|-------------|--------------------------------------|

Description

Sorts H2OFrame by the columns specified. H2OFrame can contain String columns but should not sort on any String columns. Otherwise, an error will be thrown. To sort column c1 in descending order, do desc(c1). Returns a new H2OFrame, like dplyr::arrange.

Usage

```
h2o.arrange(x, ...)
```

Arguments

| | |
|-----|----------------------------------|
| x | The H2OFrame input to be sorted. |
| ... | The column names to sort by. |

| | |
|-----------------|---------------------------------------|
| h2o.ascharacter | <i>Convert H2O Data to Characters</i> |
|-----------------|---------------------------------------|

Description

Convert H2O Data to Characters

Usage

```
h2o.ascharacter(x)
```

Arguments

| | |
|---|---------------------|
| x | An H2OFrame object. |
|---|---------------------|

See Also

[as.character](#) for the base R implementation.

| | |
|--------------|------------------------------------|
| h2o.asfactor | <i>Convert H2O Data to Factors</i> |
|--------------|------------------------------------|

Description

Convert H2O Data to Factors

Usage

```
h2o.asfactor(x)
```

Arguments

x An H2OFrame object.

See Also

[as.factor](#) for the base R implementation.

| | |
|---------------|-------------------------------------|
| h2o.asnumeric | <i>Convert H2O Data to Numerics</i> |
|---------------|-------------------------------------|

Description

Convert H2O Data to Numerics

Usage

```
h2o.asnumeric(x)
```

Arguments

x An H2OFrame object.

See Also

[as.numeric](#) for the base R implementation.

| | |
|------------|------------------------------|
| h2o.assign | <i>Rename an H2O object.</i> |
|------------|------------------------------|

Description

Makes a copy of the data frame and gives it the desired the key.

Usage

```
h2o.assign(data, key)
```

Arguments

| | |
|------|--|
| data | An H2OFrame object |
| key | The hex key to be associated with the H2O parsed data object |

| | |
|-------------|--|
| h2o.as_date | <i>Convert between character representations and objects of Date class</i> |
|-------------|--|

Description

Functions to convert between character representations and objects of class "Date" representing calendar dates.

Usage

```
h2o.as_date(x, format, ...)
```

Arguments

| | |
|--------|--|
| x | H2OFrame column of strings or factors to be converted |
| format | A character string indicating date pattern |
| ... | Further arguments to be passed from or to other methods. |

| | |
|---------|-------------------------|
| h2o.auc | <i>Retrieve the AUC</i> |
|---------|-------------------------|

Description

Retrieves the AUC value from an [H2OBinomialMetrics](#). If "train", "valid", and "xval" parameters are FALSE (default), then the training AUC value is returned. If more than one parameter is set to TRUE, then a named vector of AUCs are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.auc(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|---|
| object | An H2OBinomialMetrics object. |
| train | Retrieve the training AUC |
| valid | Retrieve the validation AUC |
| xval | Retrieve the cross-validation AUC |

See Also

[h2o.giniCoef](#) for the Gini coefficient, [h2o.mse](#) for MSE, and [h2o.metric](#) for the various threshold metrics. See [h2o.performance](#) for creating H2OModelMetrics objects.

Examples

```
library(h2o)
h2o.init()

prosPath <- system.file("extdata", "prostate.csv", package="h2o")
hex <- h2o.uploadFile(prosPath)

hex[,2] <- as.factor(hex[,2])
model <- h2o.gbm(x = 3:9, y = 2, training_frame = hex, distribution = "bernoulli")
perf <- h2o.performance(model, hex)
h2o.auc(perf)
```

| | |
|------------|-----------------------------------|
| h2o.automl | <i>Automatic Machine Learning</i> |
|------------|-----------------------------------|

Description

The Automatic Machine Learning (AutoML) function automates the supervised machine learning model training process. The current version of AutoML trains and cross-validates a Random Forest, an Extremely-Randomized Forest, a random grid of Gradient Boosting Machines (GBMs), a random grid of Deep Neural Nets, and then trains a Stacked Ensemble using all of the models.

Usage

```
h2o.automl(x, y, training_frame, validation_frame = NULL,
  leaderboard_frame = NULL, nfolds = 5, fold_column = NULL,
  weights_column = NULL, max_runtime_secs = 3600, max_models = NULL,
  stopping_metric = c("AUTO", "deviance", "logloss", "MSE", "RMSE", "MAE",
  "RMSLE", "AUC", "lift_top_group", "misclassification",
  "mean_per_class_error"), stopping_tolerance = NULL, stopping_rounds = 3,
  seed = NULL, project_name = NULL, exclude_algos = NULL)
```

Arguments

- | | |
|--------------------|---|
| x | A vector containing the names or indices of the predictor variables to use in building the model. If x is missing, then all columns except y are used. |
| y | The name or index of the response variable in the model. For classification, the y column must be a factor, otherwise regression will be performed. Indexes are 1-based in R. |
| training_frame | Training frame (H2OFrame or ID). |
| validation_frame | Validation frame (H2OFrame or ID); Optional. This frame is used for early stopping of individual models and early stopping of the grid searches (unless max_models or max_runtimes_secs overrides metric-based early stopping). |
| leaderboard_frame | Leaderboard frame (H2OFrame or ID); Optional. If provided, the Leaderboard will be scored using this data frame instead of using cross-validation metrics, which is the default. |
| nfolds | Number of folds for k-fold cross-validation. Defaults to 5. Use 0 to disable cross-validation; this will also disable Stacked Ensemble (thus decreasing the overall model performance). |
| fold_column | Column with cross-validation fold index assignment per observation; used to override the default, randomized, 5-fold cross-validation scheme for individual models in the AutoML run. |
| weights_column | Column with observation weights. Giving some observation a weight of zero is equivalent to excluding it from the dataset; giving an observation a relative weight of 2 is equivalent to repeating that row twice. Negative weights are not allowed. |
| max_runtime_secs | Maximum allowed runtime in seconds for the entire model training process. Use 0 to disable. Defaults to 3600 secs (1 hour). |
| max_models | Maximum number of models to build in the AutoML process (does not include Stacked Ensembles). Defaults to NULL. |
| stopping_metric | Metric to use for early stopping (AUTO is logloss for classification, deviance for regression). Must be one of "AUTO", "deviance", "logloss", "MSE", "RMSE", "MAE", "RMSLE", "AUC", "lift_top_group", "misclassification", "mean_per_class_error". Defaults to AUTO. |
| stopping_tolerance | Relative tolerance for metric-based stopping criterion (stop if relative improvement is not at least this much). This value defaults to 0.001 if the dataset is at least 1 million rows; otherwise it defaults to a bigger value determined by the size of the dataset and the non-NA-rate. In that case, the value is computed as $1/\sqrt{\text{nrows} * \text{non-NA-rate}}$. |

| | |
|-----------------|---|
| stopping_rounds | Integer. Early stopping based on convergence of stopping_metric. Stop if simple moving average of length k of the stopping_metric does not improve for k (stopping_rounds) scoring events. Defaults to 3 and must be a non-zero integer. Use 0 to disable early stopping. |
| seed | Integer. Set a seed for reproducibility. AutoML can only guarantee reproducibility if max_models or early stopping is used because max_runtime_secs is resource limited, meaning that if the resources are not the same between runs, AutoML may be able to train more models on one run vs another. |
| project_name | Character string to identify an AutoML project. Defaults to NULL, which means a project name will be auto-generated based on the training frame ID. |
| exclude_algos | Vector of character strings naming the algorithms to skip during the model-building phase. An example use is exclude_algos = c("GLM", "DeepLearning", "DRF"), and the full list of options is: "GLM", "GBM", "DRF" (Random Forest and Extremely-Randomized Trees), "DeepLearning" and "StackedEnsemble". Defaults to NULL, which means that all appropriate H2O algorithms will be used, if the search stopping criteria allow. Optional. |

Details

AutoML finds the best model, given a training frame and response, and returns an H2OAutoML object, which contains a leaderboard of all the models that were trained in the process, ranked by a default model performance metric.

Value

An [H2OAutoML](#) object.

Examples

```
library(h2o)
h2o.init()
votes_path <- system.file("extdata", "housevotes.csv", package = "h2o")
votes_hf <- h2o.uploadFile(path = votes_path, header = TRUE)
aml <- h2o.automl(y = "Class", training_frame = votes_hf, max_runtime_secs = 30)
```

h2o.betweenss

Get the between cluster sum of squares

Description

Get the between cluster sum of squares. If "train", "valid", and "xval" parameters are FALSE (default), then the training betweenss value is returned. If more than one parameter is set to TRUE, then a named vector of betweenss' are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.betweenss(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|--|
| object | An H2OClusteringModel object. |
| train | Retrieve the training between cluster sum of squares |
| valid | Retrieve the validation between cluster sum of squares |
| xval | Retrieve the cross-validation between cluster sum of squares |

| | |
|------------|--|
| h2o.biases | <i>Return the respective bias vector</i> |
|------------|--|

Description

Return the respective bias vector

Usage

```
h2o.biases(object, vector_id = 1)
```

Arguments

| | |
|-----------|---|
| object | An H2OModel or H2OModelMetrics |
| vector_id | An integer, ranging from 1 to number of layers + 1, that specifies the bias vector to return. |

| | |
|-------------|--------------------|
| h2o.bottomN | <i>H2O bottomN</i> |
|-------------|--------------------|

Description

bottomN function will grab the bottom N percent of values of a column and return it in a H2OFrame. Extract the top N percent of values of a column and return it in a H2OFrame.

Usage

```
h2o.bottomN(x, column, nPercent)
```

Arguments

| | |
|----------|---|
| x | an H2OFrame |
| column | is a column name or column index to grab the top N percent value from |
| nPercent | is a bottom percentage value to grab |

Value

An H2OFrame with 2 columns. The first column is the original row indices, second column contains the bottomN values

| | |
|-----------|--|
| h2o.cbind | <i>Combine H2O Datasets by Columns</i> |
|-----------|--|

Description

Takes a sequence of H2O data sets and combines them by column

Usage

```
h2o.cbind(...)
```

Arguments

... A sequence of H2OFrame arguments. All datasets must exist on the same H2O instance (IP and port) and contain the same number of rows.

Value

An H2OFrame object containing the combined ... arguments column-wise.

See Also

[cbind](#) for the base R method.

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
prostate.cbind <- h2o.cbind(prostate.hex, prostate.hex)
head(prostate.cbind)
```

| | |
|-------------|--|
| h2o.ceiling | <i>Take a single numeric argument and return a numeric vector with the smallest integers</i> |
|-------------|--|

Description

ceiling takes a single numeric argument x and returns a numeric vector containing the smallest integers not less than the corresponding elements of x.

Usage

```
h2o.ceiling(x)
```

Arguments

x An H2OFrame object.

See Also

[ceiling](#) for the base R implementation.

| | |
|-------------|-----------------------------------|
| h2o.centers | <i>Retrieve the Model Centers</i> |
|-------------|-----------------------------------|

Description

Retrieve the Model Centers

Usage

```
h2o.centers(object)
```

Arguments

object An [H2OClusteringModel](#) object.

| | |
|----------------|---------------------------------------|
| h2o.centersSTD | <i>Retrieve the Model Centers STD</i> |
|----------------|---------------------------------------|

Description

Retrieve the Model Centers STD

Usage

```
h2o.centersSTD(object)
```

Arguments

object An [H2OClusteringModel](#) object.

| | |
|--------------------|-------------------------------------|
| h2o.centroid_stats | <i>Retrieve centroid statistics</i> |
|--------------------|-------------------------------------|

Description

Retrieve the centroid statistics. If "train", "valid", and "xval" parameters are FALSE (default), then the training centroid stats value is returned. If more than one parameter is set to TRUE, then a named list of centroid stats data frames are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.centroid_stats(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|---|
| object | An H2OClusteringModel object. |
| train | Retrieve the training centroid statistics |
| valid | Retrieve the validation centroid statistics |
| xval | Retrieve the cross-validation centroid statistics |

| | |
|--------------|------------------------------|
| h2o.clearLog | <i>Delete All H2O R Logs</i> |
|--------------|------------------------------|

Description

Clear all H2O R command and error response logs from the local disk. Used primarily for debugging purposes.

Usage

```
h2o.clearLog()
```

See Also

[h2o.startLogging](#), [h2o.stopLogging](#), [h2o.openLog](#)

Examples

```
library(h2o)
h2o.init()
h2o.startLogging()
ausPath = system.file("extdata", "australia.csv", package="h2o")
australia.hex = h2o.importFile(path = ausPath)
h2o.stopLogging()
h2o.clearLog()
```

| | |
|-----------------|-------------------------------|
| h2o.clusterInfo | <i>Print H2O cluster info</i> |
|-----------------|-------------------------------|

Description

Print H2O cluster info

Usage

```
h2o.clusterInfo()
```

| | |
|-----------------|---|
| h2o.clusterIsUp | <i>Determine if an H2O cluster is up or not</i> |
|-----------------|---|

Description

Determine if an H2O cluster is up or not

Usage

```
h2o.clusterIsUp(conn = h2o.getConnection())
```

Arguments

| | |
|------|----------------------|
| conn | H2OConnection object |
|------|----------------------|

Value

TRUE if the cluster is up; FALSE otherwise

| | |
|-------------------|---|
| h2o.clusterStatus | <i>Return the status of the cluster</i> |
|-------------------|---|

Description

Retrieve information on the status of the cluster running H2O.

Usage

```
h2o.clusterStatus()
```

See Also

[H2OConnection](#), [h2o.init](#)

Examples

```
h2o.init()  
h2o.clusterStatus()
```

| | |
|-------------------|-----------------------------------|
| h2o.cluster_sizes | <i>Retrieve the cluster sizes</i> |
|-------------------|-----------------------------------|

Description

Retrieve the cluster sizes. If "train", "valid", and "xval" parameters are FALSE (default), then the training cluster sizes value is returned. If more than one parameter is set to TRUE, then a named list of cluster size vectors are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.cluster_sizes(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|---|
| object | An H2OClusteringModel object. |
| train | Retrieve the training cluster sizes |
| valid | Retrieve the validation cluster sizes |
| xval | Retrieve the cross-validation cluster sizes |

| | |
|----------|--|
| h2o.coef | <i>Return the coefficients that can be applied to the non-standardized data.</i> |
|----------|--|

Description

Note: standardize = True by default. If set to False, then coef() returns the coefficients that are fit directly.

Usage

```
h2o.coef(object)
```

Arguments

| | |
|--------|-------------------------------------|
| object | an H2OModel object. |
|--------|-------------------------------------|

| | |
|---------------|---|
| h2o.coef_norm | <i>Return coefficients fitted on the standardized data (requires standardize = True, which is on by default). These coefficients can be used to evaluate variable importance.</i> |
|---------------|---|

Description

Return coefficients fitted on the standardized data (requires standardize = True, which is on by default). These coefficients can be used to evaluate variable importance.

Usage

```
h2o.coef_norm(object)
```

Arguments

object an [H2OModel](#) object.

| | |
|--------------|---|
| h2o.colnames | <i>Return column names of an H2OFrame</i> |
|--------------|---|

Description

Return column names of an H2OFrame

Usage

```
h2o.colnames(x)
```

Arguments

x An H2OFrame object.

See Also

[colnames](#) for the base R implementation.

h2o.columns_by_type *Obtain a list of columns that are specified by 'coltype'*

Description

Obtain a list of columns that are specified by 'coltype'

Usage

```
h2o.columns_by_type(object, coltype = "numeric", ...)
```

Arguments

| | |
|---------|--|
| object | H2OFrame object |
| coltype | A character string indicating which column type to filter by. This must be one of the following: "numeric" - Numeric, but not categorical or time "categorical" - Integer, with a categorical/factor String mapping "string" - String column "time" - Long msec since the Unix Epoch - with a variety of display/parse options "uuid" - UUID "bad" - No none-NA rows (triple negative! all NAs or zero rows) |
| ... | Ignored |

Value

A list of column indices that correspond to "type"

Examples

```
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
h2o.columns_by_type(prostate.hex,coltype="numeric")
```

h2o.computeGram *Compute weighted gram matrix.*

Description

Compute weighted gram matrix.

Usage

```
h2o.computeGram(X, weights = "", use_all_factor_levels = FALSE,
  standardize = TRUE, skip_missing = FALSE)
```

Arguments

| | |
|-----------------------|---|
| X | an H2OModel corresponding to H2O frame. |
| weights | character corresponding to name of weight vector in frame. |
| use_all_factor_levels | logical flag telling h2o whether or not to skip first level of categorical variables during one-hot encoding. |
| standardize | logical flag telling h2o whether or not to standardize data |
| skip_missing | logical flag telling h2o whether skip rows with missing data or impute them with mean |

h2o.confusionMatrix *Access H2O Confusion Matrices*

Description

Retrieve either a single or many confusion matrices from H2O objects.

Usage

```
h2o.confusionMatrix(object, ...)

## S4 method for signature 'H2OModel'
h2o.confusionMatrix(object, newdata, valid = FALSE, ...)

## S4 method for signature 'H2OModelMetrics'
h2o.confusionMatrix(object, thresholds = NULL,
  metrics = NULL)
```

Arguments

| | |
|------------|--|
| object | Either an H2OModel object or an H2OModelMetrics object. |
| ... | Extra arguments for extracting train or valid confusion matrices. |
| newdata | An H2OFrame object that can be scored on. Requires a valid response column. |
| valid | Retrieve the validation metric. |
| thresholds | (Optional) A value or a list of valid values between 0.0 and 1.0. This value is only used in the case of H2OBinomialMetrics objects. |
| metrics | (Optional) A metric or a list of valid metrics ("min_per_class_accuracy", "absolute_mcc", "tnr", "fnr", "fpr", "tpr", "precision", "accuracy", "f0point5", "f2", "f1"). This value is only used in the case of H2OBinomialMetrics objects. |

Details

The [H2OModelMetrics](#) version of this function will only take [H2OBinomialMetrics](#) or [H2OMultinomialMetrics](#) objects. If no threshold is specified, all possible thresholds are selected.

Value

Calling this function on [H2OModel](#) objects returns a confusion matrix corresponding to the [predict](#) function. If used on an [H2OBinomialMetrics](#) object, returns a list of matrices corresponding to the number of thresholds specified.

See Also

[predict](#) for generating prediction frames, [h2o.performance](#) for creating [H2OModelMetrics](#).

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
hex <- h2o.uploadFile(prosPath)
hex[,2] <- as.factor(hex[,2])
model <- h2o.gbm(x = 3:9, y = 2, training_frame = hex, distribution = "bernoulli")
h2o.confusionMatrix(model, hex)
# Generating a ModelMetrics object
perf <- h2o.performance(model, hex)
h2o.confusionMatrix(perf)
```

| | |
|-------------|---|
| h2o.connect | <i>Connect to a running H2O instance.</i> |
|-------------|---|

Description

Connect to a running H2O instance.

Usage

```
h2o.connect(ip = "localhost", port = 54321, strict_version_check = TRUE,
  proxy = NA_character_, https = FALSE, insecure = FALSE,
  username = NA_character_, password = NA_character_,
  cookies = NA_character_, context_path = NA_character_, config = NULL)
```

Arguments

| | |
|----------------------|--|
| ip | Object of class character representing the IP address of the server where H2O is running. |
| port | Object of class numeric representing the port number of the H2O server. |
| strict_version_check | (Optional) Setting this to FALSE is unsupported and should only be done when advised by technical support. |
| proxy | (Optional) A character string specifying the proxy path. |
| https | (Optional) Set this to TRUE to use https instead of http. |
| insecure | (Optional) Set this to TRUE to disable SSL certificate checking. |
| username | (Optional) Username to login with. |
| password | (Optional) Password to login with. |
| cookies | (Optional) Vector(or list) of cookies to add to request. |
| context_path | (Optional) The last part of connection URL: http://<ip>:<port>/<context_path> |
| config | (Optional) A list describing connection parameters. |

Value

an instance of H2OConnection object representing a connection to the running H2O instance.

Examples

```
## Not run:
library(h2o)
# Try to connect to a H2O instance running at http://localhost:54321/cluster_X
# If not found, start a local H2O instance from R with the default settings.
#h2o.connect(ip = "localhost", port = 54321, context_path = "cluster_X")
# Or
#config = list(ip = "localhost", port = 54321, context_path = "cluster_X")
#h2o.connect(config = config)

# Skip strict version check during connecting to the instance
#h2o.connect(config = c(strict_version_check = FALSE, config))

## End(Not run)
```

h2o.cor

Correlation of columns.

Description

Compute the correlation matrix of one or two H2OFrames.

Usage

```
h2o.cor(x, y = NULL, na.rm = FALSE, use)

cor(x, ...)
```

Arguments

| | |
|-------|---|
| x | An H2OFrame object. |
| y | NULL (default) or an H2OFrame. The default is equivalent to y = x. |
| na.rm | logical. Should missing values be removed? |
| use | An optional character string indicating how to handle missing values. This must be one of the following: "everything" - outputs NaNs whenever one of its contributing observations is missing "all.obs" - presence of missing observations will throw an error "complete.obs" - discards missing values along with all observations in their rows so that only complete observations are used |
| ... | Further arguments to be passed down from other methods. |

Examples

```
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
cor(prostate.hex$AGE)
```

| | |
|---------|--------------------------------|
| h2o.cos | <i>Compute the cosine of x</i> |
|---------|--------------------------------|

Description

Compute the cosine of x

Usage

```
h2o.cos(x)
```

Arguments

x An H2OFrame object.

See Also

[cos](#) for the base R implementation.

| | |
|----------|---|
| h2o.cosh | <i>Compute the hyperbolic cosine of x</i> |
|----------|---|

Description

Compute the hyperbolic cosine of x

Usage

```
h2o.cosh(x)
```

Arguments

x An H2OFrame object.

See Also

[cosh](#) for the base R implementation.

| | |
|-----------|--|
| h2o.coxph | <i>Trains a Cox Proportional Hazards Model (CoxPH) on an H2O dataset</i> |
|-----------|--|

Description

Trains a Cox Proportional Hazards Model (CoxPH) on an H2O dataset

Usage

```
h2o.coxph(x, event_column, training_frame, model_id = NULL,
          start_column = NULL, stop_column = NULL, weights_column = NULL,
          offset_column = NULL, ties = c("efron", "breslow"), init = 0,
          lre_min = 9, iter_max = 20)
```

Arguments

| | |
|----------------|---|
| x | (Optional) A vector containing the names or indices of the predictor variables to use in building the model. If x is missing, then all columns except event_column, start_column and stop_column are used. |
| event_column | The name of binary data column in the training frame indicating the occurrence of an event. |
| training_frame | Id of the training data frame. |
| model_id | Destination id for this model; auto-generated if not specified. |
| start_column | start_column |
| stop_column | stop_column |
| weights_column | Column with observation weights. Giving some observation a weight of zero is equivalent to excluding it from the dataset; giving an observation a relative weight of 2 is equivalent to repeating that row twice. Negative weights are not allowed. Note: Weights are per-row observation weights and do not increase the size of the data frame. This is typically the number of times a row is repeated, but non-integer values are supported as well. During training, rows with higher weights matter more, due to the larger loss function pre-factor. |
| offset_column | Offset column. This will be added to the combination of columns before applying the link function. |
| ties | ties Must be one of: "efron", "breslow". Defaults to efron. |
| init | init Defaults to 0. |
| lre_min | lre_min Defaults to 9. |
| iter_max | iter_max Defaults to 20. |

h2o.createFrame

*Data H2OFrame Creation in H2O***Description**

Creates a data frame in H2O with real-valued, categorical, integer, and binary columns specified by the user.

Usage

```
h2o.createFrame(rows = 10000, cols = 10, randomize = TRUE, value = 0,
  real_range = 100, categorical_fraction = 0.2, factors = 100,
  integer_fraction = 0.2, integer_range = 100, binary_fraction = 0.1,
  binary_ones_fraction = 0.02, time_fraction = 0, string_fraction = 0,
  missing_fraction = 0.01, response_factors = 2, has_response = FALSE,
  seed, seed_for_column_types)
```

Arguments

| | |
|----------------------|---|
| rows | The number of rows of data to generate. |
| cols | The number of columns of data to generate. Excludes the response column if <code>has_response = TRUE</code> . |
| randomize | A logical value indicating whether data values should be randomly generated. This must be <code>TRUE</code> if either <code>categorical_fraction</code> or <code>integer_fraction</code> is non-zero. |
| value | If <code>randomize = FALSE</code> , then all real-valued entries will be set to this value. |
| real_range | The range of randomly generated real values. |
| categorical_fraction | The fraction of total columns that are categorical. |
| factors | The number of (unique) factor levels in each categorical column. |
| integer_fraction | The fraction of total columns that are integer-valued. |
| integer_range | The range of randomly generated integer values. |
| binary_fraction | The fraction of total columns that are binary-valued. |
| binary_ones_fraction | The fraction of values in a binary column that are set to 1. |
| time_fraction | The fraction of randomly created date/time columns. |
| string_fraction | The fraction of randomly created string columns. |
| missing_fraction | The fraction of total entries in the data frame that are set to NA. |
| response_factors | If <code>has_response = TRUE</code> , then this is the number of factor levels in the response column. |
| has_response | A logical value indicating whether an additional response column should be prepended to the final H2O data frame. If set to <code>TRUE</code> , the total number of columns will be <code>cols+1</code> . |

seed A seed used to generate random values when `randomize = TRUE`.
seed_for_column_types A seed used to generate random column types when `randomize = TRUE`.

Value

Returns an `H2OFrame` object.

Examples

```
library(h2o)
h2o.init()
hex <- h2o.createFrame(rows = 1000, cols = 100, categorical_fraction = 0.1,
                       factors = 5, integer_fraction = 0.5, integer_range = 1,
                       has_response = TRUE)

head(hex)
summary(hex)

hex2 <- h2o.createFrame(rows = 100, cols = 10, randomize = FALSE, value = 5,
                       categorical_fraction = 0, integer_fraction = 0)

summary(hex2)
```

`h2o.cross_validation_fold_assignment`

Retrieve the cross-validation fold assignment

Description

Retrieve the cross-validation fold assignment

Usage

```
h2o.cross_validation_fold_assignment(object)
```

Arguments

object An [H2OModel](#) object.

Value

Returns a `H2OFrame`

`h2o.cross_validation_holdout_predictions`

Retrieve the cross-validation holdout predictions

Description

Retrieve the cross-validation holdout predictions

Usage

`h2o.cross_validation_holdout_predictions(object)`

Arguments

`object` An [H2OModel](#) object.

Value

Returns a H2OFrame

`h2o.cross_validation_models`

Retrieve the cross-validation models

Description

Retrieve the cross-validation models

Usage

`h2o.cross_validation_models(object)`

Arguments

`object` An [H2OModel](#) object.

Value

Returns a list of H2OModel objects

h2o.cross_validation_predictions
Retrieve the cross-validation predictions

Description

Retrieve the cross-validation predictions

Usage

```
h2o.cross_validation_predictions(object)
```

Arguments

object An [H2OModel](#) object.

Value

Returns a list of H2OFrame objects

h2o.cummax *Return the cumulative max over a column or across a row*

Description

Return the cumulative max over a column or across a row

Usage

```
h2o.cummax(x, axis = 0)
```

Arguments

x An H2OFrame object.
axis An int that indicates whether to do down a column (0) or across a row (1).

See Also

[cummax](#) for the base R implementation.

| | |
|------------|--|
| h2o.cummin | <i>Return the cumulative min over a column or across a row</i> |
|------------|--|

Description

Return the cumulative min over a column or across a row

Usage

```
h2o.cummin(x, axis = 0)
```

Arguments

| | |
|------|--|
| x | An H2OFrame object. |
| axis | An int that indicates whether to do down a column (0) or across a row (1). |

See Also

[cummin](#) for the base R implementation.

| | |
|-------------|--|
| h2o.cumprod | <i>Return the cumulative product over a column or across a row</i> |
|-------------|--|

Description

Return the cumulative product over a column or across a row

Usage

```
h2o.cumprod(x, axis = 0)
```

Arguments

| | |
|------|--|
| x | An H2OFrame object. |
| axis | An int that indicates whether to do down a column (0) or across a row (1). |

See Also

[cumprod](#) for the base R implementation.

| | |
|------------|--|
| h2o.cumsum | <i>Return the cumulative sum over a column or across a row</i> |
|------------|--|

Description

Return the cumulative sum over a column or across a row

Usage

```
h2o.cumsum(x, axis = 0)
```

Arguments

| | |
|------|--|
| x | An H2OFrame object. |
| axis | An int that indicates whether to do down a column (0) or across a row (1). |

See Also

[cumsum](#) for the base R implementation.

| | |
|---------|---------------------------------------|
| h2o.cut | <i>Cut H2O Numeric Data to Factor</i> |
|---------|---------------------------------------|

Description

Divides the range of the H2O data into intervals and codes the values according to which interval they fall in. The leftmost interval corresponds to the level one, the next is level two, etc.

Usage

```
h2o.cut(x, breaks, labels = NULL, include.lowest = FALSE, right = TRUE,
        dig.lab = 3, ...)
```

```
## S3 method for class 'H2OFrame'
cut(x, breaks, labels = NULL, include.lowest = FALSE,
    right = TRUE, dig.lab = 3, ...)
```

Arguments

| | |
|----------------|--|
| x | An H2OFrame object with a single numeric column. |
| breaks | A numeric vector of two or more unique cut points. |
| labels | Labels for the levels of the resulting category. By default, labels are constructed using "(a,b]" interval notation. |
| include.lowest | Logical, indicating if an 'x[i]' equal to the lowest (or highest, for right = FALSE) 'breaks' value should be included |
| right | Logical, indicating if the intervals should be closed on the right (opened on the left) or vice versa. |
| dig.lab | Integer which is used when labels are not given, determines the number of digits used in formatting the break numbers. |
| ... | Further arguments passed to or from other methods. |

Value

Returns an H2OFrame object containing the factored data with intervals as levels.

Examples

```
library(h2o)
h2o.init()
irisPath <- system.file("extdata", "iris_wheader.csv", package="h2o")
iris.hex <- h2o.uploadFile(path = irisPath, destination_frame = "iris.hex")
summary(iris.hex)

# Cut sepal length column into intervals determined by min/max/quantiles
sepal_len.cut <- cut(iris.hex$sepal_len, c(4.2, 4.8, 5.8, 6, 8))
head(sepal_len.cut)
summary(sepal_len.cut)
```

h2o.day

Convert Milliseconds to Day of Month in H2O Datasets

Description

Converts the entries of an H2OFrame object from milliseconds to days of the month (on a 1 to 31 scale).

Usage

```
h2o.day(x)

day(x)

## S3 method for class 'H2OFrame'
day(x)
```

Arguments

x An H2OFrame object.

Value

An H2OFrame object containing the entries of x converted to days of the month.

See Also

[h2o.month](#)

| | |
|---------------|--|
| h2o.dayOfWeek | <i>Convert Milliseconds to Day of Week in H2O Datasets</i> |
|---------------|--|

Description

Converts the entries of an H2OFrame object from milliseconds to days of the week (on a 0 to 6 scale).

Usage

```
h2o.dayOfWeek(x)

dayOfWeek(x)

## S3 method for class 'H2OFrame'
dayOfWeek(x)
```

Arguments

x An H2OFrame object.

Value

An H2OFrame object containing the entries of x converted to days of the week.

See Also

[h2o.day](#), [h2o.month](#)

| | |
|---------|-----------------------------------|
| h2o.dct | <i>Compute DCT of an H2OFrame</i> |
|---------|-----------------------------------|

Description

Compute the Discrete Cosine Transform of every row in the H2OFrame

Usage

```
h2o.dct(data, destination_frame, dimensions, inverse = FALSE)
```

Arguments

| | |
|-------------------|--|
| data | An H2OFrame object representing the dataset to transform |
| destination_frame | A frame ID for the result |
| dimensions | An array containing the 3 integer values for height, width, depth of each sample. The product of HxWxD must total up to less than the number of columns. For 1D, use c(L,1,1), for 2D, use C(N,M,1). |
| inverse | Whether to perform the inverse transform |

Value

Returns an H2OFrame object.

Examples

```
library(h2o)
h2o.init()
df <- h2o.createFrame(rows = 1000, cols = 8*16*24,
                      categorical_fraction = 0, integer_fraction = 0, missing_fraction = 0)
df1 <- h2o.dct(data=df, dimensions=c(8*16*24,1,1))
df2 <- h2o.dct(data=df1,dimensions=c(8*16*24,1,1),inverse=TRUE)
max(abs(df1-df2))

df1 <- h2o.dct(data=df, dimensions=c(8*16,24,1))
df2 <- h2o.dct(data=df1,dimensions=c(8*16,24,1),inverse=TRUE)
max(abs(df1-df2))

df1 <- h2o.dct(data=df, dimensions=c(8,16,24))
df2 <- h2o.dct(data=df1,dimensions=c(8,16,24),inverse=TRUE)
max(abs(df1-df2))
```

h2o.ddply

Split H2O Dataset, Apply Function, and Return Results

Description

For each subset of an H2O data set, apply a user-specified function, then combine the results. This is an experimental feature.

Usage

```
h2o.ddply(X, .variables, FUN, ..., .progress = "none")
```

Arguments

| | |
|------------|---|
| X | An H2OFrame object to be processed. |
| .variables | Variables to split X by, either the indices or names of a set of columns. |
| FUN | Function to apply to each subset grouping. |
| ... | Additional arguments passed on to FUN. |
| .progress | Name of the progress bar to use. #TODO: (Currently unimplemented) |

Value

Returns an H2OFrame object containing the results from the split/apply operation, arranged

See Also

[ddply](#) for the plyr library implementation.

Examples

```

library(h2o)
h2o.init()

# Import iris dataset to H2O
irisPath <- system.file("extdata", "iris_wheader.csv", package = "h2o")
iris.hex <- h2o.uploadFile(path = irisPath, destination_frame = "iris.hex")
# Add function taking mean of sepal_len column
fun <- function(df) { sum(df[,1], na.rm = TRUE)/nrow(df) }
# Apply function to groups by class of flower
# uses h2o's ddply, since iris.hex is an H2OFrame object
res <- h2o.ddply(iris.hex, "class", fun)
head(res)

```

h2o.decryptionSetup *Setup a Decryption Tool*

Description

If your source file is encrypted - setup a Decryption Tool and then provide the reference (result of this function) to the import functions.

Usage

```

h2o.decryptionSetup(keystore, keystore_type = "JCEKS",
  key_alias = NA_character_, password = NA_character_, decrypt_tool = "",
  decrypt_impl = "water.parser.GenericDecryptionTool",
  cipher_spec = NA_character_)

```

Arguments

| | |
|---------------|--|
| keystore | An H2OFrame object referencing a loaded Java Keystore (see example). |
| keystore_type | (Optional) Specification of Keystore type, defaults to JCEKS. |
| key_alias | Which key from the keystore to use for decryption. |
| password | Password to the keystore and the key. |
| decrypt_tool | (Optional) Name of the decryption tool. |
| decrypt_impl | (Optional) Java class name implementing the Decryption Tool. |
| cipher_spec | Specification of a cipher (eg.: AES/ECB/PKCS5Padding). |

See Also

[h2o.importFile](#), [h2o.parseSetup](#)

Examples

```
## Not run:
library(h2o)
h2o.init()
ksPath <- system.file("extdata", "keystore.jks", package = "h2o")
keystore <- h2o.importFile(path = ksPath, parse = FALSE) # don't parse, keep as a binary file
cipher <- "AES/ECB/PKCS5Padding"
pwd <- "Password123"
kAlias <- "secretKeyAlias"
dt <- h2o.decryptionSetup(keystore, key_alias = kAlias, password = pwd, cipher_spec = cipher)
dataPath <- system.file("extdata", "prostate.csv.aes", package = "h2o")
data <- h2o.importFile(dataPath, decrypt_tool = dt)
summary(data)

## End(Not run)
```

h2o.deepfeatures

Feature Generation via H2O Deep Learning or DeepWater Model

Description

Extract the non-linear feature from an H2O data set using an H2O deep learning model.

Usage

```
h2o.deepfeatures(object, data, layer)
```

Arguments

| | |
|--------|--|
| object | An H2OModel object that represents the deep learning model to be used for feature extraction. |
| data | An H2OFrame object. |
| layer | Index (for DeepLearning , integer) or Name (for DeepWater , String) of the hidden layer to extract |

Value

Returns an [H2OFrame](#) object with as many features as the number of units in the hidden layer of the specified index.

See Also

[link{h2o.deeplearning}](#) for making H2O Deep Learning models.

[link{h2o.deepwater}](#) for making H2O DeepWater models.

Examples

```

library(h2o)
h2o.init()
prosPath = system.file("extdata", "prostate.csv", package = "h2o")
prostate.hex = h2o.importFile(path = prosPath)
prostate.dl = h2o.deeplearning(x = 3:9, y = 2, training_frame = prostate.hex,
                             hidden = c(100, 200), epochs = 5)
prostate.deepfeatures_layer1 = h2o.deepfeatures(prostate.dl, prostate.hex, layer = 1)
prostate.deepfeatures_layer2 = h2o.deepfeatures(prostate.dl, prostate.hex, layer = 2)
head(prostate.deepfeatures_layer1)
head(prostate.deepfeatures_layer2)

#if (h2o.deepwater.available()) {
# prostate.dl = h2o.deepwater(x = 3:9, y = 2, backend="mxnet", training_frame = prostate.hex,
#                             hidden = c(100, 200), epochs = 5)
# prostate.deepfeatures_layer1 =
#   h2o.deepfeatures(prostate.dl, prostate.hex, layer = "fc1_w")
# prostate.deepfeatures_layer2 =
#   h2o.deepfeatures(prostate.dl, prostate.hex, layer = "fc2_w")
# head(prostate.deepfeatures_layer1)
# head(prostate.deepfeatures_layer2)
#}

```

h2o.deeplearning

*Build a Deep Neural Network model using CPUs***Description**

Builds a feed-forward multilayer artificial neural network on an H2OFrame.

Usage

```

h2o.deeplearning(x, y, training_frame, model_id = NULL,
                validation_frame = NULL, nfolds = 0,
                keep_cross_validation_predictions = FALSE,
                keep_cross_validation_fold_assignment = FALSE, fold_assignment = c("AUTO",
                "Random", "Modulo", "Stratified"), fold_column = NULL,
                ignore_const_cols = TRUE, score_each_iteration = FALSE,
                weights_column = NULL, offset_column = NULL, balance_classes = FALSE,
                class_sampling_factors = NULL, max_after_balance_size = 5,
                max_hit_ratio_k = 0, checkpoint = NULL, pretrained_autoencoder = NULL,
                overwrite_with_best_model = TRUE, use_all_factor_levels = TRUE,
                standardize = TRUE, activation = c("Tanh", "TanhWithDropout", "Rectifier",
                "RectifierWithDropout", "Maxout", "MaxoutWithDropout"), hidden = c(200,
                200), epochs = 10, train_samples_per_iteration = -2,
                target_ratio_comm_to_comp = 0.05, seed = -1, adaptive_rate = TRUE,
                rho = 0.99, epsilon = 1e-08, rate = 0.005, rate_annealing = 1e-06,
                rate_decay = 1, momentum_start = 0, momentum_ramp = 1e+06,
                momentum_stable = 0, nesterov_accelerated_gradient = TRUE,
                input_dropout_ratio = 0, hidden_dropout_ratios = NULL, l1 = 0, l2 = 0,

```

```

max_w2 = 3.4028235e+38, initial_weight_distribution = c("UniformAdaptive",
"Uniform", "Normal"), initial_weight_scale = 1, initial_weights = NULL,
initial_biases = NULL, loss = c("Automatic", "CrossEntropy", "Quadratic",
"Huber", "Absolute", "Quantile"), distribution = c("AUTO", "bernoulli",
"multinomial", "gaussian", "poisson", "gamma", "tweedie", "laplace",
"quantile", "huber"), quantile_alpha = 0.5, tweedie_power = 1.5,
huber_alpha = 0.9, score_interval = 5, score_training_samples = 10000,
score_validation_samples = 0, score_duty_cycle = 0.1,
classification_stop = 0, regression_stop = 1e-06, stopping_rounds = 5,
stopping_metric = c("AUTO", "deviance", "logloss", "MSE", "RMSE", "MAE",
"RMSLE", "AUC", "lift_top_group", "misclassification",
"mean_per_class_error"), stopping_tolerance = 0, max_runtime_secs = 0,
score_validation_sampling = c("Uniform", "Stratified"),
diagnostics = TRUE, fast_mode = TRUE, force_load_balance = TRUE,
variable_importances = TRUE, replicate_training_data = TRUE,
single_node_mode = FALSE, shuffle_training_data = FALSE,
missing_values_handling = c("MeanImputation", "Skip"), quiet_mode = FALSE,
autoencoder = FALSE, sparse = FALSE, col_major = FALSE,
average_activation = 0, sparsity_beta = 0,
max_categorical_features = 2147483647, reproducible = FALSE,
export_weights_and_biases = FALSE, mini_batch_size = 1,
categorical_encoding = c("AUTO", "Enum", "OneHotInternal", "OneHotExplicit",
"Binary", "Eigen", "LabelEncoder", "SortByResponse", "EnumLimited"),
elastic_averaging = FALSE, elastic_averaging_moving_rate = 0.9,
elastic_averaging_regularization = 0.001, verbose = FALSE)

```

Arguments

| | |
|---------------------------------------|--|
| x | (Optional) A vector containing the names or indices of the predictor variables to use in building the model. If x is missing, then all columns except y are used. |
| y | The name or column index of the response variable in the data. The response must be either a numeric or a categorical/factor variable. If the response is numeric, then a regression model will be trained, otherwise it will train a classification model. |
| training_frame | Id of the training data frame. |
| model_id | Destination id for this model; auto-generated if not specified. |
| validation_frame | Id of the validation data frame. |
| nfolds | Number of folds for K-fold cross-validation (0 to disable or >= 2). Defaults to 0. |
| keep_cross_validation_predictions | Logical. Whether to keep the predictions of the cross-validation models. Defaults to FALSE. |
| keep_cross_validation_fold_assignment | Logical. Whether to keep the cross-validation fold assignment. Defaults to FALSE. |
| fold_assignment | Cross-validation fold assignment scheme, if fold_column is not specified. The 'Stratified' option will stratify the folds based on the response variable, for classification problems. Must be one of: "AUTO", "Random", "Modulo", "Stratified". Defaults to AUTO. |

| | |
|--|---|
| <code>fold_column</code> | Column with cross-validation fold index assignment per observation. |
| <code>ignore_const_cols</code> | Logical. Ignore constant columns. Defaults to TRUE. |
| <code>score_each_iteration</code> | Logical. Whether to score during each iteration of model training. Defaults to FALSE. |
| <code>weights_column</code> | Column with observation weights. Giving some observation a weight of zero is equivalent to excluding it from the dataset; giving an observation a relative weight of 2 is equivalent to repeating that row twice. Negative weights are not allowed. Note: Weights are per-row observation weights and do not increase the size of the data frame. This is typically the number of times a row is repeated, but non-integer values are supported as well. During training, rows with higher weights matter more, due to the larger loss function pre-factor. |
| <code>offset_column</code> | Offset column. This will be added to the combination of columns before applying the link function. |
| <code>balance_classes</code> | Logical. Balance training data class counts via over/under-sampling (for imbalanced data). Defaults to FALSE. |
| <code>class_sampling_factors</code> | Desired over/under-sampling ratios per class (in lexicographic order). If not specified, sampling factors will be automatically computed to obtain class balance during training. Requires <code>balance_classes</code> . |
| <code>max_after_balance_size</code> | Maximum relative size of the training data after balancing class counts (can be less than 1.0). Requires <code>balance_classes</code> . Defaults to 5.0. |
| <code>max_hit_ratio_k</code> | Max. number (top K) of predictions to use for hit ratio computation (for multi-class only, 0 to disable). Defaults to 0. |
| <code>checkpoint</code> | Model checkpoint to resume training with. |
| <code>pretrained_autoencoder</code> | Pretrained autoencoder model to initialize this model with. |
| <code>overwrite_with_best_model</code> | Logical. If enabled, override the final model with the best model found during training. Defaults to TRUE. |
| <code>use_all_factor_levels</code> | Logical. Use all factor levels of categorical variables. Otherwise, the first factor level is omitted (without loss of accuracy). Useful for variable importances and auto-enabled for autoencoder. Defaults to TRUE. |
| <code>standardize</code> | Logical. If enabled, automatically standardize the data. If disabled, the user must provide properly scaled input data. Defaults to TRUE. |
| <code>activation</code> | Activation function. Must be one of: "Tanh", "TanhWithDropout", "Rectifier", "RectifierWithDropout", "Maxout", "MaxoutWithDropout". Defaults to Rectifier. |
| <code>hidden</code> | Hidden layer sizes (e.g. [100, 100]). Defaults to [200, 200]. |
| <code>epochs</code> | How many times the dataset should be iterated (streamed), can be fractional. Defaults to 10. |
| <code>train_samples_per_iteration</code> | Number of training samples (globally) per MapReduce iteration. Special values are 0: one epoch, -1: all available data (e.g., replicated training data), -2: automatic. Defaults to -2. |

| | |
|-------------------------------|---|
| target_ratio_comm_to_comp | Target ratio of communication overhead to computation. Only for multi-node operation and train_samples_per_iteration = -2 (auto-tuning). Defaults to 0.05. |
| seed | Seed for random numbers (affects certain parts of the algo that are stochastic and those might or might not be enabled by default) Note: only reproducible when running single threaded. Defaults to -1 (time-based random number). |
| adaptive_rate | Logical. Adaptive learning rate. Defaults to TRUE. |
| rho | Adaptive learning rate time decay factor (similarity to prior updates). Defaults to 0.99. |
| epsilon | Adaptive learning rate smoothing factor (to avoid divisions by zero and allow progress). Defaults to 1e-08. |
| rate | Learning rate (higher => less stable, lower => slower convergence). Defaults to 0.005. |
| rate_annealing | Learning rate annealing: rate / (1 + rate_annealing * samples). Defaults to 1e-06. |
| rate_decay | Learning rate decay factor between layers (N-th layer: rate * rate_decay ^ (n - 1)). Defaults to 1. |
| momentum_start | Initial momentum at the beginning of training (try 0.5). Defaults to 0. |
| momentum_ramp | Number of training samples for which momentum increases. Defaults to 1000000. |
| momentum_stable | Final momentum after the ramp is over (try 0.99). Defaults to 0. |
| nesterov_accelerated_gradient | Logical. Use Nesterov accelerated gradient (recommended). Defaults to TRUE. |
| input_dropout_ratio | Input layer dropout ratio (can improve generalization, try 0.1 or 0.2). Defaults to 0. |
| hidden_dropout_ratios | Hidden layer dropout ratios (can improve generalization), specify one value per hidden layer, defaults to 0.5. |
| l1 | L1 regularization (can add stability and improve generalization, causes many weights to become 0). Defaults to 0. |
| l2 | L2 regularization (can add stability and improve generalization, causes many weights to be small. Defaults to 0. |
| max_w2 | Constraint for squared sum of incoming weights per unit (e.g. for Rectifier). Defaults to 3.4028235e+38. |
| initial_weight_distribution | Initial weight distribution. Must be one of: "UniformAdaptive", "Uniform", "Normal". Defaults to UniformAdaptive. |
| initial_weight_scale | Uniform: -value...value, Normal: stddev. Defaults to 1. |
| initial_weights | A list of H2OFrame ids to initialize the weight matrices of this model with. |
| initial_biases | A list of H2OFrame ids to initialize the bias vectors of this model with. |
| loss | Loss function. Must be one of: "Automatic", "CrossEntropy", "Quadratic", "Huber", "Absolute", "Quantile". Defaults to Automatic. |
| distribution | Distribution function Must be one of: "AUTO", "bernoulli", "multinomial", "gaussian", "poisson", "gamma", "tweedie", "laplace", "quantile", "huber". Defaults to AUTO. |

| | |
|---------------------------|--|
| quantile_alpha | Desired quantile for Quantile regression, must be between 0 and 1. Defaults to 0.5. |
| tweedie_power | Tweedie power for Tweedie regression, must be between 1 and 2. Defaults to 1.5. |
| huber_alpha | Desired quantile for Huber/M-regression (threshold between quadratic and linear loss, must be between 0 and 1). Defaults to 0.9. |
| score_interval | Shortest time interval (in seconds) between model scoring. Defaults to 5. |
| score_training_samples | Number of training set samples for scoring (0 for all). Defaults to 10000. |
| score_validation_samples | Number of validation set samples for scoring (0 for all). Defaults to 0. |
| score_duty_cycle | Maximum duty cycle fraction for scoring (lower: more training, higher: more scoring). Defaults to 0.1. |
| classification_stop | Stopping criterion for classification error fraction on training data (-1 to disable). Defaults to 0. |
| regression_stop | Stopping criterion for regression error (MSE) on training data (-1 to disable). Defaults to 1e-06. |
| stopping_rounds | Early stopping based on convergence of stopping_metric. Stop if simple moving average of length k of the stopping_metric does not improve for k:=stopping_rounds scoring events (0 to disable) Defaults to 5. |
| stopping_metric | Metric to use for early stopping (AUTO: logloss for classification, deviance for regression) Must be one of: "AUTO", "deviance", "logloss", "MSE", "RMSE", "MAE", "RMSLE", "AUC", "lift_top_group", "misclassification", "mean_per_class_error". Defaults to AUTO. |
| stopping_tolerance | Relative tolerance for metric-based stopping criterion (stop if relative improvement is not at least this much) Defaults to 0. |
| max_runtime_secs | Maximum allowed runtime in seconds for model training. Use 0 to disable. Defaults to 0. |
| score_validation_sampling | Method used to sample validation dataset for scoring. Must be one of: "Uniform", "Stratified". Defaults to Uniform. |
| diagnostics | Logical. Enable diagnostics for hidden layers. Defaults to TRUE. |
| fast_mode | Logical. Enable fast mode (minor approximation in back-propagation). Defaults to TRUE. |
| force_load_balance | Logical. Force extra load balancing to increase training speed for small datasets (to keep all cores busy). Defaults to TRUE. |
| variable_importances | Logical. Compute variable importances for input features (Gedeon method) - can be slow for large networks. Defaults to TRUE. |
| replicate_training_data | Logical. Replicate the entire training dataset onto every node for faster training on small datasets. Defaults to TRUE. |

| | |
|----------------------------------|---|
| single_node_mode | Logical. Run on a single node for fine-tuning of model parameters. Defaults to FALSE. |
| shuffle_training_data | Logical. Enable shuffling of training data (recommended if training data is replicated and train_samples_per_iteration is close to #nodes x #rows, of if using balance_classes). Defaults to FALSE. |
| missing_values_handling | Handling of missing values. Either MeanImputation or Skip. Must be one of: "MeanImputation", "Skip". Defaults to MeanImputation. |
| quiet_mode | Logical. Enable quiet mode for less output to standard output. Defaults to FALSE. |
| autoencoder | Logical. Auto-Encoder. Defaults to FALSE. |
| sparse | Logical. Sparse data handling (more efficient for data with lots of 0 values). Defaults to FALSE. |
| col_major | Logical. #DEPRECATED Use a column major weight matrix for input layer. Can speed up forward propagation, but might slow down backpropagation. Defaults to FALSE. |
| average_activation | Average activation for sparse auto-encoder. #Experimental Defaults to 0. |
| sparsity_beta | Sparsity regularization. #Experimental Defaults to 0. |
| max_categorical_features | Max. number of categorical features, enforced via hashing. #Experimental Defaults to 2147483647. |
| reproducible | Logical. Force reproducibility on small data (will be slow - only uses 1 thread). Defaults to FALSE. |
| export_weights_and_biases | Logical. Whether to export Neural Network weights and biases to H2O Frames. Defaults to FALSE. |
| mini_batch_size | Mini-batch size (smaller leads to better fit, larger can speed up and generalize better). Defaults to 1. |
| categorical_encoding | Encoding scheme for categorical features Must be one of: "AUTO", "Enum", "OneHotInternal", "OneHotExplicit", "Binary", "Eigen", "LabelEncoder", "Sort-ByResponse", "EnumLimited". Defaults to AUTO. |
| elastic_averaging | Logical. Elastic averaging between compute nodes can improve distributed model convergence. #Experimental Defaults to FALSE. |
| elastic_averaging_moving_rate | Elastic averaging moving rate (only if elastic averaging is enabled). Defaults to 0.9. |
| elastic_averaging_regularization | Elastic averaging regularization strength (only if elastic averaging is enabled). Defaults to 0.001. |
| verbose | Logical. Print scoring history to the console (Metrics per tree for GBM, DRF, & XGBoost. Metrics per epoch for Deep Learning). Defaults to FALSE. |

See Also

[predict.H2OModel](#) for prediction

Examples

```

library(h2o)
h2o.init()
iris.hex <- as.h2o(iris)
iris.dl <- h2o.deeplearning(x = 1:4, y = 5, training_frame = iris.hex, seed=123456)

# now make a prediction
predictions <- h2o.predict(iris.dl, iris.hex)

```

h2o.deepwater

Build a Deep Learning model using multiple native GPU backends

Description

Builds a deep neural network on an H2OFrame containing various data sources.

Usage

```

h2o.deepwater(x, y, training_frame, model_id = NULL, checkpoint = NULL,
  autoencoder = FALSE, validation_frame = NULL, nfolds = 0,
  balance_classes = FALSE, max_after_balance_size = 5,
  class_sampling_factors = NULL, keep_cross_validation_predictions = FALSE,
  keep_cross_validation_fold_assignment = FALSE, fold_assignment = c("AUTO",
  "Random", "Modulo", "Stratified"), fold_column = NULL,
  offset_column = NULL, weights_column = NULL,
  score_each_iteration = FALSE, categorical_encoding = c("AUTO", "Enum",
  "OneHotInternal", "OneHotExplicit", "Binary", "Eigen", "LabelEncoder",
  "SortByResponse", "EnumLimited"), overwrite_with_best_model = TRUE,
  epochs = 10, train_samples_per_iteration = -2,
  target_ratio_comm_to_comp = 0.05, seed = -1, standardize = TRUE,
  learning_rate = 0.001, learning_rate_annealing = 1e-06,
  momentum_start = 0.9, momentum_ramp = 10000, momentum_stable = 0.9,
  distribution = c("AUTO", "bernoulli", "multinomial", "gaussian", "poisson",
  "gamma", "tweedie", "laplace", "quantile", "huber"), score_interval = 5,
  score_training_samples = 10000, score_validation_samples = 0,
  score_duty_cycle = 0.1, classification_stop = 0, regression_stop = 0,
  stopping_rounds = 5, stopping_metric = c("AUTO", "deviance", "logloss",
  "MSE", "RMSE", "MAE", "RMSLE", "AUC", "lift_top_group", "misclassification",
  "mean_per_class_error"), stopping_tolerance = 0, max_runtime_secs = 0,
  ignore_const_cols = TRUE, shuffle_training_data = TRUE,
  mini_batch_size = 32, clip_gradient = 10, network = c("auto", "user",
  "lenet", "alexnet", "vgg", "googlenet", "inception_bn", "resnet"),
  backend = c("mxnet", "caffe", "tensorflow"), image_shape = c(0, 0),
  channels = 3, sparse = FALSE, gpu = TRUE, device_id = c(0),
  cache_data = TRUE, network_definition_file = NULL,
  network_parameters_file = NULL, mean_image_file = NULL,
  export_native_parameters_prefix = NULL, activation = c("Rectifier",
  "Tanh"), hidden = NULL, input_dropout_ratio = 0,
  hidden_dropout_ratios = NULL, problem_type = c("auto", "image",
  "dataset"))

```

Arguments

| | |
|---------------------------------------|---|
| x | (Optional) A vector containing the names or indices of the predictor variables to use in building the model. If x is missing, then all columns except y are used. |
| y | The name or column index of the response variable in the data. The response must be either a numeric or a categorical/factor variable. If the response is numeric, then a regression model will be trained, otherwise it will train a classification model. |
| training_frame | Id of the training data frame. |
| model_id | Destination id for this model; auto-generated if not specified. |
| checkpoint | Model checkpoint to resume training with. |
| autoencoder | Logical. Auto-Encoder. Defaults to FALSE. |
| validation_frame | Id of the validation data frame. |
| nfolds | Number of folds for K-fold cross-validation (0 to disable or >= 2). Defaults to 0. |
| balance_classes | Logical. Balance training data class counts via over/under-sampling (for imbalanced data). Defaults to FALSE. |
| max_after_balance_size | Maximum relative size of the training data after balancing class counts (can be less than 1.0). Requires balance_classes. Defaults to 5.0. |
| class_sampling_factors | Desired over/under-sampling ratios per class (in lexicographic order). If not specified, sampling factors will be automatically computed to obtain class balance during training. Requires balance_classes. |
| keep_cross_validation_predictions | Logical. Whether to keep the predictions of the cross-validation models. Defaults to FALSE. |
| keep_cross_validation_fold_assignment | Logical. Whether to keep the cross-validation fold assignment. Defaults to FALSE. |
| fold_assignment | Cross-validation fold assignment scheme, if fold_column is not specified. The 'Stratified' option will stratify the folds based on the response variable, for classification problems. Must be one of: "AUTO", "Random", "Modulo", "Stratified". Defaults to AUTO. |
| fold_column | Column with cross-validation fold index assignment per observation. |
| offset_column | Offset column. This will be added to the combination of columns before applying the link function. |
| weights_column | Column with observation weights. Giving some observation a weight of zero is equivalent to excluding it from the dataset; giving an observation a relative weight of 2 is equivalent to repeating that row twice. Negative weights are not allowed. Note: Weights are per-row observation weights and do not increase the size of the data frame. This is typically the number of times a row is repeated, but non-integer values are supported as well. During training, rows with higher weights matter more, due to the larger loss function pre-factor. |
| score_each_iteration | Logical. Whether to score during each iteration of model training. Defaults to FALSE. |

| | |
|-----------------------------|---|
| categorical_encoding | Encoding scheme for categorical features Must be one of: "AUTO", "Enum", "OneHotInternal", "OneHotExplicit", "Binary", "Eigen", "LabelEncoder", "Sort-ByResponse", "EnumLimited". Defaults to AUTO. |
| overwrite_with_best_model | Logical. If enabled, override the final model with the best model found during training. Defaults to TRUE. |
| epochs | How many times the dataset should be iterated (streamed), can be fractional. Defaults to 10. |
| train_samples_per_iteration | Number of training samples (globally) per MapReduce iteration. Special values are 0: one epoch, -1: all available data (e.g., replicated training data), -2: automatic. Defaults to -2. |
| target_ratio_comm_to_comp | Target ratio of communication overhead to computation. Only for multi-node operation and train_samples_per_iteration = -2 (auto-tuning). Defaults to 0.05. |
| seed | Seed for random numbers (affects certain parts of the algo that are stochastic and those might or might not be enabled by default) Note: only reproducible when running single threaded. Defaults to -1 (time-based random number). |
| standardize | Logical. If enabled, automatically standardize the data. If disabled, the user must provide properly scaled input data. Defaults to TRUE. |
| learning_rate | Learning rate (higher => less stable, lower => slower convergence). Defaults to 0.001. |
| learning_rate_annealing | Learning rate annealing: $rate / (1 + rate_annealing * samples)$. Defaults to $1e-06$. |
| momentum_start | Initial momentum at the beginning of training (try 0.5). Defaults to 0.9. |
| momentum_ramp | Number of training samples for which momentum increases. Defaults to 10000. |
| momentum_stable | Final momentum after the ramp is over (try 0.99). Defaults to 0.9. |
| distribution | Distribution function Must be one of: "AUTO", "bernoulli", "multinomial", "gaussian", "poisson", "gamma", "tweedie", "laplace", "quantile", "huber". Defaults to AUTO. |
| score_interval | Shortest time interval (in seconds) between model scoring. Defaults to 5. |
| score_training_samples | Number of training set samples for scoring (0 for all). Defaults to 10000. |
| score_validation_samples | Number of validation set samples for scoring (0 for all). Defaults to 0. |
| score_duty_cycle | Maximum duty cycle fraction for scoring (lower: more training, higher: more scoring). Defaults to 0.1. |
| classification_stop | Stopping criterion for classification error fraction on training data (-1 to disable). Defaults to 0. |
| regression_stop | Stopping criterion for regression error (MSE) on training data (-1 to disable). Defaults to 0. |

| | |
|---------------------------------|--|
| stopping_rounds | Early stopping based on convergence of stopping_metric. Stop if simple moving average of length k of the stopping_metric does not improve for k:=stopping_rounds scoring events (0 to disable) Defaults to 5. |
| stopping_metric | Metric to use for early stopping (AUTO: logloss for classification, deviance for regression) Must be one of: "AUTO", "deviance", "logloss", "MSE", "RMSE", "MAE", "RMSLE", "AUC", "lift_top_group", "misclassification", "mean_per_class_error". Defaults to AUTO. |
| stopping_tolerance | Relative tolerance for metric-based stopping criterion (stop if relative improvement is not at least this much) Defaults to 0. |
| max_runtime_secs | Maximum allowed runtime in seconds for model training. Use 0 to disable. Defaults to 0. |
| ignore_const_cols | Logical. Ignore constant columns. Defaults to TRUE. |
| shuffle_training_data | Logical. Enable global shuffling of training data. Defaults to TRUE. |
| mini_batch_size | Mini-batch size (smaller leads to better fit, larger can speed up and generalize better). Defaults to 32. |
| clip_gradient | Clip gradients once their absolute value is larger than this value. Defaults to 10. |
| network | Network architecture. Must be one of: "auto", "user", "lenet", "alexnet", "vgg", "googlenet", "inception_bn", "resnet". Defaults to auto. |
| backend | Deep Learning Backend. Must be one of: "mxnet", "caffe", "tensorflow". Defaults to mxnet. |
| image_shape | Width and height of image. Defaults to [0, 0]. |
| channels | Number of (color) channels. Defaults to 3. |
| sparse | Logical. Sparse data handling (more efficient for data with lots of 0 values). Defaults to FALSE. |
| gpu | Logical. Whether to use a GPU (if available). Defaults to TRUE. |
| device_id | Device IDs (which GPUs to use). Defaults to [0]. |
| cache_data | Logical. Whether to cache the data in memory (automatically disabled if data size is too large). Defaults to TRUE. |
| network_definition_file | Path of file containing network definition (graph, architecture). |
| network_parameters_file | Path of file containing network (initial) parameters (weights, biases). |
| mean_image_file | Path of file containing the mean image data for data normalization. |
| export_native_parameters_prefix | Path (prefix) where to export the native model parameters after every iteration. |
| activation | Activation function. Only used if no user-defined network architecture file is provided, and only for problem_type=dataset. Must be one of: "Rectifier", "Tanh". |
| hidden | Hidden layer sizes (e.g. [200, 200]). Only used if no user-defined network architecture file is provided, and only for problem_type=dataset. |

| | |
|-----------------------|---|
| input_dropout_ratio | Input layer dropout ratio (can improve generalization, try 0.1 or 0.2). Defaults to 0. |
| hidden_dropout_ratios | Hidden layer dropout ratios (can improve generalization), specify one value per hidden layer, defaults to 0.5. |
| problem_type | Problem type, auto-detected by default. If set to image, the H2OFrame must contain a string column containing the path (URI or URL) to the images in the first column. If set to text, the H2OFrame must contain a string column containing the text in the first column. If set to dataset, Deep Water behaves just like any other H2O Model and builds a model on the provided H2OFrame (non-String columns). Must be one of: "auto", "image", "dataset". Defaults to auto. |

h2o.deepwater.available

Determines whether Deep Water is available

Description

Ask the H2O server whether a Deep Water model can be built. (Depends on availability of native backends.) Returns TRUE if a Deep Water model can be built, or FALSE otherwise.

Usage

```
h2o.deepwater.available(h2oRestApiVersion = .h2o.__REST_API_VERSION)
```

Arguments

h2oRestApiVersion
(Optional) Specific version of the REST API to use.

h2o.describe

H2O Description of A Dataset

Description

Reports the "Flow" style summary rollups on an instance of H2OFrame. Includes information about column types, mins/maxs/missing/zero counts/stds/number of levels

Usage

```
h2o.describe(frame)
```

Arguments

frame An H2OFrame object.

Value

A table with the Frame stats.

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.importFile(path = prosPath)
h2o.describe(prostate.hex)
```

| | |
|--------------|---|
| h2o.diff1ag1 | <i>Conduct a lag 1 transform on a numeric H2OFrame column</i> |
|--------------|---|

Description

Conduct a lag 1 transform on a numeric H2OFrame column

Usage

```
h2o.diff1ag1(object)
```

Arguments

| | |
|--------|-----------------|
| object | H2OFrame object |
|--------|-----------------|

Value

Returns an H2OFrame object.

| | |
|---------|---|
| h2o.dim | <i>Returns the number of rows and columns for an H2OFrame object.</i> |
|---------|---|

Description

Returns the number of rows and columns for an H2OFrame object.

Usage

```
h2o.dim(x)
```

Arguments

| | |
|---|---------------------|
| x | An H2OFrame object. |
|---|---------------------|

See Also

[dim](#) for the base R implementation.

| | |
|--------------|------------------------------------|
| h2o.dimnames | <i>Column names of an H2OFrame</i> |
|--------------|------------------------------------|

Description

Column names of an H2OFrame

Usage

```
h2o.dimnames(x)
```

Arguments

x An H2OFrame object.

See Also

[dimnames](#) for the base R implementation.

| | |
|--------------|---|
| h2o.distance | <i>Compute a pairwise distance measure between all rows of two numeric H2OFrames.</i> |
|--------------|---|

Description

Compute a pairwise distance measure between all rows of two numeric H2OFrames.

Usage

```
h2o.distance(x, y, measure)
```

Arguments

x An H2OFrame object (large, references).
y An H2OFrame object (small, queries).
measure An optional string indicating what distance measure to use. Must be one of:
"l1" - Absolute distance (L1-norm, >=0) "l2" - Euclidean distance (L2-norm,
>=0) "cosine" - Cosine similarity (-1...1) "cosine_sq" - Squared Cosine similar-
ity (0...1)

Examples

```
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
h2o.distance(prostate.hex[11:30,], prostate.hex[1:10,], "cosine")
```

h2o.downloadAllLogs *Download H2O Log Files to Disk*

Description

h2o.downloadAllLogs downloads all H2O log files to local disk in .zip format. Generally used for debugging purposes.

Usage

```
h2o.downloadAllLogs(dirname = ".", filename = NULL)
```

Arguments

| | |
|----------|---|
| dirname | (Optional) A character string indicating the directory that the log file should be saved in. |
| filename | (Optional) A character string indicating the name that the log file should be saved to. Note that the saved format is .zip, so the file name must include the .zip extension. |

Examples

```
h2o.downloadAllLogs(dirname='./your_directory_name/', filename = 'autoh2o_log.zip')
```

h2o.downloadCSV *Download H2O Data to Disk*

Description

Download an H2O data set to a CSV file on the local disk

Usage

```
h2o.downloadCSV(data, filename)
```

Arguments

| | |
|----------|--|
| data | an H2OFrame object to be downloaded. |
| filename | A string indicating the name that the CSV file should be saved to. |

Warning

Files located on the H2O server may be very large! Make sure you have enough hard drive space to accomodate the entire file.

Examples

```

library(h2o)
h2o.init()
irisPath <- system.file("extdata", "iris_wheader.csv", package = "h2o")
iris.hex <- h2o.uploadFile(path = irisPath)

myFile <- paste(getwd(), "my_iris_file.csv", sep = .Platform$file.sep)
h2o.downloadCSV(iris.hex, myFile)
file.info(myFile)
file.remove(myFile)

```

| | |
|-------------------|---|
| h2o.download_mojo | <i>Download the model in MOJO format.</i> |
|-------------------|---|

Description

Download the model in MOJO format.

Usage

```

h2o.download_mojo(model, path = getwd(), get_genmodel_jar = FALSE,
  genmodel_name = "")

```

Arguments

| | |
|------------------|--|
| model | An H2OModel |
| path | The path where MOJO file should be saved. Saved to current directory by default. |
| get_genmodel_jar | If TRUE, then also download h2o-genmodel.jar and store it in folder "path". |
| genmodel_name | Custom name of genmodel jar. |

Value

Name of the MOJO file written to the path.

Examples

```

library(h2o)
h <- h2o.init()
fr <- as.h2o(iris)
my_model <- h2o.gbm(x=1:4, y=5, training_frame=fr)
h2o.download_mojo(my_model) # save to the current working directory

```

| | |
|-------------------|--|
| h2o.download_pojo | <i>Download the Scoring POJO (Plain Old Java Object) of an H2O Model</i> |
|-------------------|--|

Description

Download the Scoring POJO (Plain Old Java Object) of an H2O Model

Usage

```
h2o.download_pojo(model, path = NULL, getjar = NULL, get_jar = TRUE,
  jar_name = "")
```

Arguments

| | |
|----------|--|
| model | An H2OModel |
| path | The path to the directory to store the POJO (no trailing slash). If NULL, then print to to console. The file name will be a compilable java file name. |
| getjar | (DEPRECATED) Whether to also download the h2o-genmodel.jar file needed to compile the POJO. This argument is now called 'get_jar'. |
| get_jar | Whether to also download the h2o-genmodel.jar file needed to compile the POJO |
| jar_name | Custom name of genmodel jar. |

Value

If path is NULL, then pretty print the POJO to the console. Otherwise save it to the specified directory and return POJO file name.

Examples

```
library(h2o)
h <- h2o.init()
fr <- as.h2o(iris)
my_model <- h2o.gbm(x=1:4, y=5, training_frame=fr)

h2o.download_pojo(my_model) # print the model to screen
# h2o.download_pojo(my_model, getwd()) # save the POJO and jar file to the current working
#                                     directory, NOT RUN
# h2o.download_pojo(my_model, getwd(), get_jar = FALSE ) # save only the POJO to the current
#                                                         working directory, NOT RUN
h2o.download_pojo(my_model, getwd()) # save to the current working directory
```

| | |
|-------------|------------------------|
| h2o.entropy | <i>Shannon entropy</i> |
|-------------|------------------------|

Description

Return the Shannon entropy of a string column. If the string is empty, the entropy is 0.

Usage

```
h2o.entropy(x)
```

Arguments

x The column on which to calculate the entropy.

Examples

```
library(h2o)
h2o.init()
buys <- as.h2o(c("no", "no", "yes", "yes", "yes", "no", "yes", "no", "yes", "yes", "no"))
buys_entropy <- h2o.entropy(buys)
```

| | |
|---------|--|
| h2o.exp | <i>Compute the exponential function of x</i> |
|---------|--|

Description

Compute the exponential function of x

Usage

```
h2o.exp(x)
```

Arguments

x An H2OFrame object.

See Also

[exp](#) for the base R implementation.

| | |
|----------------|---|
| h2o.exportFile | <i>Export an H2O Data Frame (H2OFrame) to a File or to a collection of Files.</i> |
|----------------|---|

Description

Exports an H2OFrame (which can be either VA or FV) to a file. This file may be on the H2O instace's local filesystem, or to HDFS (preface the path with hdfs://) or to S3N (preface the path with s3n://).

Usage

```
h2o.exportFile(data, path, force = FALSE, parts = 1)
```

Arguments

| | |
|-------|---|
| data | An H2OFrame object. |
| path | The path to write the file to. Must include the directory and also filename if exporting to a single file. May be prefaced with hdfs:// or s3n://. Each row of data appears as line of the file. |
| force | logical, indicates how to deal with files that already exist. |
| parts | integer, number of part files to export to. Default is to write to a single file. Large data can be exported to multiple 'part' files, where each part file contains subset of the data. User can specify the maximum number of part files or use value -1 to indicate that H2O should itself determine the optimal number of files. Parameter path will be considered to be a path to a directory if export to multiple part files is desired. Part files conform to naming scheme 'part-m-?????'. |

Details

In the case of existing files `force = TRUE` will overwrite the file. Otherwise, the operation will fail.

Examples

```
## Not run:
library(h2o)
h2o.init()
irisPath <- system.file("extdata", "iris.csv", package = "h2o")
iris.hex <- h2o.uploadFile(path = irisPath)

# These aren't real paths
# h2o.exportFile(iris.hex, path = "/path/on/h2o/server/filesystem/iris.csv")
# h2o.exportFile(iris.hex, path = "hdfs://path/in/hdfs/iris.csv")
# h2o.exportFile(iris.hex, path = "s3n://path/in/s3/iris.csv")

## End(Not run)
```

| | |
|----------------|-------------------------------|
| h2o.exportHDFS | <i>Export a Model to HDFS</i> |
|----------------|-------------------------------|

Description

Exports an [H2OModel](#) to HDFS.

Usage

```
h2o.exportHDFS(object, path, force = FALSE)
```

Arguments

| | |
|--------|--|
| object | an H2OModel class object. |
| path | The path to write the model to. Must include the directory and filename. |
| force | logical, indicates how to deal with files that already exist. |

| | |
|------------|---------------|
| h2o.fillna | <i>fillna</i> |
|------------|---------------|

Description

Fill NA's in a sequential manner up to a specified limit

Usage

```
h2o.fillna(x, method = "forward", axis = 1, maxlen = 1L)
```

Arguments

| | |
|--------|--|
| x | an H2OFrame |
| method | A String: "forward" or "backward" |
| axis | An Integer 1 for row-wise fill (default), 2 for column-wise fill |
| maxlen | An Integer for maximum number of consecutive NA's to fill |

Value

An H2OFrame after filling missing values

Examples

```
library(h2o)
h2o.init()
fr.with.nas = h2o.createFrame(categorical_fraction=0.0,missing_fraction=0.7,rows=6,cols=2,seed=123)
fr <- h2o.fillna(fr.with.nas, "forward", axis=1, maxlen=2L)
```

| | |
|------------------|--------------------------|
| h2o.filterNACols | <i>Filter NA Columns</i> |
|------------------|--------------------------|

Description

Filter NA Columns

Usage

```
h2o.filterNACols(data, frac = 0.2)
```

Arguments

| | |
|------|---|
| data | A dataset to filter on. |
| frac | The threshold of NAs to allow per column (columns \geq this threshold are filtered) |

Value

Returns a numeric vector of indexes that pertain to non-NA columns

| | |
|------------------|--|
| h2o.findSynonyms | <i>Find synonyms using a word2vec model.</i> |
|------------------|--|

Description

Find synonyms using a word2vec model.

Usage

```
h2o.findSynonyms(word2vec, word, count = 20)
```

Arguments

| | |
|----------|--|
| word2vec | A word2vec model. |
| word | A single word to find synonyms for. |
| count | The top 'count' synonyms will be returned. |

h2o.find_row_by_threshold

Find the threshold, give the max metric. No duplicate thresholds allowed

Description

Find the threshold, give the max metric. No duplicate thresholds allowed

Usage

```
h2o.find_row_by_threshold(object, threshold)
```

Arguments

| | |
|-----------|------------------------|
| object | H2OBinomialMetrics |
| threshold | number between 0 and 1 |

h2o.find_threshold_by_max_metric

Find the threshold, give the max metric

Description

Find the threshold, give the max metric

Usage

```
h2o.find_threshold_by_max_metric(object, metric)
```

Arguments

| | |
|--------|--------------------|
| object | H2OBinomialMetrics |
| metric | "F1," for example |

| | |
|-----------|---|
| h2o.floor | <i>Take a single numeric argument and return a numeric vector with the largest integers</i> |
|-----------|---|

Description

floor takes a single numeric argument x and returns a numeric vector containing the largest integers not greater than the corresponding elements of x.

Usage

```
h2o.floor(x)
```

Arguments

x An H2OFrame object.

See Also

[floor](#) for the base R implementation.

| | |
|----------|----------------------|
| h2o.flow | <i>Open H2O Flow</i> |
|----------|----------------------|

Description

Open H2O Flow in your browser

Usage

```
h2o.flow()
```

| | |
|---------------|-------------------------------------|
| h2o.gainsLift | <i>Access H2O Gains/Lift Tables</i> |
|---------------|-------------------------------------|

Description

Retrieve either a single or many Gains/Lift tables from H2O objects.

Usage

```
h2o.gainsLift(object, ...)  
  
## S4 method for signature 'H2OModel'  
h2o.gainsLift(object, newdata, valid = FALSE,  
              xval = FALSE, ...)  
  
## S4 method for signature 'H2OModelMetrics'  
h2o.gainsLift(object)
```

Arguments

| | |
|---------|---|
| object | Either an H2OModel object or an H2OModelMetrics object. |
| ... | further arguments to be passed to/from this method. |
| newdata | An H2OFrame object that can be scored on. Requires a valid response column. |
| valid | Retrieve the validation metric. |
| xval | Retrieve the cross-validation metric. |

Details

The [H2OModelMetrics](#) version of this function will only take [H2OBinomialMetrics](#) objects.

Value

Calling this function on [H2OModel](#) objects returns a Gains/Lift table corresponding to the [predict](#) function.

See Also

[predict](#) for generating prediction frames, [h2o.performance](#) for creating [H2OModelMetrics](#).

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
hex <- h2o.uploadFile(prosPath)
hex[,2] <- as.factor(hex[,2])
model <- h2o.gbm(x = 3:9, y = 2, distribution = "bernoulli",
                training_frame = hex, validation_frame = hex, nfolds=3)
h2o.gainsLift(model)           ## extract training metrics
h2o.gainsLift(model, valid=TRUE) ## extract validation metrics (here: the same)
h2o.gainsLift(model, xval =TRUE) ## extract cross-validation metrics
h2o.gainsLift(model, newdata=hex) ## score on new data (here: the same)
# Generating a ModelMetrics object
perf <- h2o.performance(model, hex)
h2o.gainsLift(perf)           ## extract from existing metrics object
```

h2o.gbm

Build gradient boosted classification or regression trees

Description

Builds gradient boosted classification trees and gradient boosted regression trees on a parsed data set. The default distribution function will guess the model type based on the response column type. In order to run properly, the response column must be an numeric for "gaussian" or an enum for "bernoulli" or "multinomial".

Usage

```

h2o.gbm(x, y, training_frame, model_id = NULL, validation_frame = NULL,
  nfolds = 0, keep_cross_validation_predictions = FALSE,
  keep_cross_validation_fold_assignment = FALSE,
  score_each_iteration = FALSE, score_tree_interval = 0,
  fold_assignment = c("AUTO", "Random", "Modulo", "Stratified"),
  fold_column = NULL, ignore_const_cols = TRUE, offset_column = NULL,
  weights_column = NULL, balance_classes = FALSE,
  class_sampling_factors = NULL, max_after_balance_size = 5,
  max_hit_ratio_k = 0, ntrees = 50, max_depth = 5, min_rows = 10,
  nbins = 20, nbins_top_level = 1024, nbins_cats = 1024,
  r2_stopping = Inf, stopping_rounds = 0, stopping_metric = c("AUTO",
  "deviance", "logloss", "MSE", "RMSE", "MAE", "RMSLE", "AUC", "lift_top_group",
  "misclassification", "mean_per_class_error"), stopping_tolerance = 0.001,
  max_runtime_secs = 0, seed = -1, build_tree_one_node = FALSE,
  learn_rate = 0.1, learn_rate_annealing = 1, distribution = c("AUTO",
  "bernoulli", "quasibinomial", "multinomial", "gaussian", "poisson", "gamma",
  "tweedie", "laplace", "quantile", "huber"), quantile_alpha = 0.5,
  tweedie_power = 1.5, huber_alpha = 0.9, checkpoint = NULL,
  sample_rate = 1, sample_rate_per_class = NULL, col_sample_rate = 1,
  col_sample_rate_change_per_level = 1, col_sample_rate_per_tree = 1,
  min_split_improvement = 1e-05, histogram_type = c("AUTO",
  "UniformAdaptive", "Random", "QuantilesGlobal", "RoundRobin"),
  max_abs_leafnode_pred = Inf, pred_noise_bandwidth = 0,
  categorical_encoding = c("AUTO", "Enum", "OneHotInternal", "OneHotExplicit",
  "Binary", "Eigen", "LabelEncoder", "SortByResponse", "EnumLimited"),
  calibrate_model = FALSE, calibration_frame = NULL,
  custom_metric_func = NULL, verbose = FALSE)

```

Arguments

| | |
|---------------------------------------|---|
| x | (Optional) A vector containing the names or indices of the predictor variables to use in building the model. If x is missing, then all columns except y are used. |
| y | The name or column index of the response variable in the data. The response must be either a numeric or a categorical/factor variable. If the response is numeric, then a regression model will be trained, otherwise it will train a classification model. |
| training_frame | Id of the training data frame. |
| model_id | Destination id for this model; auto-generated if not specified. |
| validation_frame | Id of the validation data frame. |
| nfolds | Number of folds for K-fold cross-validation (0 to disable or >= 2). Defaults to 0. |
| keep_cross_validation_predictions | Logical. Whether to keep the predictions of the cross-validation models. Defaults to FALSE. |
| keep_cross_validation_fold_assignment | Logical. Whether to keep the cross-validation fold assignment. Defaults to FALSE. |
| score_each_iteration | Logical. Whether to score during each iteration of model training. Defaults to FALSE. |

| | |
|------------------------|---|
| score_tree_interval | Score the model after every so many trees. Disabled if set to 0. Defaults to 0. |
| fold_assignment | Cross-validation fold assignment scheme, if fold_column is not specified. The 'Stratified' option will stratify the folds based on the response variable, for classification problems. Must be one of: "AUTO", "Random", "Modulo", "Stratified". Defaults to AUTO. |
| fold_column | Column with cross-validation fold index assignment per observation. |
| ignore_const_cols | Logical. Ignore constant columns. Defaults to TRUE. |
| offset_column | Offset column. This will be added to the combination of columns before applying the link function. |
| weights_column | Column with observation weights. Giving some observation a weight of zero is equivalent to excluding it from the dataset; giving an observation a relative weight of 2 is equivalent to repeating that row twice. Negative weights are not allowed. Note: Weights are per-row observation weights and do not increase the size of the data frame. This is typically the number of times a row is repeated, but non-integer values are supported as well. During training, rows with higher weights matter more, due to the larger loss function pre-factor. |
| balance_classes | Logical. Balance training data class counts via over/under-sampling (for imbalanced data). Defaults to FALSE. |
| class_sampling_factors | Desired over/under-sampling ratios per class (in lexicographic order). If not specified, sampling factors will be automatically computed to obtain class balance during training. Requires balance_classes. |
| max_after_balance_size | Maximum relative size of the training data after balancing class counts (can be less than 1.0). Requires balance_classes. Defaults to 5.0. |
| max_hit_ratio_k | Max. number (top K) of predictions to use for hit ratio computation (for multi-class only, 0 to disable) Defaults to 0. |
| ntrees | Number of trees. Defaults to 50. |
| max_depth | Maximum tree depth. Defaults to 5. |
| min_rows | Fewest allowed (weighted) observations in a leaf. Defaults to 10. |
| nbins | For numerical columns (real/int), build a histogram of (at least) this many bins, then split at the best point Defaults to 20. |
| nbins_top_level | For numerical columns (real/int), build a histogram of (at most) this many bins at the root level, then decrease by factor of two per level Defaults to 1024. |
| nbins_cats | For categorical columns (factors), build a histogram of this many bins, then split at the best point. Higher values can lead to more overfitting. Defaults to 1024. |
| r2_stopping | r2_stopping is no longer supported and will be ignored if set - please use stopping_rounds, stopping_metric and stopping_tolerance instead. Previous version of H2O would stop making trees when the R ² metric equals or exceeds this Defaults to 1.797693135e+308. |
| stopping_rounds | Early stopping based on convergence of stopping_metric. Stop if simple moving average of length k of the stopping_metric does not improve for k:=stopping_rounds scoring events (0 to disable) Defaults to 0. |

| | |
|----------------------------------|--|
| stopping_metric | Metric to use for early stopping (AUTO: logloss for classification, deviance for regression) Must be one of: "AUTO", "deviance", "logloss", "MSE", "RMSE", "MAE", "RMSLE", "AUC", "lift_top_group", "misclassification", "mean_per_class_error". Defaults to AUTO. |
| stopping_tolerance | Relative tolerance for metric-based stopping criterion (stop if relative improvement is not at least this much) Defaults to 0.001. |
| max_runtime_secs | Maximum allowed runtime in seconds for model training. Use 0 to disable. Defaults to 0. |
| seed | Seed for random numbers (affects certain parts of the algo that are stochastic and those might or might not be enabled by default) Defaults to -1 (time-based random number). |
| build_tree_one_node | Logical. Run on one node only; no network overhead but fewer cpus used. Suitable for small datasets. Defaults to FALSE. |
| learn_rate | Learning rate (from 0.0 to 1.0) Defaults to 0.1. |
| learn_rate_annealing | Scale the learning rate by this factor after each tree (e.g., 0.99 or 0.999) Defaults to 1. |
| distribution | Distribution function Must be one of: "AUTO", "bernoulli", "quasibinomial", "multinomial", "gaussian", "poisson", "gamma", "tweedie", "laplace", "quantile", "huber". Defaults to AUTO. |
| quantile_alpha | Desired quantile for Quantile regression, must be between 0 and 1. Defaults to 0.5. |
| tweedie_power | Tweedie power for Tweedie regression, must be between 1 and 2. Defaults to 1.5. |
| huber_alpha | Desired quantile for Huber/M-regression (threshold between quadratic and linear loss, must be between 0 and 1). Defaults to 0.9. |
| checkpoint | Model checkpoint to resume training with. |
| sample_rate | Row sample rate per tree (from 0.0 to 1.0) Defaults to 1. |
| sample_rate_per_class | A list of row sample rates per class (relative fraction for each class, from 0.0 to 1.0), for each tree |
| col_sample_rate | Column sample rate (from 0.0 to 1.0) Defaults to 1. |
| col_sample_rate_change_per_level | Relative change of the column sampling rate for every level (must be > 0.0 and <= 2.0) Defaults to 1. |
| col_sample_rate_per_tree | Column sample rate per tree (from 0.0 to 1.0) Defaults to 1. |
| min_split_improvement | Minimum relative improvement in squared error reduction for a split to happen Defaults to 1e-05. |
| histogram_type | What type of histogram to use for finding optimal split points Must be one of: "AUTO", "UniformAdaptive", "Random", "QuantilesGlobal", "RoundRobin". Defaults to AUTO. |

| | |
|-----------------------|---|
| max_abs_leafnode_pred | Maximum absolute value of a leaf node prediction Defaults to 1.797693135e+308. |
| pred_noise_bandwidth | Bandwidth (sigma) of Gaussian multiplicative noise $\sim N(1, \text{sigma})$ for tree node predictions Defaults to 0. |
| categorical_encoding | Encoding scheme for categorical features Must be one of: "AUTO", "Enum", "OneHotInternal", "OneHotExplicit", "Binary", "Eigen", "LabelEncoder", "Sort-ByResponse", "EnumLimited". Defaults to AUTO. |
| calibrate_model | Logical. Use Platt Scaling to calculate calibrated class probabilities. Calibration can provide more accurate estimates of class probabilities. Defaults to FALSE. |
| calibration_frame | Calibration frame for Platt Scaling |
| custom_metric_func | Reference to custom evaluation function, format: 'language:keyName=funcName' |
| verbose | Logical. Print scoring history to the console (Metrics per tree for GBM, DRF, & XGBoost. Metrics per epoch for Deep Learning). Defaults to FALSE. |

See Also

[predict.H2OModel](#) for prediction

Examples

```
library(h2o)
h2o.init()

# Run regression GBM on australia.hex data
ausPath <- system.file("extdata", "australia.csv", package="h2o")
australia.hex <- h2o.uploadFile(path = ausPath)
independent <- c("premax", "salmax", "minairtemp", "maxairtemp", "maxsst",
"maxsoilmoist", "Max_czcs")
dependent <- "runoffnew"
h2o.gbm(y = dependent, x = independent, training_frame = australia.hex,
ntrees = 3, max_depth = 3, min_rows = 2)
```

| | |
|-------------------|-----------------------------------|
| h2o.getConnection | <i>Retrieve an H2O Connection</i> |
|-------------------|-----------------------------------|

Description

Attempt to recover an h2o connection.

Usage

```
h2o.getConnection()
```

Value

Returns an [H2OConnection](#) object.

| | |
|--------------|---|
| h2o.getFrame | <i>Get an R Reference to an H2O Dataset, that will NOT be GC'd by default</i> |
|--------------|---|

Description

Get the reference to a frame with the given id in the H2O instance.

Usage

```
h2o.getFrame(id)
```

Arguments

| | |
|----|--|
| id | A string indicating the unique frame of the dataset to retrieve. |
|----|--|

| | |
|--------------------|-------------------------|
| h2o.getFutureModel | <i>Get future model</i> |
|--------------------|-------------------------|

Description

Get future model

Usage

```
h2o.getFutureModel(object, verbose = FALSE)
```

Arguments

| | |
|---------|---|
| object | H2OModel |
| verbose | Print model progress to console. Default is FALSE |

| | |
|----------------------------------|--|
| h2o.getGLMFullRegularizationPath | <i>Extract full regularization path from a GLM model</i> |
|----------------------------------|--|

Description

Extract the full regularization path from a GLM model (assuming it was run with the lambda search option).

Usage

```
h2o.getGLMFullRegularizationPath(model)
```

Arguments

| | |
|-------|--|
| model | an H2OModel corresponding from a h2o.glm call. |
|-------|--|

| | |
|-------------|--|
| h2o.getGrid | <i>Get a grid object from H2O distributed K/V store.</i> |
|-------------|--|

Description

Note that if neither cross-validation nor a validation frame is used in the grid search, then the training metrics will display in the "get grid" output. If a validation frame is passed to the grid, and `nfolds = 0`, then the validation metrics will display. However, if `nfolds > 1`, then cross-validation metrics will display even if a validation frame is provided.

Usage

```
h2o.getGrid(grid_id, sort_by, decreasing)
```

Arguments

| | |
|-------------------------|--|
| <code>grid_id</code> | ID of existing grid object to fetch |
| <code>sort_by</code> | Sort the models in the grid space by a metric. Choices are "logloss", "residual_deviance", "mse", "auc", "accuracy", "precision", "recall", "f1", etc. |
| <code>decreasing</code> | Specify whether sort order should be decreasing |

Examples

```
library(h2o)
library(jsonlite)
h2o.init()
iris.hex <- as.h2o(iris)
h2o.grid("gbm", grid_id = "gbm_grid_id", x = c(1:4), y = 5,
        training_frame = iris.hex, hyper_params = list(ntrees = c(1,2,3)))
grid <- h2o.getGrid("gbm_grid_id")
# Get grid summary
summary(grid)
# Fetch grid models
model_ids <- grid@model_ids
models <- lapply(model_ids, function(id) { h2o.getModel(id)})
```

| | |
|-----------|--|
| h2o.getId | <i>Get back-end distributed key/value store id from an H2OFrame.</i> |
|-----------|--|

Description

Get back-end distributed key/value store id from an H2OFrame.

Usage

```
h2o.getId(x)
```


Arguments

x An H2OFrame

Value

The id of the H2OFrame

h2o.getModel *Get an R reference to an H2O model*

Description

Returns a reference to an existing model in the H2O instance.

Usage

```
h2o.getModel(model_id)
```

Arguments

model_id A string indicating the unique model_id of the model to retrieve.

Value

Returns an object that is a subclass of [H2OModel](#).

Examples

```
library(h2o)
h2o.init()

iris.hex <- as.h2o(iris, "iris.hex")
model_id <- h2o.gbm(x = 1:4, y = 5, training_frame = iris.hex)@model_id
model.retrieved <- h2o.getModel(model_id)
```

h2o.getTimezone *Get the Time Zone on the H2O Cloud Returns a string*

Description

Get the Time Zone on the H2O Cloud Returns a string

Usage

```
h2o.getTimezone()
```

| | |
|--------------|---------------------------------|
| h2o.getTypes | <i>Get the types-per-column</i> |
|--------------|---------------------------------|

Description

Get the types-per-column

Usage

```
h2o.getTypes(x)
```

Arguments

| | |
|---|-------------|
| x | An H2OFrame |
|---|-------------|

Value

A list of types per column

| | |
|----------------|------------------------|
| h2o.getVersion | <i>Get h2o version</i> |
|----------------|------------------------|

Description

Get h2o version

Usage

```
h2o.getVersion()
```

| | |
|--------------|--------------------------------------|
| h2o.giniCoef | <i>Retrieve the GINI Coefficient</i> |
|--------------|--------------------------------------|

Description

Retrieves the GINI coefficient from an [H2O Binomial Metrics](#). If "train", "valid", and "xval" parameters are FALSE (default), then the training GINI value is returned. If more than one parameter is set to TRUE, then a named vector of GINIs are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.giniCoef(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|--|
| object | an H2OBinomialMetrics object. |
| train | Retrieve the training GINI Coefficient |
| valid | Retrieve the validation GINI Coefficient |
| xval | Retrieve the cross-validation GINI Coefficient |

See Also

[h2o.auc](#) for AUC, [h2o.giniCoef](#) for the GINI coefficient, and [h2o.metric](#) for the various. See [h2o.performance](#) for creating H2OModelMetrics objects. threshold metrics.

Examples

```
library(h2o)
h2o.init()

prosPath <- system.file("extdata", "prostate.csv", package="h2o")
hex <- h2o.uploadFile(prosPath)

hex[,2] <- as.factor(hex[,2])
model <- h2o.gbm(x = 3:9, y = 2, training_frame = hex, distribution = "bernoulli")
perf <- h2o.performance(model, hex)
h2o.giniCoef(perf)
```

h2o.glm

Fit a generalized linear model

Description

Fits a generalized linear model, specified by a response variable, a set of predictors, and a description of the error distribution.

Usage

```
h2o.glm(x, y, training_frame, model_id = NULL, validation_frame = NULL,
  nfolds = 0, seed = -1, keep_cross_validation_predictions = FALSE,
  keep_cross_validation_fold_assignment = FALSE, fold_assignment = c("AUTO",
  "Random", "Modulo", "Stratified"), fold_column = NULL,
  ignore_const_cols = TRUE, score_each_iteration = FALSE,
  offset_column = NULL, weights_column = NULL, family = c("gaussian",
  "binomial", "quasibinomial", "ordinal", "multinomial", "poisson", "gamma",
  "tweedie"), tweedie_variance_power = 0, tweedie_link_power = 1,
  solver = c("AUTO", "IRLSM", "L_BFGS", "COORDINATE_DESCENT_NAIVE",
  "COORDINATE_DESCENT", "GRADIENT_DESCENT_LH", "GRADIENT_DESCENT_SQERR"),
  alpha = NULL, lambda = NULL, lambda_search = FALSE,
  early_stopping = TRUE, nlambda = -1, standardize = TRUE,
  missing_values_handling = c("MeanImputation", "Skip"),
  compute_p_values = FALSE, remove_collinear_columns = FALSE,
  intercept = TRUE, non_negative = FALSE, max_iterations = -1,
```

```
objective_epsilon = -1, beta_epsilon = 1e-04, gradient_epsilon = -1,
link = c("family_default", "identity", "logit", "log", "inverse", "tweedie",
"ologit", "oprobit", "ologlog"), prior = -1, lambda_min_ratio = -1,
beta_constraints = NULL, max_active_predictors = -1,
interactions = NULL, interaction_pairs = NULL, obj_reg = -1,
balance_classes = FALSE, class_sampling_factors = NULL,
max_after_balance_size = 5, max_hit_ratio_k = 0, max_runtime_secs = 0,
custom_metric_func = NULL)
```

Arguments

| | |
|---------------------------------------|---|
| x | (Optional) A vector containing the names or indices of the predictor variables to use in building the model. If x is missing, then all columns except y are used. |
| y | The name or column index of the response variable in the data. The response must be either a numeric or a categorical/factor variable. If the response is numeric, then a regression model will be trained, otherwise it will train a classification model. |
| training_frame | Id of the training data frame. |
| model_id | Destination id for this model; auto-generated if not specified. |
| validation_frame | Id of the validation data frame. |
| nfolds | Number of folds for K-fold cross-validation (0 to disable or >= 2). Defaults to 0. |
| seed | Seed for random numbers (affects certain parts of the algo that are stochastic and those might or might not be enabled by default) Defaults to -1 (time-based random number). |
| keep_cross_validation_predictions | Logical. Whether to keep the predictions of the cross-validation models. Defaults to FALSE. |
| keep_cross_validation_fold_assignment | Logical. Whether to keep the cross-validation fold assignment. Defaults to FALSE. |
| fold_assignment | Cross-validation fold assignment scheme, if fold_column is not specified. The 'Stratified' option will stratify the folds based on the response variable, for classification problems. Must be one of: "AUTO", "Random", "Modulo", "Stratified". Defaults to AUTO. |
| fold_column | Column with cross-validation fold index assignment per observation. |
| ignore_const_cols | Logical. Ignore constant columns. Defaults to TRUE. |
| score_each_iteration | Logical. Whether to score during each iteration of model training. Defaults to FALSE. |
| offset_column | Offset column. This will be added to the combination of columns before applying the link function. |
| weights_column | Column with observation weights. Giving some observation a weight of zero is equivalent to excluding it from the dataset; giving an observation a relative weight of 2 is equivalent to repeating that row twice. Negative weights are not allowed. Note: Weights are per-row observation weights and do not increase the |

| | |
|--------------------------|---|
| | size of the data frame. This is typically the number of times a row is repeated, but non-integer values are supported as well. During training, rows with higher weights matter more, due to the larger loss function pre-factor. |
| family | Family. Use binomial for classification with logistic regression, others are for regression problems. Must be one of: "gaussian", "binomial", "quasibinomial", "ordinal", "multinomial", "poisson", "gamma", "tweedie". Defaults to gaussian. |
| tweedie_variance_power | Tweedie variance power Defaults to 0. |
| tweedie_link_power | Tweedie link power Defaults to 1. |
| solver | AUTO will set the solver based on given data and the other parameters. IRLSM is fast on problems with small number of predictors and for lambda-search with L1 penalty, L_BFGS scales better for datasets with many columns. Coordinate descent is experimental (beta). Must be one of: "AUTO", "IRLSM", "L_BFGS", "COORDINATE_DESCENT_NAIVE", "COORDINATE_DESCENT", "GRADIENT_DESCENT_LH", "GRADIENT_DESCENT_SQERR". Defaults to AUTO. |
| alpha | Distribution of regularization between the L1 (Lasso) and L2 (Ridge) penalties. A value of 1 for alpha represents Lasso regression, a value of 0 produces Ridge regression, and anything in between specifies the amount of mixing between the two. Default value of alpha is 0 when SOLVER = 'L-BFGS'; 0.5 otherwise. |
| lambda | Regularization strength |
| lambda_search | Logical. Use lambda search starting at lambda max, given lambda is then interpreted as lambda min Defaults to FALSE. |
| early_stopping | Logical. Stop early when there is no more relative improvement on train or validation (if provided) Defaults to TRUE. |
| nlambdas | Number of lambdas to be used in a search. Default indicates: If alpha is zero, with lambda search set to True, the value of nlambdas is set to 30 (fewer lambdas are needed for ridge regression) otherwise it is set to 100. Defaults to -1. |
| standardize | Logical. Standardize numeric columns to have zero mean and unit variance Defaults to TRUE. |
| missing_values_handling | Handling of missing values. Either MeanImputation or Skip. Must be one of: "MeanImputation", "Skip". Defaults to MeanImputation. |
| compute_p_values | Logical. Request p-values computation, p-values work only with IRLSM solver and no regularization Defaults to FALSE. |
| remove_collinear_columns | Logical. In case of linearly dependent columns, remove some of the dependent columns Defaults to FALSE. |
| intercept | Logical. Include constant term in the model Defaults to TRUE. |
| non_negative | Logical. Restrict coefficients (not intercept) to be non-negative Defaults to FALSE. |
| max_iterations | Maximum number of iterations Defaults to -1. |
| objective_epsilon | Converge if objective value changes less than this. Default indicates: If lambda_search is set to True the value of objective_epsilon is set to .0001. If the lambda_search is set to False and lambda is equal to zero, the value of objective_epsilon is set to .000001, for any other value of lambda the default value of objective_epsilon is set to .0001. Defaults to -1. |

| | |
|------------------------|--|
| beta_epsilon | Converge if beta changes less (using L-infinity norm) than beta esilon, ONLY applies to IRLSM solver Defaults to 0.0001. |
| gradient_epsilon | Converge if objective changes less (using L-infinity norm) than this, ONLY applies to L-BFGS solver. Default indicates: If lambda_search is set to False and lambda is equal to zero, the default value of gradient_epsilon is equal to .000001, otherwise the default value is .0001. If lambda_search is set to True, the conditional values above are 1E-8 and 1E-6 respectively. Defaults to -1. |
| link | Must be one of: "family_default", "identity", "logit", "log", "inverse", "tweedie", "ologit", "oprobit", "ologlog". Defaults to family_default. |
| prior | Prior probability for y==1. To be used only for logistic regression iff the data has been sampled and the mean of response does not reflect reality. Defaults to -1. |
| lambda_min_ratio | Minimum lambda used in lambda search, specified as a ratio of lambda_max (the smallest lambda that drives all coefficients to zero). Default indicates: if the number of observations is greater than the number of variables, then lambda_min_ratio is set to 0.0001; if the number of observations is less than the number of variables, then lambda_min_ratio is set to 0.01. Defaults to -1. |
| beta_constraints | Beta constraints |
| max_active_predictors | Maximum number of active predictors during computation. Use as a stopping criterion to prevent expensive model building with many predictors. Default indicates: If the IRLSM solver is used, the value of max_active_predictors is set to 5000 otherwise it is set to 100000000. Defaults to -1. |
| interactions | A list of predictor column indices to interact. All pairwise combinations will be computed for the list. |
| interaction_pairs | A list of pairwise (first order) column interactions. |
| obj_reg | Likelihood divider in objective value computation, default is 1/nobs Defaults to -1. |
| balance_classes | Logical. Balance training data class counts via over/under-sampling (for im-balanced data). Defaults to FALSE. |
| class_sampling_factors | Desired over/under-sampling ratios per class (in lexicographic order). If not specified, sampling factors will be automatically computed to obtain class balance during training. Requires balance_classes. |
| max_after_balance_size | Maximum relative size of the training data after balancing class counts (can be less than 1.0). Requires balance_classes. Defaults to 5.0. |
| max_hit_ratio_k | Maximum number (top K) of predictions to use for hit ratio computation (for multi-class only, 0 to disable) Defaults to 0. |
| max_runtime_secs | Maximum allowed runtime in seconds for model training. Use 0 to disable. Defaults to 0. |
| custom_metric_func | Reference to custom evaluation function, format: 'language:keyName=funcName' |

Value

A subclass of `H2OModel` is returned. The specific subclass depends on the machine learning task at hand (if it's binomial classification, then an `H2OBinomialModel` is returned, if it's regression then a `H2ORegressionModel` is returned). The default print-out of the models is shown, but further GLM-specific information can be queried out of the object. To access these various items, please refer to the `seealso` section below. Upon completion of the GLM, the resulting object has coefficients, normalized coefficients, residual/null deviance, `aic`, and a host of model metrics including MSE, AUC (for logistic regression), degrees of freedom, and confusion matrices. Please refer to the more in-depth GLM documentation available here: <https://h2o-release.s3.amazonaws.com/h2o-dev/re1-shannon/2/docs-website/h2o-docs/index.html#Data+Science+Algorithms-GLM>

See Also

`predict.H2OModel` for prediction, `h2o.mse`, `h2o.auc`, `h2o.confusionMatrix`, `h2o.performance`, `h2o.giniCoef`, `h2o.logloss`, `h2o.varimp`, `h2o.scoreHistory`

Examples

```
h2o.init()

# Run GLM of CAPSULE ~ AGE + RACE + PSA + DCAPS
prostatePath = system.file("extdata", "prostate.csv", package = "h2o")
prostate.hex = h2o.importFile(path = prostatePath, destination_frame = "prostate.hex")
h2o.glm(y = "CAPSULE", x = c("AGE", "RACE", "PSA", "DCAPS"), training_frame = prostate.hex,
family = "binomial", nfolds = 0, alpha = 0.5, lambda_search = FALSE)

# Run GLM of VOL ~ CAPSULE + AGE + RACE + PSA + GLEASON
myX = setdiff(colnames(prostate.hex), c("ID", "DPROS", "DCAPS", "VOL"))
h2o.glm(y = "VOL", x = myX, training_frame = prostate.hex, family = "gaussian",
nfolds = 0, alpha = 0.1, lambda_search = FALSE)

# GLM variable importance
# Also see:
# https://github.com/h2oai/h2o/blob/master/R/tests/testdir_demos/runit_demo_VI_all_algos.R
data.hex = h2o.importFile(
path = "https://s3.amazonaws.com/h2o-public-test-data/smalldata/demos/bank-additional-full.csv",
destination_frame = "data.hex")
myX = 1:20
myY="y"
my.glm = h2o.glm(x=myX, y=myY, training_frame=data.hex, family="binomial", standardize=TRUE,
lambda_search=TRUE)
```

h2o.glm

Generalized low rank decomposition of an H2O data frame

Description

Builds a generalized low rank decomposition of an H2O data frame

Usage

```
h2o.glm(training_frame, cols = NULL, model_id = NULL,
  validation_frame = NULL, ignore_const_cols = TRUE,
  score_each_iteration = FALSE, loading_name = NULL, transform = c("NONE",
  "STANDARDIZE", "NORMALIZE", "DEMEAN", "DESCALE"), k = 1,
  loss = c("Quadratic", "Absolute", "Huber", "Poisson", "Hinge", "Logistic",
  "Periodic"), loss_by_col = c("Quadratic", "Absolute", "Huber", "Poisson",
  "Hinge", "Logistic", "Periodic", "Categorical", "Ordinal"),
  loss_by_col_idx = NULL, multi_loss = c("Categorical", "Ordinal"),
  period = 1, regularization_x = c("None", "Quadratic", "L2", "L1",
  "NonNegative", "OneSparse", "UnitOneSparse", "Simplex"),
  regularization_y = c("None", "Quadratic", "L2", "L1", "NonNegative",
  "OneSparse", "UnitOneSparse", "Simplex"), gamma_x = 0, gamma_y = 0,
  max_iterations = 1000, max_updates = 2000, init_step_size = 1,
  min_step_size = 1e-04, seed = -1, init = c("Random", "SVD", "PlusPlus",
  "User"), svd_method = c("GramSVD", "Power", "Randomized"), user_y = NULL,
  user_x = NULL, expand_user_y = TRUE, impute_original = FALSE,
  recover_svd = FALSE, max_runtime_secs = 0)
```

Arguments

| | |
|----------------------|---|
| training_frame | Id of the training data frame. |
| cols | (Optional) A vector containing the data columns on which k-means operates. |
| model_id | Destination id for this model; auto-generated if not specified. |
| validation_frame | Id of the validation data frame. |
| ignore_const_cols | Logical. Ignore constant columns. Defaults to TRUE. |
| score_each_iteration | Logical. Whether to score during each iteration of model training. Defaults to FALSE. |
| loading_name | Frame key to save resulting X |
| transform | Transformation of training data Must be one of: "NONE", "STANDARDIZE", "NORMALIZE", "DEMEAN", "DESCALE". Defaults to NONE. |
| k | Rank of matrix approximation Defaults to 1. |
| loss | Numeric loss function Must be one of: "Quadratic", "Absolute", "Huber", "Poisson", "Hinge", "Logistic", "Periodic". Defaults to Quadratic. |
| loss_by_col | Loss function by column (override) Must be one of: "Quadratic", "Absolute", "Huber", "Poisson", "Hinge", "Logistic", "Periodic", "Categorical", "Ordinal". |
| loss_by_col_idx | Loss function by column index (override) |
| multi_loss | Categorical loss function Must be one of: "Categorical", "Ordinal". Defaults to Categorical. |
| period | Length of period (only used with periodic loss function) Defaults to 1. |
| regularization_x | Regularization function for X matrix Must be one of: "None", "Quadratic", "L2", "L1", "NonNegative", "OneSparse", "UnitOneSparse", "Simplex". Defaults to None. |

| | |
|------------------|---|
| regularization_y | Regularization function for Y matrix Must be one of: "None", "Quadratic", "L2", "L1", "NonNegative", "OneSparse", "UnitOneSparse", "Simplex". Defaults to None. |
| gamma_x | Regularization weight on X matrix Defaults to 0. |
| gamma_y | Regularization weight on Y matrix Defaults to 0. |
| max_iterations | Maximum number of iterations Defaults to 1000. |
| max_updates | Maximum number of updates, defaults to 2*max_iterations Defaults to 2000. |
| init_step_size | Initial step size Defaults to 1. |
| min_step_size | Minimum step size Defaults to 0.0001. |
| seed | Seed for random numbers (affects certain parts of the algo that are stochastic and those might or might not be enabled by default) Defaults to -1 (time-based random number). |
| init | Initialization mode Must be one of: "Random", "SVD", "PlusPlus", "User". Defaults to PlusPlus. |
| svd_method | Method for computing SVD during initialization (Caution: Randomized is currently experimental and unstable) Must be one of: "GramSVD", "Power", "Randomized". Defaults to Randomized. |
| user_y | User-specified initial Y |
| user_x | User-specified initial X |
| expand_user_y | Logical. Expand categorical columns in user-specified initial Y Defaults to TRUE. |
| impute_original | Logical. Reconstruct original training data by reversing transform Defaults to FALSE. |
| recover_svd | Logical. Recover singular values and eigenvectors of XY Defaults to FALSE. |
| max_runtime_secs | Maximum allowed runtime in seconds for model training. Use 0 to disable. Defaults to 0. |

Value

Returns an object of class [H2ODimReductionModel](#).

References

M. Udell, C. Horn, R. Zadeh, S. Boyd (2014). Generalized Low Rank Models[<http://arxiv.org/abs/1410.0342>]. Unpublished manuscript, Stanford Electrical Engineering Department N. Halko, P.G. Martinsson, J.A. Tropp. Finding structure with randomness: Probabilistic algorithms for constructing approximate matrix decompositions[<http://arxiv.org/abs/0909.4061>]. SIAM Rev., Survey and Review section, Vol. 53, num. 2, pp. 217-288, June 2011.

See Also

[h2o.kmeans](#), [h2o.svd](#), [h2o.prcomp](#)

Examples

```
library(h2o)
h2o.init()
ausPath <- system.file("extdata", "australia.csv", package="h2o")
australia.hex <- h2o.uploadFile(path = ausPath)
h2o.glm(training_frame = australia.hex, k = 5, loss = "Quadratic", regularization_x = "L1",
gamma_x = 0.5, gamma_y = 0, max_iterations = 1000)
```

h2o.grep

*Search for matches to an argument pattern***Description**

Searches for matches to argument ‘pattern’ within each element of a string column.

Usage

```
h2o.grep(pattern, x, ignore.case = FALSE, invert = FALSE,
output.logical = FALSE)
```

Arguments

| | |
|----------------|--|
| pattern | A character string containing a regular expression. |
| x | An H2O frame that wraps a single string column. |
| ignore.case | If TRUE case is ignored during matching. |
| invert | Identify elements that do not match the pattern. |
| output.logical | If TRUE returns logical vector of indicators instead of list of matching positions |

Details

This function has similar semantics as R’s native `grep` function and it supports a subset of its parameters. Default behavior is to return indices of the elements matching the pattern. Parameter ‘output.logical’ can be used to return a logical vector indicating if the element matches the pattern (1) or not (0).

Value

H2OFrame holding the matching positions or a logical vector if ‘output.logical’ is enabled.

Examples

```
library(h2o)
h2o.init()
addresses <- as.h2o(c("2307", "Leghorn St", "Mountain View", "CA", "94043"))
zip.codes <- addresses[h2o.grep("[0-9]{5}", addresses, output.logical = TRUE),]
```

h2o.grid

*H2O Grid Support***Description**

Provides a set of functions to launch a grid search and get its results.

Usage

```
h2o.grid(algorithm, grid_id, x, y, training_frame, ..., hyper_params = list(),
         is_supervised = NULL, do_hyper_params_check = FALSE,
         search_criteria = NULL)
```

Arguments

| | |
|-----------------------|--|
| algorithm | Name of algorithm to use in grid search (gbm, randomForest, kmeans, glm, deeplearning, naivebayes, pca). |
| grid_id | (Optional) ID for resulting grid search. If it is not specified then it is autogenerated. |
| x | (Optional) A vector containing the names or indices of the predictor variables to use in building the model. If x is missing, then all columns except y are used. |
| y | The name or column index of the response variable in the data. The response must be either a numeric or a categorical/factor variable. If the response is numeric, then a regression model will be trained, otherwise it will train a classification model. |
| training_frame | Id of the training data frame. |
| ... | arguments describing parameters to use with algorithm (i.e., x, y, training_frame). Look at the specific algorithm - h2o.gbm, h2o.glm, h2o.kmeans, h2o.deepLearning - for available parameters. |
| hyper_params | List of lists of hyper parameters (i.e., list(ntrees=c(1,2), max_depth=c(5,7))). |
| is_supervised | (Optional) If specified then override the default heuristic which decides if the given algorithm name and parameters specify a supervised or unsupervised algorithm. |
| do_hyper_params_check | Perform client check for specified hyper parameters. It can be time expensive for large hyper space. |
| search_criteria | (Optional) List of control parameters for smarter hyperparameter search. The default strategy 'Cartesian' covers the entire space of hyperparameter combinations. Specify the 'RandomDiscrete' strategy to get random search of all the combinations of your hyperparameters. RandomDiscrete should be usually combined with at least one early stopping criterion, max_models and/or max_runtime_secs, e.g. list(strategy = "RandomDiscrete", max_models = 42, max_runtime_secs = 100) or list(strategy = "RandomDiscrete", stopping_metric = "AUTO", stopping_tolerance = 0.01) or list(strategy = "RandomDiscrete", stopping_metric = "misclassification", stopping_tolerance = 0.01) |

Details

Launch grid search with given algorithm and parameters.

Examples

```

library(h2o)
library(jsonlite)
h2o.init()
iris.hex <- as.h2o(iris)
grid <- h2o.grid("gbm", x = c(1:4), y = 5, training_frame = iris.hex,
               hyper_params = list(ntrees = c(1,2,3)))
# Get grid summary
summary(grid)
# Fetch grid models
model_ids <- grid@model_ids
models <- lapply(model_ids, function(id) { h2o.getModel(id)})

```

h2o.group_by

Group and Apply by Column

Description

Performs a group by and apply similar to ddply.

Usage

```
h2o.group_by(data, by, ..., gb.control = list(na.methods = NULL, col.names =
NULL))
```

Arguments

| | |
|------------|--|
| data | an H2OFrame object. |
| by | a list of column names |
| ... | any supported aggregate function. See <i>Details</i> : for more help. |
| gb.control | a list of how to handle NA values in the dataset as well as how to name output columns. The method is specified using the <code>rm.method</code> argument. See <i>Details</i> : for more help. |

Details

In the case of `na.methods` within `gb.control`, there are three possible settings. "all" will include NAs in computation of functions. "rm" will completely remove all NA fields. "ignore" will remove NAs from the numerator but keep the rows for computational purposes. If a list smaller than the number of columns groups is supplied, the list will be padded by "ignore".

Note that to specify a list of column names in the `gb.control` list, you must add the `col.names` argument. Similar to `na.methods`, `col.names` will pad the list with the default column names if the length is less than the number of columns groups supplied.

Supported functions include `nrow`. This function is required and accepts a string for the name of the generated column. Other supported aggregate functions accept `col` and `na` arguments for specifying columns and the handling of NAs ("all", "ignore", and `GroupBy` object; `max` calculates the maximum of each column specified in `col` for each group of a `GroupBy` object; `mean` calculates the mean of each column specified in `col` for each group of a `GroupBy` object; `min` calculates the minimum of

each column specified in col for each group of a GroupBy object; mode calculates the mode of each column specified in col for each group of a GroupBy object; sd calculates the standard deviation of each column specified in col for each group of a GroupBy object; ss calculates the sum of squares of each column specified in col for each group of a GroupBy object; sum calculates the sum of each column specified in col for each group of a GroupBy object; and var calculates the variance of each column specified in col for each group of a GroupBy object. If an aggregate is provided without a value (for example, as max in `sum(col="X1", na="all").mean(col="X5", na="all").max()`), then it is assumed that the aggregation should apply to all columns except the GroupBy columns. Note again that nrow is required and cannot be empty.

Value

Returns a new H2OFrame object with columns equivalent to the number of groups created

| | |
|----------|---------------------------------|
| h2o.gsub | <i>String Global Substitute</i> |
|----------|---------------------------------|

Description

Creates a copy of the target column in which each string has all occurrence of the regex pattern replaced with the replacement substring.

Usage

```
h2o.gsub(pattern, replacement, x, ignore.case = FALSE)
```

Arguments

| | |
|-------------|---------------------------------|
| pattern | The pattern to replace. |
| replacement | The replacement pattern. |
| x | The column on which to operate. |
| ignore.case | Case sensitive or not |

Examples

```
library(h2o)
h2o.init()
string_to_gsub <- as.h2o("r tutorial")
sub_string <- h2o.gsub("r ", "H2O ", string_to_gsub)
```

| | |
|----------|---|
| h2o.head | <i>Return the Head or Tail of an H2O Dataset.</i> |
|----------|---|

Description

Returns the first or last rows of an H2OFrame object.

Usage

```
h2o.head(x, n = 6L, ...)

## S3 method for class 'H2OFrame'
head(x, n = 6L, ...)

h2o.tail(x, n = 6L, ...)

## S3 method for class 'H2OFrame'
tail(x, n = 6L, ...)
```

Arguments

| | |
|-----|---|
| x | An H2OFrame object. |
| n | (Optional) A single integer. If positive, number of rows in x to return. If negative, all but the n first/last number of rows in x. |
| ... | Ignored. |

Value

An H2OFrame containing the first or last n rows of an H2OFrame object.

Examples

```
library(h2o)
h2o.init(ip <- "localhost", port = 54321, startH2O = TRUE)
ausPath <- system.file("extdata", "australia.csv", package="h2o")
australia.hex <- h2o.uploadFile(path = ausPath)
head(australia.hex, 10)
tail(australia.hex, 10)
```

| | |
|----------|----------------------------|
| h2o.hist | <i>Compute A Histogram</i> |
|----------|----------------------------|

Description

Compute a histogram over a numeric column. If breaks=="FD", the MAD is used over the IQR in computing bin width. Note that we do not beautify the breakpoints as R does.

Usage

```
h2o.hist(x, breaks = "Sturges", plot = TRUE)
```

Arguments

| | |
|--------|---|
| x | A single numeric column from an H2OFrame. |
| breaks | Can be one of the following: A string: "Sturges", "Rice", "sqrt", "Doane", "FD", "Scott" A single number for the number of breaks splitting the range of the vec into number of breaks bins of equal width A vector of numbers giving the split points, e.g., c(-50,213.2123,9324834) |
| plot | A logical value indicating whether or not a plot should be generated (default is TRUE). |

h2o.hit_ratio_table *Retrieve the Hit Ratios*

Description

If "train", "valid", and "xval" parameters are FALSE (default), then the training Hit Ratios value is returned. If more than one parameter is set to TRUE, then a named list of Hit Ratio tables are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.hit_ratio_table(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|---|
| object | An H2OModel object. |
| train | Retrieve the training Hit Ratio |
| valid | Retrieve the validation Hit Ratio |
| xval | Retrieve the cross-validation Hit Ratio |

h2o.hour *Convert Milliseconds to Hour of Day in H2O Datasets*

Description

Converts the entries of an H2OFrame object from milliseconds to hours of the day (on a 0 to 23 scale).

Usage

```
h2o.hour(x)
```

```
hour(x)
```

```
## S3 method for class 'H2OFrame'
hour(x)
```

Arguments

x An H2OFrame object.

Value

An H2OFrame object containing the entries of x converted to hours of the day.

See Also

[h2o.day](#)

h2o.ifelse

H2O Apply Conditional Statement

Description

Applies conditional statements to numeric vectors in H2O parsed data objects when the data are numeric.

Usage

```
h2o.ifelse(test, yes, no)
```

```
ifelse(test, yes, no)
```

Arguments

test A logical description of the condition to be met (>, <, =, etc...)

yes The value to return if the condition is TRUE.

no The value to return if the condition is FALSE.

Details

Both numeric and categorical values can be tested. However when returning a yes and no condition both conditions must be either both categorical or numeric.

Value

Returns a vector of new values matching the conditions stated in the ifelse call.

Examples

```
h2o.init()
ausPath <- system.file("extdata", "australia.csv", package="h2o")
australia.hex <- h2o.importFile(path = ausPath)
australia.hex[,9] <- ifelse(australia.hex[,3] < 279.9, 1, 0)
summary(australia.hex)
```

| | |
|----------------|------------------------------|
| h2o.importFile | <i>Import Files into H2O</i> |
|----------------|------------------------------|

Description

Imports files into an H2O cloud. The default behavior is to pass-through to the parse phase automatically.

Usage

```
h2o.importFile(path, destination_frame = "", parse = TRUE, header = NA,
  sep = "", col.names = NULL, col.types = NULL, na.strings = NULL,
  decrypt_tool = NULL)
```

```
h2o.importFolder(path, pattern = "", destination_frame = "", parse = TRUE,
  header = NA, sep = "", col.names = NULL, col.types = NULL,
  na.strings = NULL, decrypt_tool = NULL)
```

```
h2o.importHDFS(path, pattern = "", destination_frame = "", parse = TRUE,
  header = NA, sep = "", col.names = NULL, na.strings = NULL)
```

```
h2o.uploadFile(path, destination_frame = "", parse = TRUE, header = NA,
  sep = "", col.names = NULL, col.types = NULL, na.strings = NULL,
  progressBar = FALSE, parse_type = NULL, decrypt_tool = NULL)
```

Arguments

| | |
|-------------------|---|
| path | The complete URL or normalized file path of the file to be imported. Each row of data appears as one line of the file. |
| destination_frame | (Optional) The unique hex key assigned to the imported file. If none is given, a key will automatically be generated based on the URL path. |
| parse | (Optional) A logical value indicating whether the file should be parsed after import, for details see h2o.parseRaw . |
| header | (Optional) A logical value indicating whether the first line of the file contains column headers. If left empty, the parser will try to automatically detect this. |
| sep | (Optional) The field separator character. Values on each line of the file are separated by this character. If sep = "", the parser will automatically detect the separator. |
| col.names | (Optional) An H2OFrame object containing a single delimited line with the column names for the file. |
| col.types | (Optional) A vector to specify whether columns should be forced to a certain type upon import parsing. |
| na.strings | (Optional) H2O will interpret these strings as missing. |
| decrypt_tool | (Optional) Specify a Decryption Tool (key-reference acquired by calling h2o.decryptionSetup). |
| pattern | (Optional) Character string containing a regular expression to match file(s) in the folder. |

| | |
|-------------|---|
| progressBar | (Optional) When FALSE, tell H2O parse call to block synchronously instead of polling. This can be faster for small datasets but loses the progress bar. |
| parse_type | (Optional) Specify which parser type H2O will use. Valid types are "ARFF", "XLS", "CSV", "SVMLight" |

Details

h2o.importFile is a parallelized reader and pulls information from the server from a location specified by the client. The path is a server-side path. This is a fast, scalable, highly optimized way to read data. H2O pulls the data from a data store and initiates the data transfer as a read operation.

Unlike the import function, which is a parallelized reader, h2o.uploadFile is a push from the client to the server. The specified path must be a client-side path. This is not scalable and is only intended for smaller data sizes. The client pushes the data from a local filesystem (for example, on your machine where R is running) to H2O. For big-data operations, you don't want the data stored on or flowing through the client.

h2o.importFolder imports an entire directory of files. If the given path is relative, then it will be relative to the start location of the H2O instance. The default behavior is to pass-through to the parse phase automatically.

h2o.importHDFS is deprecated. Instead, use h2o.importFile.

See Also

[h2o.import_sql_select](#), [h2o.import_sql_table](#), [h2o.parseRaw](#)

Examples

```
h2o.init(ip = "localhost", port = 54321, startH2O = TRUE)
prosPath = system.file("extdata", "prostate.csv", package = "h2o")
prostate.hex = h2o.importFile(path = prosPath, destination_frame = "prostate.hex")
class(prostate.hex)
summary(prostate.hex)

#Import files with a certain regex pattern by utilizing h2o.importFolder()
#In this example we import all .csv files in the directory prostate_folder
prosPath = system.file("extdata", "prostate_folder", package = "h2o")
prostate_pattern.hex = h2o.importFolder(path = prosPath, pattern = ".*.csv",
                                       destination_frame = "prostate.hex")
class(prostate_pattern.hex)
summary(prostate_pattern.hex)
```

h2o.import_sql_select *Import SQL table that is result of SELECT SQL query into H2O*

Description

Creates a temporary SQL table from the specified sql_query. Runs multiple SELECT SQL queries on the temporary table concurrently for parallel ingestion, then drops the table. Be sure to start the h2o.jar in the terminal with your downloaded JDBC driver in the classpath: 'java -cp <path_to_h2o_jar>:<path_to_jdbc_driver.jar> water.H2OApp' Also see h2o.import_sql_table. Currently supported SQL databases are MySQL, PostgreSQL, and MariaDB. Support for Oracle 12g and Microsoft SQL Server

Usage

```
h2o.import_sql_select(connection_url, select_query, username, password,
  optimize = NULL)
```

Arguments

| | |
|----------------|---|
| connection_url | URL of the SQL database connection as specified by the Java Database Connectivity (JDBC) Driver. For example, "jdbc:mysql://localhost:3306/menagerie?&useSSL=false" |
| select_query | SQL query starting with 'SELECT' that returns rows from one or more database tables. |
| username | Username for SQL server |
| password | Password for SQL server |
| optimize | (Optional) Optimize import of SQL table for faster imports. Experimental. Default is true. |

Details

```
For example, my_sql_conn_url <- "jdbc:mysql://172.16.2.178:3306/ingestSQL?&useSSL=false"
select_query <- "SELECT bikeid from citibike20k" username <- "root" password <- "abc123"
my_citibike_data <- h2o.import_sql_select(my_sql_conn_url, select_query, username, password)
```

h2o.import_sql_table *Import SQL Table into H2O*

Description

Imports SQL table into an H2O cloud. Assumes that the SQL table is not being updated and is stable. Runs multiple SELECT SQL queries concurrently for parallel ingestion. Be sure to start the h2o.jar in the terminal with your downloaded JDBC driver in the classpath: 'java -cp <path_to_h2o_jar>:<path_to_jdbc_driver_jar> water.H2OApp' Also see h2o.import_sql_select. Currently supported SQL databases are MySQL, PostgreSQL, and MariaDB. Support for Oracle 12g and Microsoft SQL Server

Usage

```
h2o.import_sql_table(connection_url, table, username, password,
  columns = NULL, optimize = NULL)
```

Arguments

| | |
|----------------|---|
| connection_url | URL of the SQL database connection as specified by the Java Database Connectivity (JDBC) Driver. For example, "jdbc:mysql://localhost:3306/menagerie?&useSSL=false" |
| table | Name of SQL table |
| username | Username for SQL server |
| password | Password for SQL server |
| columns | (Optional) Character vector of column names to import from SQL table. Default is to import all columns. |
| optimize | (Optional) Optimize import of SQL table for faster imports. Experimental. Default is true. |

Details

```
For example, my_sql_conn_url <- "jdbc:mysql://172.16.2.178:3306/ingestSQL?&useSSL=false"
table <- "citibike20k" username <- "root" password <- "abc123" my_citibike_data <- h2o.import_sql_table(my_sql_conn
table, username, password)
```

h2o.impute

*Basic Imputation of H2O Vectors***Description**

Perform inplace imputation by filling missing values with aggregates computed on the "na.rm'd" vector. Additionally, it's possible to perform imputation based on groupings of columns from within data; these columns can be passed by index or name to the by parameter. If a factor column is supplied, then the method must be "mode".

Usage

```
h2o.impute(data, column = 0, method = c("mean", "median", "mode"),
  combine_method = c("interpolate", "average", "lo", "hi"), by = NULL,
  groupByFrame = NULL, values = NULL)
```

Arguments

| | |
|----------------|--|
| data | The dataset containing the column to impute. |
| column | A specific column to impute, default of 0 means impute the whole frame. |
| method | "mean" replaces NAs with the column mean; "median" replaces NAs with the column median; "mode" replaces with the most common factor (for factor columns only); |
| combine_method | If method is "median", then choose how to combine quantiles on even sample sizes. This parameter is ignored in all other cases. |
| by | group by columns |
| groupByFrame | Impute the column col with this pre-computed grouped frame. |
| values | A vector of impute values (one per column). NaN indicates to skip the column |

Details

The default method is selected based on the type of the column to impute. If the column is numeric then "mean" is selected; if it is categorical, then "mode" is selected. Other column types (e.g. String, Time, UUID) are not supported.

Value

an H2OFrame with imputed values

Examples

```

h2o.init()
fr <- as.h2o(iris, destination_frame="iris")
fr[sample(nrow(fr),40),5] <- NA # randomly replace 50 values with NA
# impute with a group by
fr <- h2o.impute(fr, "Species", "mode", by=c("Sepal.Length", "Sepal.Width"))

```

h2o.init

*Initialize and Connect to H2O***Description**

Attempts to start and/or connect to and H2O instance.

Usage

```

h2o.init(ip = "localhost", port = 54321, startH2O = TRUE,
  forceDL = FALSE, enable_assertions = TRUE, license = NULL,
  nthreads = -1, max_mem_size = NULL, min_mem_size = NULL,
  ice_root = tempdir(), strict_version_check = TRUE,
  proxy = NA_character_, https = FALSE, insecure = FALSE,
  username = NA_character_, password = NA_character_,
  cookies = NA_character_, context_path = NA_character_,
  ignore_config = FALSE, extra_classpath = NULL)

```

Arguments

| | |
|-------------------|--|
| ip | Object of class character representing the IP address of the server where H2O is running. |
| port | Object of class numeric representing the port number of the H2O server. |
| startH2O | (Optional) A logical value indicating whether to try to start H2O from R if no connection with H2O is detected. This is only possible if ip = "localhost" or ip = "127.0.0.1". If an existing connection is detected, R does not start H2O. |
| forceDL | (Optional) A logical value indicating whether to force download of the H2O executable. Defaults to FALSE, so the executable will only be downloaded if it does not already exist in the h2o R library resources directory h2o/java/h2o.jar. This value is only used when R starts H2O. |
| enable_assertions | (Optional) A logical value indicating whether H2O should be launched with assertions enabled. Used mainly for error checking and debugging purposes. This value is only used when R starts H2O. |
| license | (Optional) A character string value specifying the full path of the license file. This value is only used when R starts H2O. |
| nthreads | (Optional) Number of threads in the thread pool. This relates very closely to the number of CPUs used. -1 means use all CPUs on the host (Default). A positive integer specifies the number of CPUs directly. This value is only used when R starts H2O. |

| | |
|----------------------|---|
| max_mem_size | (Optional) A character string specifying the maximum size, in bytes, of the memory allocation pool to H2O. This value must a multiple of 1024 greater than 2MB. Append the letter m or M to indicate megabytes, or g or G to indicate gigabytes. This value is only used when R starts H2O. |
| min_mem_size | (Optional) A character string specifying the minimum size, in bytes, of the memory allocation pool to H2O. This value must a multiple of 1024 greater than 2MB. Append the letter m or M to indicate megabytes, or g or G to indicate gigabytes. This value is only used when R starts H2O. |
| ice_root | (Optional) A directory to handle object spillage. The default varies by OS. |
| strict_version_check | (Optional) Setting this to FALSE is unsupported and should only be done when advised by technical support. |
| proxy | (Optional) A character string specifying the proxy path. |
| https | (Optional) Set this to TRUE to use https instead of http. |
| insecure | (Optional) Set this to TRUE to disable SSL certificate checking. |
| username | (Optional) Username to login with. |
| password | (Optional) Password to login with. |
| cookies | (Optional) Vector(or list) of cookies to add to request. |
| context_path | (Optional) The last part of connection URL: http://<ip>:<port>/<context_path> |
| ignore_config | (Optional) A logical value indicating whether a search for a .h2oconfig file should be conducted or not. Default value is FALSE. |
| extra_classpath | (Optional) A vector of paths to libraries to be added to the Java classpath when H2O is started from R. |

Details

By default, this method first checks if an H2O instance is connectible. If it cannot connect and `start = TRUE` with `ip = "localhost"`, it will attempt to start an instance of H2O at `localhost:54321`. If an open ip and port of your choice are passed in, then this method will attempt to start an H2O instance at that specified ip port.

When initializing H2O locally, this method searches for `h2o.jar` in the R library resources (`system.file("java", "h2o.` and if the file does not exist, it will automatically attempt to download the correct version from Amazon S3. The user must have Internet access for this process to be successful.

Once connected, the method checks to see if the local H2O R package version matches the version of H2O running on the server. If there is a mismatch and the user indicates she wishes to upgrade, it will remove the local H2O R package and download/install the H2O R package from the server.

Value

this method will load it and return a `H2OConnection` object containing the IP address and port number of the H2O server.

Note

Users may wish to manually upgrade their package (rather than waiting until being prompted), which requires that they fully uninstall and reinstall the H2O package, and the H2O client package. You must unload packages running in the environment before upgrading. It's recommended that users restart R or R studio after upgrading

See Also

[H2O R package documentation](#) for more details. [h2o.shutdown](#) for shutting down from R.

Examples

```
## Not run:
# Try to connect to a local H2O instance that is already running.
# If not found, start a local H2O instance from R with the default settings.
h2o.init()

# Try to connect to a local H2O instance.
# If not found, raise an error.
h2o.init(startH2O = FALSE)

# Try to connect to a local H2O instance that is already running.
# If not found, start a local H2O instance from R with 5 gigabytes of memory.
h2o.init(max_mem_size = "5g")

# Try to connect to a local H2O instance that is already running.
# If not found, start a local H2O instance from R that uses 5 gigabytes of memory.
h2o.init(max_mem_size = "5g")

## End(Not run)
```

h2o.insertMissingValues

Insert Missing Values into an H2OFrame

Description

Randomly replaces a user-specified fraction of entries in an H2O dataset with missing values.

Usage

```
h2o.insertMissingValues(data, fraction = 0.1, seed = -1)
```

Arguments

| | |
|----------|--|
| data | An H2OFrame object representing the dataset. |
| fraction | A number between 0 and 1 indicating the fraction of entries to replace with missing. |
| seed | A random number used to select which entries to replace with missing values. Default of seed = -1 will automatically generate a seed in H2O. |

Value

Returns an H2OFrame object.

WARNING

This will modify the original dataset. Unless this is intended, this function should only be called on a subset of the original.

Examples

```
library(h2o)
h2o.init()
irisPath <- system.file("extdata", "iris.csv", package = "h2o")
iris.hex <- h2o.importFile(path = irisPath)
summary(iris.hex)
irismiss.hex <- h2o.insertMissingValues(iris.hex, fraction = 0.25)
head(irismiss.hex)
summary(irismiss.hex)
```

h2o.interaction

*Categorical Interaction Feature Creation in H2O***Description**

Creates a data frame in H2O with n-th order interaction features between categorical columns, as specified by the user.

Usage

```
h2o.interaction(data, destination_frame, factors, pairwise, max_factors,
               min_occurrence)
```

Arguments

| | |
|-------------------|--|
| data | An H2OFrame object containing the categorical columns. |
| destination_frame | A string indicating the destination key. If empty, this will be auto-generated by H2O. |
| factors | Factor columns (either indices or column names). |
| pairwise | Whether to create pairwise interactions between factors (otherwise create one higher-order interaction). Only applicable if there are 3 or more factors. |
| max_factors | Max. number of factor levels in pair-wise interaction terms (if enforced, one extra catch-all factor will be made) |
| min_occurrence | Min. occurrence threshold for factor levels in pair-wise interaction terms |

Value

Returns an H2OFrame object.

Examples

```
library(h2o)
h2o.init()

# Create some random data
myframe <- h2o.createFrame(rows = 20, cols = 5,
                           seed = -12301283, randomize = TRUE, value = 0,
```



```

        categorical_fraction = 0.8, factors = 10, real_range = 1,
        integer_fraction = 0.2, integer_range = 10,
        binary_fraction = 0, binary_ones_fraction = 0.5,
        missing_fraction = 0.2,
        response_factors = 1)
# Turn integer column into a categorical
myframe[,5] <- as.factor(myframe[,5])
head(myframe, 20)

# Create pairwise interactions
pairwise <- h2o.interaction(myframe, destination_frame = 'pairwise',
                           factors = list(c(1,2),c("C2","C3","C4")),
                           pairwise=TRUE, max_factors = 10, min_occurrence = 1)

head(pairwise, 20)
h2o.levels(pairwise,2)

# Create 5-th order interaction
higherorder <- h2o.interaction(myframe, destination_frame = 'higherorder', factors = c(1,2,3,4,5),
                              pairwise=FALSE, max_factors = 10000, min_occurrence = 1)

head(higherorder, 20)

# Limit the number of factors of the "categoricalized" integer column
# to at most 3 factors, and only if they occur at least twice
head(myframe[,5], 20)
trim_integer_levels <- h2o.interaction(myframe, destination_frame = 'trim_integers', factors = "C5",
                                       pairwise = FALSE, max_factors = 3, min_occurrence = 2)

head(trim_integer_levels, 20)

# Put all together
myframe <- h2o.cbind(myframe, pairwise, higherorder, trim_integer_levels)
myframe
head(myframe,20)
summary(myframe)

```

h2o.isax

iSAX

Description

Compute the iSAX index for a DataFrame which is assumed to be numeric time series data

Usage

```
h2o.isax(x, num_words, max_cardinality, optimize_card = FALSE)
```

Arguments

| | |
|-----------------|--|
| x | an H2OFrame |
| num_words | Number of iSAX words for the timeseries. ie granularity along the time series |
| max_cardinality | Maximum cardinality of the iSAX word. Each word can have less than the max |
| optimize_card | An optimization flag that will find the max cardinality regardless of what is passed in for max_cardinality. |

Value

An H2OFrame with the name of time series, string representation of iSAX word, followed by binary representation

References

http://www.cs.ucr.edu/~eamonn/iSAX_2.0.pdf

<http://www.cs.ucr.edu/~eamonn/SAX.pdf>

| | |
|-----------------|---------------------------|
| h2o.ischaracter | <i>Check if character</i> |
|-----------------|---------------------------|

Description

Check if character

Usage

```
h2o.ischaracter(x)
```

Arguments

x An H2OFrame object.

See Also

[is.character](#) for the base R implementation.

| | |
|--------------|------------------------|
| h2o.isfactor | <i>Check if factor</i> |
|--------------|------------------------|

Description

Check if factor

Usage

```
h2o.isfactor(x)
```

Arguments

x An H2OFrame object.

See Also

[is.factor](#) for the base R implementation.

| | |
|---------------|-------------------------|
| h2o.isnumeric | <i>Check if numeric</i> |
|---------------|-------------------------|

Description

Check if numeric

Usage

```
h2o.isnumeric(x)
```

Arguments

| | |
|---|---------------------|
| x | An H2OFrame object. |
|---|---------------------|

See Also

[is.numeric](#) for the base R implementation.

| | |
|---------------|-------------------------------------|
| h2o.is_client | <i>Check Client Mode Connection</i> |
|---------------|-------------------------------------|

Description

Check Client Mode Connection

Usage

```
h2o.is_client()
```

| | |
|------------------|--|
| h2o.kfold_column | <i>Produce a k-fold column vector.</i> |
|------------------|--|

Description

Create a k-fold vector useful for H2O algorithms that take a `fold_assignments` argument.

Usage

```
h2o.kfold_column(data, nfolds, seed = -1)
```

Arguments

| | |
|--------|---|
| data | A dataframe against which to create the fold column. |
| nfolds | The number of desired folds. |
| seed | A random seed, -1 indicates that H2O will choose one. |

Value

Returns an H2OFrame object with fold assignments.

| | |
|----------------|--|
| h2o.killMinus3 | <i>Dump the stack into the JVM's stdout.</i> |
|----------------|--|

Description

A poor man's profiler, but effective.

Usage

```
h2o.killMinus3()
```

| | |
|------------|--|
| h2o.kmeans | <i>Performs k-means clustering on an H2O dataset</i> |
|------------|--|

Description

Performs k-means clustering on an H2O dataset

Usage

```
h2o.kmeans(training_frame, x, model_id = NULL, validation_frame = NULL,
  nfolds = 0, keep_cross_validation_predictions = FALSE,
  keep_cross_validation_fold_assignment = FALSE, fold_assignment = c("AUTO",
  "Random", "Modulo", "Stratified"), fold_column = NULL,
  ignore_const_cols = TRUE, score_each_iteration = FALSE, k = 1,
  estimate_k = FALSE, user_points = NULL, max_iterations = 10,
  standardize = TRUE, seed = -1, init = c("Random", "PlusPlus",
  "Furthest", "User"), max_runtime_secs = 0,
  categorical_encoding = c("AUTO", "Enum", "OneHotInternal", "OneHotExplicit",
  "Binary", "Eigen", "LabelEncoder", "SortByResponse", "EnumLimited"))
```

Arguments

| | |
|---------------------------------------|---|
| training_frame | Id of the training data frame. |
| x | A vector containing the character names of the predictors in the model. |
| model_id | Destination id for this model; auto-generated if not specified. |
| validation_frame | Id of the validation data frame. |
| nfolds | Number of folds for K-fold cross-validation (0 to disable or >= 2). Defaults to 0. |
| keep_cross_validation_predictions | Logical. Whether to keep the predictions of the cross-validation models. Defaults to FALSE. |
| keep_cross_validation_fold_assignment | Logical. Whether to keep the cross-validation fold assignment. Defaults to FALSE. |

| | |
|----------------------|--|
| fold_assignment | Cross-validation fold assignment scheme, if fold_column is not specified. The 'Stratified' option will stratify the folds based on the response variable, for classification problems. Must be one of: "AUTO", "Random", "Modulo", "Stratified". Defaults to AUTO. |
| fold_column | Column with cross-validation fold index assignment per observation. |
| ignore_const_cols | Logical. Ignore constant columns. Defaults to TRUE. |
| score_each_iteration | Logical. Whether to score during each iteration of model training. Defaults to FALSE. |
| k | The max. number of clusters. If estimate_k is disabled, the model will find k centroids, otherwise it will find up to k centroids. Defaults to 1. |
| estimate_k | Logical. Whether to estimate the number of clusters (<=k) iteratively and deterministically. Defaults to FALSE. |
| user_points | This option allows you to specify a dataframe, where each row represents an initial cluster center. The user-specified points must have the same number of columns as the training observations. The number of rows must equal the number of clusters |
| max_iterations | Maximum training iterations (if estimate_k is enabled, then this is for each inner Lloyds iteration) Defaults to 10. |
| standardize | Logical. Standardize columns before computing distances Defaults to TRUE. |
| seed | Seed for random numbers (affects certain parts of the algo that are stochastic and those might or might not be enabled by default) Defaults to -1 (time-based random number). |
| init | Initialization mode Must be one of: "Random", "PlusPlus", "Furthest", "User". Defaults to Furthest. |
| max_runtime_secs | Maximum allowed runtime in seconds for model training. Use 0 to disable. Defaults to 0. |
| categorical_encoding | Encoding scheme for categorical features Must be one of: "AUTO", "Enum", "OneHotInternal", "OneHotExplicit", "Binary", "Eigen", "LabelEncoder", "Sort-ByResponse", "EnumLimited". Defaults to AUTO. |

Value

Returns an object of class [H2OClusteringModel](#).

See Also

[h2o.cluster_sizes](#), [h2o.totss](#), [h2o.num_iterations](#), [h2o.betweenss](#), [h2o.tot_withinss](#), [h2o.withinss](#), [h2o.centersSTD](#), [h2o.centers](#)

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
```

```
h2o.kmeans(training_frame = prostate.hex, k = 10, x = c("AGE", "RACE", "VOL", "GLEASON"))
```

| | |
|--------------|-----------------------------|
| h2o.kurtosis | <i>Kurtosis of a column</i> |
|--------------|-----------------------------|

Description

Obtain the kurtosis of a column of a parsed H2O data object.

Usage

```
h2o.kurtosis(x, ..., na.rm = TRUE)
```

```
kurtosis.H2OFrame(x, ..., na.rm = TRUE)
```

Arguments

| | |
|-------|--|
| x | An H2OFrame object. |
| ... | Further arguments to be passed from or to other methods. |
| na.rm | A logical value indicating whether NA or missing values should be stripped before the computation. |

Value

Returns a list containing the kurtosis for each column (NaN for non-numeric columns).

Examples

```
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
h2o.kurtosis(prostate.hex$AGE)
```

| | |
|------------|--|
| h2o.levels | <i>Return the levels from the column requested column.</i> |
|------------|--|

Description

Return the levels from the column requested column.

Usage

```
h2o.levels(x, i)
```

Arguments

| | |
|---|---|
| x | An H2OFrame object. |
| i | Optional, the index of the column whose domain is to be returned. |

See Also

[levels](#) for the base R method.

Examples

```
iris.hex <- as.h2o(iris)
h2o.levels(iris.hex, 5) # returns "setosa" "versicolor" "virginica"
```

h2o.listTimezones *List all of the Time Zones Acceptable by the H2O Cloud.*

Description

List all of the Time Zones Acceptable by the H2O Cloud.

Usage

```
h2o.listTimezones()
```

h2o.list_all_extensions
List all H2O registered extensions

Description

List all H2O registered extensions

Usage

```
h2o.list_all_extensions()
```

h2o.list_api_extensions
List registered API extensions

Description

List registered API extensions

Usage

```
h2o.list_api_extensions()
```

```
h2o.list_core_extensions
      List registered core extensions
```

Description

List registered core extensions

Usage

```
h2o.list_core_extensions()
```

```
h2o.loadModel      Load H2O Model from HDFS or Local Disk
```

Description

Load a saved H2O model from disk. (Note that ensemble binary models can now be loaded using this method.)

Usage

```
h2o.loadModel(path)
```

Arguments

path The path of the H2O Model to be imported. and port of the server running H2O.

Value

Returns a [H2OModel](#) object of the class corresponding to the type of model built.

See Also

[h2o.saveModel](#), [H2OModel](#)

Examples

```
## Not run:
# library(h2o)
# h2o.init()
# prosPath = system.file("extdata", "prostate.csv", package = "h2o")
# prostate.hex = h2o.importFile(path = prosPath, destination_frame = "prostate.hex")
# prostate.glm = h2o.glm(y = "CAPSULE", x = c("AGE", "RACE", "PSA", "DCAPS"),
#   training_frame = prostate.hex, family = "binomial", alpha = 0.5)
# glmmodel.path = h2o.saveModel(prostate.glm, dir = "/Users/UserName/Desktop")
# glmmodel.load = h2o.loadModel(glmmodel.path)

## End(Not run)
```

| | |
|---------|-----------------------------------|
| h2o.log | <i>Compute the logarithm of x</i> |
|---------|-----------------------------------|

Description

Compute the logarithm of x

Usage

```
h2o.log(x)
```

Arguments

x An H2OFrame object.

See Also

[log](#) for the base R implementation.

| | |
|-----------|-------------------------------|
| h2o.log10 | <i>Compute the log10 of x</i> |
|-----------|-------------------------------|

Description

Compute the log10 of x

Usage

```
h2o.log10(x)
```

Arguments

x An H2OFrame object.

See Also

[log10](#) for the base R implementation.

| | |
|-----------|-------------------------------|
| h2o.log1p | <i>Compute the log1p of x</i> |
|-----------|-------------------------------|

Description

Compute the log1p of x

Usage

```
h2o.log1p(x)
```

Arguments

x An H2OFrame object.

See Also

[log1p](#) for the base R implementation.

| | |
|----------|------------------------------|
| h2o.log2 | <i>Compute the log2 of x</i> |
|----------|------------------------------|

Description

Compute the log2 of x

Usage

```
h2o.log2(x)
```

Arguments

x An H2OFrame object.

See Also

[log2](#) for the base R implementation.

| | |
|----------------|--|
| h2o.logAndEcho | <i>Log a message on the server-side logs</i> |
|----------------|--|

Description

This is helpful when running several pieces of work one after the other on a single H2O cluster and you want to make a notation in the H2O server side log where one piece of work ends and the next piece of work begins.

Usage

```
h2o.logAndEcho(message)
```

Arguments

| | |
|---------|--|
| message | A character string with the message to write to the log. |
|---------|--|

Details

h2o.logAndEcho sends a message to H2O for logging. Generally used for debugging purposes.

| | |
|-------------|------------------------------------|
| h2o.logloss | <i>Retrieve the Log Loss Value</i> |
|-------------|------------------------------------|

Description

Retrieves the log loss output for a [H2OBinomialMetrics](#) or [H2OMultinomialMetrics](#) object. If "train", "valid", and "xval" parameters are FALSE (default), then the training Log Loss value is returned. If more than one parameter is set to TRUE, then a named vector of Log Losses are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.logloss(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|---|
| object | a H2OModelMetrics object of the correct type. |
| train | Retrieve the training Log Loss |
| valid | Retrieve the validation Log Loss |
| xval | Retrieve the cross-validation Log Loss |

`h2o.ls`*List Keys on an H2O Cluster*

Description

Accesses a list of object keys in the running instance of H2O.

Usage

```
h2o.ls()
```

Value

Returns a list of hex keys in the current H2O instance.

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
h2o.ls()
```

`h2o.lstrip`*Strip set from left*

Description

Return a copy of the target column with leading characters removed. The set argument is a string specifying the set of characters to be removed. If omitted, the set argument defaults to removing whitespace.

Usage

```
h2o.lstrip(x, set = " ")
```

Arguments

| | |
|------------------|---|
| <code>x</code> | The column whose strings should be lstrip-ed. |
| <code>set</code> | string of characters to be removed |

Examples

```
library(h2o)
h2o.init()
string_to_lstrip <- as.h2o("1234567890")
lstrip_string <- h2o.lstrip(string_to_lstrip,"123") #Remove "123"
```

| | |
|---------|---|
| h2o.mae | <i>Retrieve the Mean Absolute Error Value</i> |
|---------|---|

Description

Retrieves the mean absolute error (MAE) value from an H2O model. If "train", "valid", and "xval" parameters are FALSE (default), then the training MAE value is returned. If more than one parameter is set to TRUE, then a named vector of MAEs are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.mae(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|--|
| object | An H2OModel object. |
| train | Retrieve the training MAE |
| valid | Retrieve the validation set MAE if a validation set was passed in during model build time. |
| xval | Retrieve the cross-validation MAE |

Examples

```
library(h2o)

h <- h2o.init()
fr <- as.h2o(iris)

m <- h2o.deeplearning(x=2:5,y=1,training_frame=fr)

h2o.mae(m)
```

| | |
|------------------|---|
| h2o.makeGLMModel | <i>Set betas of an existing H2O GLM Model</i> |
|------------------|---|

Description

This function allows setting betas of an existing glm model.

Usage

```
h2o.makeGLMModel(model, beta)
```

Arguments

| | |
|-------|---|
| model | an H2OModel corresponding from a <code>h2o.glm</code> call. |
| beta | a new set of betas (a named vector) |

| | |
|------------------|---|
| h2o.make_metrics | <i>Create Model Metrics from predicted and actual values in H2O</i> |
|------------------|---|

Description

Given predicted values (target for regression, class-1 probabilities or binomial or per-class probabilities for multinomial), compute a model metrics object

Usage

```
h2o.make_metrics(predicted, actuals, domain = NULL, distribution = NULL)
```

Arguments

| | |
|--------------|--|
| predicted | An H2OFrame containing predictions |
| actuals | An H2OFrame containing actual values |
| domain | Vector with response factors for classification. |
| distribution | Distribution for regression. |

Value

Returns an object of the [H2OModelMetrics](#) subclass.

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
prostate.hex$CAPSULE <- as.factor(prostate.hex$CAPSULE)
prostate.gbm <- h2o.gbm(3:9, "CAPSULE", prostate.hex)
pred <- h2o.predict(prostate.gbm, prostate.hex)[,3] ## class-1 probability
h2o.make_metrics(pred,prostate.hex$CAPSULE)
```

| | |
|-----------|------------------------------|
| h2o.match | <i>Value Matching in H2O</i> |
|-----------|------------------------------|

Description

match and %in% return values similar to the base R generic functions.

Usage

```
h2o.match(x, table, nomatch = 0, incomparables = NULL)

match.H2OFrame(x, table, nomatch = 0, incomparables = NULL)

x %in% table
```

Arguments

| | |
|---------------|--|
| x | a categorical vector from an H2OFrame object with values to be matched. |
| table | an R object to match x against. |
| nomatch | the value to be returned in the case when no match is found. |
| incomparables | a vector of values that cannot be matched. Any value in x matching a value in this vector is assigned the nomatch value. |

Value

Returns a vector of the positions of (first) matches of its first argument in its second

See Also

[match](#) for base R implementation.

Examples

```
h2o.init()
hex <- as.h2o(iris)
h2o.match(hex[,5], c("setosa", "versicolor"))
```

h2o.max

Returns the maxima of the input values.

Description

Returns the maxima of the input values.

Usage

```
h2o.max(x, na.rm = FALSE)
```

Arguments

| | |
|-------|---|
| x | An H2OFrame object. |
| na.rm | logical. indicating whether missing values should be removed. |

See Also

[max](#) for the base R implementation.

| | |
|----------|--|
| h2o.mean | <i>Compute the frame's mean by-column (or by-row).</i> |
|----------|--|

Description

Compute the frame's mean by-column (or by-row).

Usage

```
h2o.mean(x, na.rm = FALSE, axis = 0, return_frame = FALSE, ...)
```

```
## S3 method for class 'H2OFrame'
mean(x, na.rm = FALSE, axis = 0, return_frame = FALSE,
     ...)
```

Arguments

| | |
|--------------|---|
| x | An H2OFrame object. |
| na.rm | logical. Indicate whether missing values should be removed. |
| axis | integer. Indicate whether to calculate the mean down a column (0) or across a row (1). NOTE: This is only applied when return_frame is set to TRUE. Otherwise, this parameter is ignored. |
| return_frame | logical. Indicate whether to return an H2O frame or a list. Default is FALSE (returns a list). |
| ... | Further arguments to be passed from or to other methods. |

Value

Returns a list containing the mean for each column (NaN for non-numeric columns) if return_frame is set to FALSE. If return_frame is set to TRUE, then it will return an H2O frame with means per column or row (depends on axis argument).

See Also

[mean](#) , [rowMeans](#), or [colMeans](#) for the base R implementation

Examples

```
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
# Default behavior. Will return list of means per column.
h2o.mean(prostate.hex$AGE)
# return_frame set to TRUE. This will return an H2O Frame
# with mean per row or column (depends on axis argument)
h2o.mean(prostate.hex, na.rm=TRUE, axis=1, return_frame=TRUE)
```

`h2o.mean_per_class_error`*Retrieve the mean per class error*

Description

Retrieves the mean per class error from an [H2OBinomialMetrics](#). If "train", "valid", and "xval" parameters are FALSE (default), then the training mean per class error value is returned. If more than one parameter is set to TRUE, then a named vector of mean per class errors are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.mean_per_class_error(object, train = FALSE, valid = FALSE,
  xval = FALSE)
```

Arguments

| | |
|---------------------|--|
| <code>object</code> | An H2OBinomialMetrics object. |
| <code>train</code> | Retrieve the training mean per class error |
| <code>valid</code> | Retrieve the validation mean per class error |
| <code>xval</code> | Retrieve the cross-validation mean per class error |

See Also

[h2o.mse](#) for MSE, and [h2o.metric](#) for the various threshold metrics. See [h2o.performance](#) for creating H2OModelMetrics objects.

Examples

```
library(h2o)
h2o.init()

prosPath <- system.file("extdata", "prostate.csv", package="h2o")
hex <- h2o.uploadFile(prosPath)

hex[,2] <- as.factor(hex[,2])
model <- h2o.gbm(x = 3:9, y = 2, training_frame = hex, distribution = "bernoulli")
perf <- h2o.performance(model, hex)
h2o.mean_per_class_error(perf)
h2o.mean_per_class_error(model, train=TRUE)
```

```
h2o.mean_residual_deviance
```

Retrieve the Mean Residual Deviance value

Description

Retrieves the Mean Residual Deviance value from an H2O model. If "train", "valid", and "xval" parameters are FALSE (default), then the training Mean Residual Deviance value is returned. If more than one parameter is set to TRUE, then a named vector of Mean Residual Deviances are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.mean_residual_deviance(object, train = FALSE, valid = FALSE,
  xval = FALSE)
```

Arguments

| | |
|--------|--|
| object | An H2OModel object. |
| train | Retrieve the training Mean Residual Deviance |
| valid | Retrieve the validation Mean Residual Deviance |
| xval | Retrieve the cross-validation Mean Residual Deviance |

Examples

```
library(h2o)

h <- h2o.init()
fr <- as.h2o(iris)

m <- h2o.deeplearning(x=2:5,y=1,training_frame=fr)

h2o.mean_residual_deviance(m)
```

```
h2o.median
```

H2O Median

Description

Compute the median of an H2OFrame.

Usage

```
h2o.median(x, na.rm = TRUE)

## S3 method for class 'H2OFrame'
median(x, na.rm = TRUE)
```

Arguments

| | |
|-------|---|
| x | An H2OFrame object. |
| na.rm | a logical, indicating whether na's are omitted. |

Value

Returns a list containing the median for each column (NaN for non-numeric columns)

Examples

```
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath, destination_frame = "prostate.hex")
h2o.median(prostate.hex)
```

h2o.merge

Merge Two H2O Data Frames

Description

Merges two H2OFrame objects with the same arguments and meanings as merge() in base R. However, we do not support all=TRUE, all.x=TRUE and all.y=TRUE. The default method is auto and it will default to the radix method. The radix method will return the correct merge result regardless of duplicated rows in the right frame. In addition, the radix method can perform merge even if you have string columns in your frames. If there are duplicated rows in your rite frame, they will not be included if you use the hash method. The hash method cannot perform merge if you have string columns in your left frame. Hence, we consider the radix method superior to the hash method and is the default method to use.

Usage

```
h2o.merge(x, y, by = intersect(names(x), names(y)), by.x = by, by.y = by,
  all = FALSE, all.x = all, all.y = all, method = "auto")
```

Arguments

| | |
|--------|--|
| x, y | H2OFrame objects |
| by | columns used for merging by default the common names |
| by.x | x columns used for merging by name or number |
| by.y | y columns used for merging by name or number |
| all | TRUE includes all rows in x and all rows in y even if there is no match to the other |
| all.x | If all.x is true, all rows in the x will be included, even if there is no matching row in y, and vice-versa for all.y. |
| all.y | see all.x |
| method | auto(default), radix, hash |

Examples

```
h2o.init()
left <- data.frame(fruit = c('apple', 'orange', 'banana', 'lemon', 'strawberry', 'blueberry'),
  color <- c('red', 'orange', 'yellow', 'yellow', 'red', 'blue'))
right <- data.frame(fruit = c('apple', 'orange', 'banana', 'lemon', 'strawberry', 'watermelon'),
  citrus <- c(FALSE, TRUE, FALSE, TRUE, FALSE, FALSE))
l.hex <- as.h2o(left)
r.hex <- as.h2o(right)
left.hex <- h2o.merge(l.hex, r.hex, all.x = TRUE)
```

h2o.metric

H2O Model Metric Accessor Functions

Description

A series of functions that retrieve model metric details.

Usage

```
h2o.metric(object, thresholds, metric)

h2o.F0point5(object, thresholds)

h2o.F1(object, thresholds)

h2o.F2(object, thresholds)

h2o.accuracy(object, thresholds)

h2o.error(object, thresholds)

h2o.maxPerClassError(object, thresholds)

h2o.mean_per_class_accuracy(object, thresholds)

h2o.mcc(object, thresholds)

h2o.precision(object, thresholds)

h2o.tpr(object, thresholds)

h2o.fpr(object, thresholds)

h2o.fnr(object, thresholds)

h2o.tnr(object, thresholds)

h2o.recall(object, thresholds)
```

```
h2o.sensitivity(object, thresholds)
```

```
h2o.fallout(object, thresholds)
```

```
h2o.missrate(object, thresholds)
```

```
h2o.specificity(object, thresholds)
```

Arguments

| | |
|------------|--|
| object | An H2OModelMetrics object of the correct type. |
| thresholds | (Optional) A value or a list of values between 0.0 and 1.0. |
| metric | (Optional) A specified parameter to retrieve. |

Details

Many of these functions have an optional thresholds parameter. Currently only increments of 0.1 are allowed. If not specified, the functions will return all possible values. Otherwise, the function will return the value for the indicated threshold.

Currently, these functions are only supported by [H2OBinomialMetrics](#) objects.

Value

Returns either a single value, or a list of values.

See Also

[h2o.auc](#) for AUC, [h2o.giniCoef](#) for the GINI coefficient, and [h2o.mse](#) for MSE. See [h2o.performance](#) for creating [H2OModelMetrics](#) objects.

Examples

```
library(h2o)
h2o.init()

prosPath <- system.file("extdata", "prostate.csv", package="h2o")
hex <- h2o.uploadFile(prosPath)

hex[,2] <- as.factor(hex[,2])
model <- h2o.gbm(x = 3:9, y = 2, training_frame = hex, distribution = "bernoulli")
perf <- h2o.performance(model, hex)
h2o.F1(perf)
```

| | |
|---------|--|
| h2o.min | <i>Returns the minima of the input values.</i> |
|---------|--|

Description

Returns the minima of the input values.

Usage

```
h2o.min(x, na.rm = FALSE)
```

Arguments

| | |
|-------|---|
| x | An H2OFrame object. |
| na.rm | logical. indicating whether missing values should be removed. |

See Also

[min](#) for the base R implementation.

| | |
|------------|--|
| h2o.mktime | <i>Compute msec since the Unix Epoch</i> |
|------------|--|

Description

Compute msec since the Unix Epoch

Usage

```
h2o.mktime(year = 1970, month = 0, day = 0, hour = 0, minute = 0,
           second = 0, msec = 0)
```

Arguments

| | |
|--------|---------------------------------|
| year | Defaults to 1970 |
| month | zero based (months are 0 to 11) |
| day | zero based (days are 0 to 30) |
| hour | hour |
| minute | minute |
| second | second |
| msec | msec |

| | |
|-----------|---|
| h2o.month | <i>Convert Milliseconds to Months in H2O Datasets</i> |
|-----------|---|

Description

Converts the entries of an H2OFrame object from milliseconds to months (on a 1 to 12 scale).

Usage

```
h2o.month(x)

month(x)

## S3 method for class 'H2OFrame'
month(x)
```

Arguments

x An H2OFrame object.

Value

An H2OFrame object containing the entries of x converted to months of the year.

See Also

[h2o.year](#)

| | |
|---------|---|
| h2o.mse | <i>Retrieves Mean Squared Error Value</i> |
|---------|---|

Description

Retrieves the mean squared error value from an [H2OModelMetrics](#) object. If "train", "valid", and "xval" parameters are FALSE (default), then the training MSEvalue is returned. If more than one parameter is set to TRUE, then a named vector of MSEs are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.mse(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|--|
| object | An H2OModelMetrics object of the correct type. |
| train | Retrieve the training MSE |
| valid | Retrieve the validation MSE |
| xval | Retrieve the cross-validation MSE |

Details

This function only supports [H2OBinomialMetrics](#), [H2OMultinomialMetrics](#), and [H2ORegressionMetrics](#) objects.

See Also

[h2o.auc](#) for AUC, [h2o.mse](#) for MSE, and [h2o.metric](#) for the various threshold metrics. See [h2o.performance](#) for creating H2OModelMetrics objects.

Examples

```
library(h2o)
h2o.init()

prosPath <- system.file("extdata", "prostate.csv", package="h2o")
hex <- h2o.uploadFile(prosPath)

hex[,2] <- as.factor(hex[,2])
model <- h2o.gbm(x = 3:9, y = 2, training_frame = hex, distribution = "bernoulli")
perf <- h2o.performance(model, hex)
h2o.mse(perf)
```

h2o.nacnt

Count of NAs per column

Description

Gives the count of NAs per column.

Usage

```
h2o.nacnt(x)
```

Arguments

x An H2OFrame object.

Value

Returns a list containing the count of NAs per column

Examples

```
h2o.init()
iris.hex <- as.h2o(iris)
h2o.nacnt(iris.hex) # should return all 0s
h2o.insertMissingValues(iris.hex)
h2o.nacnt(iris.hex)
```

h2o.naiveBayes

Compute naive Bayes probabilities on an H2O dataset.

Description

The naive Bayes classifier assumes independence between predictor variables conditional on the response, and a Gaussian distribution of numeric predictors with mean and standard deviation computed from the training dataset. When building a naive Bayes classifier, every row in the training dataset that contains at least one NA will be skipped completely. If the test dataset has missing values, then those predictors are omitted in the probability calculation during prediction.

Usage

```
h2o.naiveBayes(x, y, training_frame, model_id = NULL, nfolds = 0,
  seed = -1, fold_assignment = c("AUTO", "Random", "Modulo", "Stratified"),
  fold_column = NULL, keep_cross_validation_predictions = FALSE,
  keep_cross_validation_fold_assignment = FALSE, validation_frame = NULL,
  ignore_const_cols = TRUE, score_each_iteration = FALSE,
  balance_classes = FALSE, class_sampling_factors = NULL,
  max_after_balance_size = 5, max_hit_ratio_k = 0, laplace = 0,
  threshold = 0.001, min_sdev = 0.001, eps = 0, eps_sdev = 0,
  min_prob = 0.001, eps_prob = 0, compute_metrics = TRUE,
  max_runtime_secs = 0)
```

Arguments

- | | |
|-----------------------------------|--|
| x | (Optional) A vector containing the names or indices of the predictor variables to use in building the model. If x is missing, then all columns except y are used. |
| y | The name or column index of the response variable in the data. The response must be either a numeric or a categorical/factor variable. If the response is numeric, then a regression model will be trained, otherwise it will train a classification model. |
| training_frame | Id of the training data frame. |
| model_id | Destination id for this model; auto-generated if not specified. |
| nfolds | Number of folds for K-fold cross-validation (0 to disable or >= 2). Defaults to 0. |
| seed | Seed for random numbers (affects certain parts of the algo that are stochastic and those might or might not be enabled by default) Defaults to -1 (time-based random number). |
| fold_assignment | Cross-validation fold assignment scheme, if fold_column is not specified. The 'Stratified' option will stratify the folds based on the response variable, for classification problems. Must be one of: "AUTO", "Random", "Modulo", "Stratified". Defaults to AUTO. |
| fold_column | Column with cross-validation fold index assignment per observation. |
| keep_cross_validation_predictions | Logical. Whether to keep the predictions of the cross-validation models. Defaults to FALSE. |

| | |
|---------------------------------------|---|
| keep_cross_validation_fold_assignment | Logical. Whether to keep the cross-validation fold assignment. Defaults to FALSE. |
| validation_frame | Id of the validation data frame. |
| ignore_const_cols | Logical. Ignore constant columns. Defaults to TRUE. |
| score_each_iteration | Logical. Whether to score during each iteration of model training. Defaults to FALSE. |
| balance_classes | Logical. Balance training data class counts via over/under-sampling (for imbalanced data). Defaults to FALSE. |
| class_sampling_factors | Desired over/under-sampling ratios per class (in lexicographic order). If not specified, sampling factors will be automatically computed to obtain class balance during training. Requires balance_classes. |
| max_after_balance_size | Maximum relative size of the training data after balancing class counts (can be less than 1.0). Requires balance_classes. Defaults to 5.0. |
| max_hit_ratio_k | Max. number (top K) of predictions to use for hit ratio computation (for multi-class only, 0 to disable) Defaults to 0. |
| laplace | Laplace smoothing parameter Defaults to 0. |
| threshold | This argument is deprecated, use 'min_sdev' instead. The minimum standard deviation to use for observations without enough data. Must be at least 1e-10. |
| min_sdev | The minimum standard deviation to use for observations without enough data. Must be at least 1e-10. |
| eps | This argument is deprecated, use 'eps_sdev' instead. A threshold cutoff to deal with numeric instability, must be positive. |
| eps_sdev | A threshold cutoff to deal with numeric instability, must be positive. |
| min_prob | Min. probability to use for observations with not enough data. |
| eps_prob | Cutoff below which probability is replaced with min_prob. |
| compute_metrics | Logical. Compute metrics on training data Defaults to TRUE. |
| max_runtime_secs | Maximum allowed runtime in seconds for model training. Use 0 to disable. Defaults to 0. |

Details

The naive Bayes classifier assumes independence between predictor variables conditional on the response, and a Gaussian distribution of numeric predictors with mean and standard deviation computed from the training dataset. When building a naive Bayes classifier, every row in the training dataset that contains at least one NA will be skipped completely. If the test dataset has missing values, then those predictors are omitted in the probability calculation during prediction.

Value

Returns an object of class [H2OBinomialModel](#) if the response has two categorical levels, and [H2OMultinomialModel](#) otherwise.

Examples

```
h2o.init()
votesPath <- system.file("extdata", "housevotes.csv", package="h2o")
votes.hex <- h2o.uploadFile(path = votesPath, header = TRUE)
h2o.naiveBayes(x = 2:17, y = 1, training_frame = votes.hex, laplace = 3)
```

| | |
|-----------|------------------------------------|
| h2o.names | <i>Column names of an H2OFrame</i> |
|-----------|------------------------------------|

Description

Column names of an H2OFrame

Usage

```
h2o.names(x)
```

Arguments

x An H2OFrame object.

See Also

[names](#) for the base R implementation.

| | |
|-------------|-----------------------------|
| h2o.na_omit | <i>Remove Rows With NAs</i> |
|-------------|-----------------------------|

Description

Remove Rows With NAs

Usage

```
h2o.na_omit(object, ...)
```

Arguments

object H2OFrame object
... Ignored

Value

Returns an H2OFrame object containing non-NA rows.

| | |
|-----------|----------------------|
| h2o.nchar | <i>String length</i> |
|-----------|----------------------|

Description

String length

Usage

```
h2o.nchar(x)
```

Arguments

x The column whose string lengths will be returned.

Examples

```
library(h2o)
h2o.init()
string_to_nchar <- as.h2o("r tutorial")
nchar_string <- h2o.nchar(string_to_nchar)
```

| | |
|----------|---|
| h2o.ncol | <i>Return the number of columns present in x.</i> |
|----------|---|

Description

Return the number of columns present in x.

Usage

```
h2o.ncol(x)
```

Arguments

x An H2OFrame object.

See Also

[ncol](#) for the base R implementation.

| | |
|-----------------|-----------------------------------|
| h2o.networkTest | <i>View Network Traffic Speed</i> |
|-----------------|-----------------------------------|

Description

View speed with various file sizes.

Usage

```
h2o.networkTest()
```

Value

Returns a table listing the network speed for 1B, 10KB, and 10MB.

| | |
|-------------|--|
| h2o.nlevels | <i>Get the number of factor levels for this frame.</i> |
|-------------|--|

Description

Get the number of factor levels for this frame.

Usage

```
h2o.nlevels(x)
```

Arguments

| | |
|---|---------------------|
| x | An H2OFrame object. |
|---|---------------------|

See Also

[nlevels](#) for the base R method.

| | |
|-----------------|-----------------------------|
| h2o.no_progress | <i>Disable Progress Bar</i> |
|-----------------|-----------------------------|

Description

Disable Progress Bar

Usage

```
h2o.no_progress()
```

| | |
|----------|--|
| h2o.nrow | <i>Return the number of rows present in x.</i> |
|----------|--|

Description

Return the number of rows present in x.

Usage

```
h2o.nrow(x)
```

Arguments

| | |
|---|---------------------|
| x | An H2OFrame object. |
|---|---------------------|

See Also

[nrow](#) for the base R implementation.

| | |
|-------------------|-----------------------------------|
| h2o.null_deviance | <i>Retrieve the null deviance</i> |
|-------------------|-----------------------------------|

Description

If "train", "valid", and "xval" parameters are FALSE (default), then the training null deviance value is returned. If more than one parameter is set to TRUE, then a named vector of null deviances are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.null_deviance(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|--|
| object | An H2OModel or H2OModelMetrics |
| train | Retrieve the training null deviance |
| valid | Retrieve the validation null deviance |
| xval | Retrieve the cross-validation null deviance |

| | |
|--------------|---|
| h2o.null_dof | <i>Retrieve the null degrees of freedom</i> |
|--------------|---|

Description

If "train", "valid", and "xval" parameters are FALSE (default), then the training null degrees of freedom value is returned. If more than one parameter is set to TRUE, then a named vector of null degrees of freedom are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.null_dof(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|--|
| object | An H2OModel or H2OModelMetrics |
| train | Retrieve the training null degrees of freedom |
| valid | Retrieve the validation null degrees of freedom |
| xval | Retrieve the cross-validation null degrees of freedom |

| | |
|--------------------|---|
| h2o.num_iterations | <i>Retrieve the number of iterations.</i> |
|--------------------|---|

Description

Retrieve the number of iterations.

Usage

```
h2o.num_iterations(object)
```

Arguments

| | |
|--------|---|
| object | An H2OClusteringModel object. |
| ... | further arguments to be passed on (currently unimplemented) |

h2o.num_valid_substrings
Count of substrings >= 2 chars that are contained in file

Description

Find the count of all possible substrings >= 2 chars that are contained in the specified line-separated text file.

Usage

```
h2o.num_valid_substrings(x, path)
```

Arguments

| | |
|------|---|
| x | The column on which to calculate the number of valid substrings. |
| path | Path to text file containing line-separated strings to be referenced. |

h2o.openLog *View H2O R Logs*

Description

Open existing logs of H2O R POST commands and error responses on local disk. Used primarily for debugging purposes.

Usage

```
h2o.openLog(type)
```

Arguments

| | |
|------|--------------------------|
| type | Currently unimplemented. |
|------|--------------------------|

See Also

[h2o.startLogging](#), [h2o.stopLogging](#), [h2o.clearLog](#)

Examples

```
## Not run:
h2o.init()

h2o.startLogging()
ausPath = system.file("extdata", "australia.csv", package="h2o")
australia.hex = h2o.importFile(path = ausPath)
h2o.stopLogging()

# Not run to avoid windows being opened during R CMD check
# h2o.openLog("Command")
# h2o.openLog("Error")

## End(Not run)
```

| | |
|--------------|-------------------------|
| h2o.parseRaw | <i>H2O Data Parsing</i> |
|--------------|-------------------------|

Description

The second phase in the data ingestion step.

Usage

```
h2o.parseRaw(data, pattern = "", destination_frame = "", header = NA,
  sep = "", col.names = NULL, col.types = NULL, na.strings = NULL,
  blocking = FALSE, parse_type = NULL, chunk_size = NULL,
  decrypt_tool = NULL)
```

Arguments

| | |
|-------------------|---|
| data | An H2OFrame object to be parsed. |
| pattern | (Optional) Character string containing a regular expression to match file(s) in the folder. |
| destination_frame | (Optional) The hex key assigned to the parsed file. |
| header | (Optional) A logical value indicating whether the first row is the column header. If missing, H2O will automatically try to detect the presence of a header. |
| sep | (Optional) The field separator character. Values on each line of the file are separated by this character. If sep = "", the parser will automatically detect the separator. |
| col.names | (Optional) An H2OFrame object containing a single delimited line with the column names for the file. |
| col.types | (Optional) A vector specifying the types to attempt to force over columns. |
| na.strings | (Optional) H2O will interpret these strings as missing. |
| blocking | (Optional) Tell H2O parse call to block synchronously instead of polling. This can be faster for small datasets but loses the progress bar. |
| parse_type | (Optional) Specify which parser type H2O will use. Valid types are "ARFF", "XLS", "CSV", "SVMLight" |
| chunk_size | size of chunk of (input) data in bytes |
| decrypt_tool | (Optional) Specify a Decryption Tool (key-reference acquired by calling h2o.decryptSetup). |

Details

Parse the Raw Data produced by the import phase.

See Also

[h2o.importFile](#), [h2o.parseSetup](#)

| | |
|----------------|--|
| h2o.parseSetup | <i>Get a parse setup back for the staged data.</i> |
|----------------|--|

Description

Get a parse setup back for the staged data.

Usage

```
h2o.parseSetup(data, pattern = "", destination_frame = "", header = NA,
  sep = "", col.names = NULL, col.types = NULL, na.strings = NULL,
  parse_type = NULL, chunk_size = NULL, decrypt_tool = NULL)
```

Arguments

| | |
|-------------------|---|
| data | An H2OFrame object to be parsed. |
| pattern | (Optional) Character string containing a regular expression to match file(s) in the folder. |
| destination_frame | (Optional) The hex key assigned to the parsed file. |
| header | (Optional) A logical value indicating whether the first row is the column header. If missing, H2O will automatically try to detect the presence of a header. |
| sep | (Optional) The field separator character. Values on each line of the file are separated by this character. If sep = "", the parser will automatically detect the separator. |
| col.names | (Optional) An H2OFrame object containing a single delimited line with the column names for the file. |
| col.types | (Optional) A vector specifying the types to attempt to force over columns. |
| na.strings | (Optional) H2O will interpret these strings as missing. |
| parse_type | (Optional) Specify which parser type H2O will use. Valid types are "ARFF", "XLS", "CSV", "SVMLight" |
| chunk_size | size of chunk of (input) data in bytes |
| decrypt_tool | (Optional) Specify a Decryption Tool (key-reference acquired by calling h2o.decryptionSetup). |

See Also

[h2o.parseRaw](#)

| | |
|-----------------|---------------------------------|
| h2o.partialPlot | <i>Partial Dependence Plots</i> |
|-----------------|---------------------------------|

Description

Partial dependence plot gives a graphical depiction of the marginal effect of a variable on the response. The effect of a variable is measured in change in the mean response. Note: Unlike random-Forest's partialPlot when plotting partial dependence the mean response (probabilities) is returned rather than the mean of the log class probability.

Usage

```
h2o.partialPlot(object, data, cols, destination_key, nbins = 20,
  plot = TRUE, plot_stddev = TRUE)
```

Arguments

| | |
|-----------------|---|
| object | An H2OModel object. |
| data | An H2OFrame object used for scoring and constructing the plot. |
| cols | Feature(s) for which partial dependence will be calculated. |
| destination_key | An key reference to the created partial dependence tables in H2O. |
| nbins | Number of bins used. For categorical columns make sure the number of bins exceed the level count. |
| plot | A logical specifying whether to plot partial dependence table. |
| plot_stddev | A logical specifying whether to add std err to partial dependence plot. |

Value

Plot and list of calculated mean response tables for each feature requested.

Examples

```
library(h2o)
h2o.init()
prostate.path <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prostate.path, destination_frame = "prostate.hex")
prostate.hex[, "CAPSULE"] <- as.factor(prostate.hex[, "CAPSULE"])
prostate.hex[, "RACE"] <- as.factor(prostate.hex[, "RACE"])
prostate.gbm <- h2o.gbm(x = c("AGE", "RACE"),
  y = "CAPSULE",
  training_frame = prostate.hex,
  ntrees = 10,
  max_depth = 5,
  learn_rate = 0.1)
h2o.partialPlot(object = prostate.gbm, data = prostate.hex, cols = c("AGE", "RACE"))
```

h2o.performance

*Model Performance Metrics in H2O***Description**

Given a trained h2o model, compute its performance on the given dataset

Usage

```
h2o.performance(model, newdata = NULL, train = FALSE, valid = FALSE,
  xval = FALSE, data = NULL)
```

Arguments

| | |
|---------|---|
| model | An H2OModel object |
| newdata | An H2OFrame. The model will make predictions on this dataset, and subsequently score them. The dataset should match the dataset that was used to train the model, in terms of column names, types, and dimensions. If newdata is passed in, then train, valid, and xval are ignored. |
| train | A logical value indicating whether to return the training metrics (constructed during training). Note: when the trained h2o model uses balance_classes, the training metrics constructed during training will be from the balanced training dataset. For more information visit: https://0xdata.atlassian.net/browse/TN-9 |
| valid | A logical value indicating whether to return the validation metrics (constructed during training). |
| xval | A logical value indicating whether to return the cross-validation metrics (constructed during training). |
| data | (DEPRECATED) An H2OFrame. This argument is now called 'newdata'. |

Value

Returns an object of the [H2OModelMetrics](#) subclass.

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
prostate.hex$CAPSULE <- as.factor(prostate.hex$CAPSULE)
prostate.gbm <- h2o.gbm(3:9, "CAPSULE", prostate.hex)
h2o.performance(model = prostate.gbm, newdata=prostate.hex)

## If model uses balance_classes
## the results from train = TRUE will not match the results from newdata = prostate.hex
prostate.gbm.balanced <- h2o.gbm(3:9, "CAPSULE", prostate.hex, balance_classes = TRUE)
h2o.performance(model = prostate.gbm.balanced, newdata = prostate.hex)
h2o.performance(model = prostate.gbm.balanced, train = TRUE)
```

| | |
|-----------|----------------------|
| h2o.pivot | <i>Pivot a frame</i> |
|-----------|----------------------|

Description

Pivot the frame designated by the three columns: index, column, and value. Index and column should be of type enum, int, or time. For cases of multiple indexes for a column label, the aggregation method is to pick the first occurrence in the data frame

Usage

```
h2o.pivot(x, index, column, value)
```

Arguments

| | |
|--------|--|
| x | an H2OFrame |
| index | the column where pivoted rows should be aligned on |
| column | the column to pivot |
| value | values of the pivoted table |

Value

An H2OFrame with columns from the columns arg, aligned on the index arg, with values from values arg

| | |
|------------|--|
| h2o.prcomp | <i>Principal component analysis of an H2O data frame</i> |
|------------|--|

Description

Principal components analysis of an H2O data frame using the power method to calculate the singular value decomposition of the Gram matrix.

Usage

```
h2o.prcomp(training_frame, x, model_id = NULL, validation_frame = NULL,
  ignore_const_cols = TRUE, score_each_iteration = FALSE,
  transform = c("NONE", "STANDARDIZE", "NORMALIZE", "DEMEAN", "DESCALE"),
  pca_method = c("GramSVD", "Power", "Randomized", "GLRM"), k = 1,
  max_iterations = 1000, use_all_factor_levels = FALSE,
  compute_metrics = TRUE, impute_missing = FALSE, seed = -1,
  max_runtime_secs = 0)
```

Arguments

| | |
|-----------------------|---|
| training_frame | Id of the training data frame. |
| x | A vector containing the character names of the predictors in the model. |
| model_id | Destination id for this model; auto-generated if not specified. |
| validation_frame | Id of the validation data frame. |
| ignore_const_cols | Logical. Ignore constant columns. Defaults to TRUE. |
| score_each_iteration | Logical. Whether to score during each iteration of model training. Defaults to FALSE. |
| transform | Transformation of training data Must be one of: "NONE", "STANDARDIZE", "NORMALIZE", "DEMEAN", "DESCALE". Defaults to NONE. |
| pca_method | Method for computing PCA (Caution: GLRM is currently experimental and unstable) Must be one of: "GramSVD", "Power", "Randomized", "GLRM". Defaults to GramSVD. |
| k | Rank of matrix approximation Defaults to 1. |
| max_iterations | Maximum training iterations Defaults to 1000. |
| use_all_factor_levels | Logical. Whether first factor level is included in each categorical expansion Defaults to FALSE. |
| compute_metrics | Logical. Whether to compute metrics on the training data Defaults to TRUE. |
| impute_missing | Logical. Whether to impute missing entries with the column mean Defaults to FALSE. |
| seed | Seed for random numbers (affects certain parts of the algo that are stochastic and those might or might not be enabled by default) Defaults to -1 (time-based random number). |
| max_runtime_secs | Maximum allowed runtime in seconds for model training. Use 0 to disable. Defaults to 0. |

Value

Returns an object of class [H2ODimReductionModel](#).

References

N. Halko, P.G. Martinsson, J.A. Tropp. Finding structure with randomness: Probabilistic algorithms for constructing approximate matrix decompositions[<http://arxiv.org/abs/0909.4061>]. SIAM Rev., Survey and Review section, Vol. 53, num. 2, pp. 217-288, June 2011.

See Also

[h2o.svd](#), [h2o.glm](#)

Examples

```
library(h2o)
h2o.init()
ausPath <- system.file("extdata", "australia.csv", package="h2o")
australia.hex <- h2o.uploadFile(path = ausPath)
h2o.prcomp(training_frame = australia.hex, k = 8, transform = "STANDARDIZE")
```

| | |
|------------------|---|
| h2o.predict_json | <i>H2O Prediction from R without having H2O running</i> |
|------------------|---|

Description

Provides the method h2o.predict with which you can predict a MOJO or POJO Jar model from R.

Usage

```
h2o.predict_json(model, json, genmodelpath, labels, classpath, javaoptions)
```

Arguments

| | |
|--------------|---|
| model | String with file name of MOJO or POJO Jar |
| json | JSON String with inputs to model |
| genmodelpath | (Optional) path name to h2o-genmodel.jar, if not set defaults to same dir as MOJO |
| labels | (Optional) if TRUE then show output labels in result |
| classpath | (Optional) Extra items for the class path of where to look for Java classes, e.g., h2o-genmodel.jar |
| javaoptions | (Optional) Java options string, default if "-Xmx4g" |

Value

Returns an object with the prediction result

Examples

```
library(h2o)
h2o.predict_json('~/GBM_model_python_1473313897851_6.zip', '{"C7":1}')
h2o.predict_json('~/GBM_model_python_1473313897851_6.zip', '{"C7":1}', c(".", "lib"))
```

| | |
|-----------|--------------------------|
| h2o.print | <i>Print An H2OFrame</i> |
|-----------|--------------------------|

Description

Print An H2OFrame

Usage

```
h2o.print(x, n = 6L)
```

Arguments

| | |
|-----|--|
| x | An H2OFrame object |
| n | An (Optional) A single integer. If positive, number of rows in x to return. If negative, all but the n first/last number of rows in x. Anything bigger than 20 rows will require asking the server (first 20 rows are cached on the client). |
| ... | Further arguments to be passed from or to other methods. |

| | |
|----------|---|
| h2o.prod | <i>Return the product of all the values present in its arguments.</i> |
|----------|---|

Description

Return the product of all the values present in its arguments.

Usage

```
h2o.prod(x)
```

Arguments

| | |
|---|---------------------|
| x | An H2OFrame object. |
|---|---------------------|

See Also

[prod](#) for the base R implementation.

h2o.proj_archetypes *Convert Archetypes to Features from H2O GLRM Model*

Description

Project each archetype in an H2O GLRM model into the corresponding feature space from the H2O training frame.

Usage

```
h2o.proj_archetypes(object, data, reverse_transform = FALSE)
```

Arguments

| | |
|-------------------|--|
| object | An H2ODimReductionModel object that represents the model containing archetypes to be projected. |
| data | An H2OFrame object representing the training data for the H2O GLRM model. |
| reverse_transform | (Optional) A logical value indicating whether to reverse the transformation from model-building by re-scaling columns and adding back the offset to each column of the projected archetypes. |

Value

Returns an H2OFrame object containing the projection of the archetypes down into the original feature space, where each row is one archetype.

See Also

[h2o.glm](#) for making an H2ODimReductionModel.

Examples

```
library(h2o)
h2o.init()
irisPath <- system.file("extdata", "iris_wheader.csv", package="h2o")
iris.hex <- h2o.uploadFile(path = irisPath)
iris.glm <- h2o.glm(training_frame = iris.hex, k = 4, loss = "Quadratic",
                   multi_loss = "Categorical", max_iterations = 1000)
iris.parch <- h2o.proj_archetypes(iris.glm, iris.hex)
head(iris.parch)
```

h2o.quantile *Quantiles of H2O Frames.*

Description

Obtain and display quantiles for H2O parsed data.

Usage

```
h2o.quantile(x, probs = c(0.001, 0.01, 0.1, 0.25, 0.333, 0.5, 0.667, 0.75,
  0.9, 0.99, 0.999), combine_method = c("interpolate", "average", "avg",
  "low", "high"), weights_column = NULL, ...)

## S3 method for class 'H2OFrame'
quantile(x, probs = c(0.001, 0.01, 0.1, 0.25, 0.333, 0.5,
  0.667, 0.75, 0.9, 0.99, 0.999), combine_method = c("interpolate", "average",
  "avg", "low", "high"), weights_column = NULL, ...)
```

Arguments

| | |
|----------------|--|
| x | An H2OFrame object with a single numeric column. |
| probs | Numeric vector of probabilities with values in [0,1]. |
| combine_method | How to combine quantiles for even sample sizes. Default is to do linear interpolation. E.g., If method is "lo", then it will take the lo value of the quantile. Abbreviations for average, low, and high are acceptable (avg, lo, hi). |
| weights_column | (Optional) String name of the observation weights column in x or an H2OFrame object with a single numeric column of observation weights. |
| ... | Further arguments passed to or from other methods. |

Details

quantile.H2OFrame, a method for the [quantile](#) generic. Obtain and return quantiles for an H2OFrame object.

Value

A vector describing the percentiles at the given cutoffs for the H2OFrame object.

Examples

```
# Request quantiles for an H2O parsed data set:
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
# Request quantiles for a subset of columns in an H2O parsed data set
quantile(prostate.hex[,3])
for(i in 1:ncol(prostate.hex))
  quantile(prostate.hex[,i])
```

| | |
|--------|------------------------------|
| h2o.r2 | <i>Retrieve the R2 value</i> |
|--------|------------------------------|

Description

Retrieves the R2 value from an H2O model. Will return R^2 for GLM Models and will return NaN otherwise. If "train", "valid", and "xval" parameters are FALSE (default), then the training R2 value is returned. If more than one parameter is set to TRUE, then a named vector of R2s are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.r2(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|---|
| object | An H2OModel object. |
| train | Retrieve the training R2 |
| valid | Retrieve the validation set R2 if a validation set was passed in during model build time. |
| xval | Retrieve the cross-validation R2 |

Examples

```
library(h2o)

h <- h2o.init()
fr <- as.h2o(iris)

m <- h2o.glm(x=2:5,y=1,training_frame=fr)

h2o.r2(m)
```

| | |
|------------------|------------------------------------|
| h2o.randomForest | <i>Build a Random Forest model</i> |
|------------------|------------------------------------|

Description

Builds a Random Forest model on an H2OFrame.

Usage

```
h2o.randomForest(x, y, training_frame, model_id = NULL,
  validation_frame = NULL, nfolds = 0,
  keep_cross_validation_predictions = FALSE,
  keep_cross_validation_fold_assignment = FALSE,
  score_each_iteration = FALSE, score_tree_interval = 0,
  fold_assignment = c("AUTO", "Random", "Modulo", "Stratified"),
```

```

fold_column = NULL, ignore_const_cols = TRUE, offset_column = NULL,
weights_column = NULL, balance_classes = FALSE,
class_sampling_factors = NULL, max_after_balance_size = 5,
max_hit_ratio_k = 0, ntrees = 50, max_depth = 20, min_rows = 1,
nbins = 20, nbins_top_level = 1024, nbins_cats = 1024,
r2_stopping = Inf, stopping_rounds = 0, stopping_metric = c("AUTO",
"deviance", "logloss", "MSE", "RMSE", "MAE", "RMSLE", "AUC", "lift_top_group",
"misclassification", "mean_per_class_error"), stopping_tolerance = 0.001,
max_runtime_secs = 0, seed = -1, build_tree_one_node = FALSE,
mtries = -1, sample_rate = 0.6320000291, sample_rate_per_class = NULL,
binomial_double_trees = FALSE, checkpoint = NULL,
col_sample_rate_change_per_level = 1, col_sample_rate_per_tree = 1,
min_split_improvement = 1e-05, histogram_type = c("AUTO",
"UniformAdaptive", "Random", "QuantilesGlobal", "RoundRobin"),
categorical_encoding = c("AUTO", "Enum", "OneHotInternal", "OneHotExplicit",
"Binary", "Eigen", "LabelEncoder", "SortByResponse", "EnumLimited"),
calibrate_model = FALSE, calibration_frame = NULL,
distribution = c("AUTO", "bernoulli", "multinomial", "gaussian", "poisson",
"gamma", "tweedie", "laplace", "quantile", "huber"),
custom_metric_func = NULL, verbose = FALSE)

```

Arguments

- x (Optional) A vector containing the names or indices of the predictor variables to use in building the model. If x is missing, then all columns except y are used.
- y The name or column index of the response variable in the data. The response must be either a numeric or a categorical/factor variable. If the response is numeric, then a regression model will be trained, otherwise it will train a classification model.
- training_frame Id of the training data frame.
- model_id Destination id for this model; auto-generated if not specified.
- validation_frame Id of the validation data frame.
- nfolds Number of folds for K-fold cross-validation (0 to disable or >= 2). Defaults to 0.
- keep_cross_validation_predictions Logical. Whether to keep the predictions of the cross-validation models. Defaults to FALSE.
- keep_cross_validation_fold_assignment Logical. Whether to keep the cross-validation fold assignment. Defaults to FALSE.
- score_each_iteration Logical. Whether to score during each iteration of model training. Defaults to FALSE.
- score_tree_interval Score the model after every so many trees. Disabled if set to 0. Defaults to 0.
- fold_assignment Cross-validation fold assignment scheme, if fold_column is not specified. The 'Stratified' option will stratify the folds based on the response variable, for classification problems. Must be one of: "AUTO", "Random", "Modulo", "Stratified". Defaults to AUTO.

| | |
|------------------------|---|
| fold_column | Column with cross-validation fold index assignment per observation. |
| ignore_const_cols | Logical. Ignore constant columns. Defaults to TRUE. |
| offset_column | Offset column. This argument is deprecated and has no use for Random Forest. |
| weights_column | Column with observation weights. Giving some observation a weight of zero is equivalent to excluding it from the dataset; giving an observation a relative weight of 2 is equivalent to repeating that row twice. Negative weights are not allowed. Note: Weights are per-row observation weights and do not increase the size of the data frame. This is typically the number of times a row is repeated, but non-integer values are supported as well. During training, rows with higher weights matter more, due to the larger loss function pre-factor. |
| balance_classes | Logical. Balance training data class counts via over/under-sampling (for imbalanced data). Defaults to FALSE. |
| class_sampling_factors | Desired over/under-sampling ratios per class (in lexicographic order). If not specified, sampling factors will be automatically computed to obtain class balance during training. Requires balance_classes. |
| max_after_balance_size | Maximum relative size of the training data after balancing class counts (can be less than 1.0). Requires balance_classes. Defaults to 5.0. |
| max_hit_ratio_k | Max. number (top K) of predictions to use for hit ratio computation (for multi-class only, 0 to disable) Defaults to 0. |
| ntrees | Number of trees. Defaults to 50. |
| max_depth | Maximum tree depth. Defaults to 20. |
| min_rows | Fewest allowed (weighted) observations in a leaf. Defaults to 1. |
| nbins | For numerical columns (real/int), build a histogram of (at least) this many bins, then split at the best point Defaults to 20. |
| nbins_top_level | For numerical columns (real/int), build a histogram of (at most) this many bins at the root level, then decrease by factor of two per level Defaults to 1024. |
| nbins_cats | For categorical columns (factors), build a histogram of this many bins, then split at the best point. Higher values can lead to more overfitting. Defaults to 1024. |
| r2_stopping | r2_stopping is no longer supported and will be ignored if set - please use stopping_rounds, stopping_metric and stopping_tolerance instead. Previous version of H2O would stop making trees when the R ² metric equals or exceeds this Defaults to 1.797693135e+308. |
| stopping_rounds | Early stopping based on convergence of stopping_metric. Stop if simple moving average of length k of the stopping_metric does not improve for k:=stopping_rounds scoring events (0 to disable) Defaults to 0. |
| stopping_metric | Metric to use for early stopping (AUTO: logloss for classification, deviance for regression) Must be one of: "AUTO", "deviance", "logloss", "MSE", "RMSE", "MAE", "RMSLE", "AUC", "lift_top_group", "misclassification", "mean_per_class_error". Defaults to AUTO. |
| stopping_tolerance | Relative tolerance for metric-based stopping criterion (stop if relative improvement is not at least this much) Defaults to 0.001. |

| | |
|----------------------------------|---|
| max_runtime_secs | Maximum allowed runtime in seconds for model training. Use 0 to disable. Defaults to 0. |
| seed | Seed for random numbers (affects certain parts of the algo that are stochastic and those might or might not be enabled by default) Defaults to -1 (time-based random number). |
| build_tree_one_node | Logical. Run on one node only; no network overhead but fewer cpus used. Suitable for small datasets. Defaults to FALSE. |
| mtries | Number of variables randomly sampled as candidates at each split. If set to -1, defaults to sqrt(p) for classification and p/3 for regression (where p is the # of predictors Defaults to -1. |
| sample_rate | Row sample rate per tree (from 0.0 to 1.0) Defaults to 0.6320000291. |
| sample_rate_per_class | A list of row sample rates per class (relative fraction for each class, from 0.0 to 1.0), for each tree |
| binomial_double_trees | Logical. For binary classification: Build 2x as many trees (one per class) - can lead to higher accuracy. Defaults to FALSE. |
| checkpoint | Model checkpoint to resume training with. |
| col_sample_rate_change_per_level | Relative change of the column sampling rate for every level (must be > 0.0 and <= 2.0) Defaults to 1. |
| col_sample_rate_per_tree | Column sample rate per tree (from 0.0 to 1.0) Defaults to 1. |
| min_split_improvement | Minimum relative improvement in squared error reduction for a split to happen Defaults to 1e-05. |
| histogram_type | What type of histogram to use for finding optimal split points Must be one of: "AUTO", "UniformAdaptive", "Random", "QuantilesGlobal", "RoundRobin". Defaults to AUTO. |
| categorical_encoding | Encoding scheme for categorical features Must be one of: "AUTO", "Enum", "OneHotInternal", "OneHotExplicit", "Binary", "Eigen", "LabelEncoder", "Sort-ByResponse", "EnumLimited". Defaults to AUTO. |
| calibrate_model | Logical. Use Platt Scaling to calculate calibrated class probabilities. Calibration can provide more accurate estimates of class probabilities. Defaults to FALSE. |
| calibration_frame | Calibration frame for Platt Scaling |
| distribution | Distribution. This argument is deprecated and has no use for Random Forest. |
| custom_metric_func | Reference to custom evaluation function, format: 'language:keyName=funcName' |
| verbose | Logical. Print scoring history to the console (Metrics per tree for GBM, DRF, & XGBoost. Metrics per epoch for Deep Learning). Defaults to FALSE. |

Value

Creates a [H2OModel](#) object of the right type.

See Also

[predict.H2OModel](#) for prediction

| | |
|-----------|--|
| h2o.range | <i>Returns a vector containing the minimum and maximum of all the given arguments.</i> |
|-----------|--|

Description

Returns a vector containing the minimum and maximum of all the given arguments.

Usage

```
h2o.range(x, na.rm = FALSE, finite = FALSE)
```

Arguments

| | |
|--------|---|
| x | An H2OFrame object. |
| na.rm | logical. indicating whether missing values should be removed. |
| finite | logical. indicating if all non-finite elements should be omitted. |

See Also

[range](#) for the base R implementation.

| | |
|-----------|-------------------------------------|
| h2o.rbind | <i>Combine H2O Datasets by Rows</i> |
|-----------|-------------------------------------|

Description

Takes a sequence of H2O data sets and combines them by rows

Usage

```
h2o.rbind(...)
```

Arguments

| | |
|-----|--|
| ... | A sequence of H2OFrame arguments. All datasets must exist on the same H2O instance (IP and port) and contain the same number and types of columns. |
|-----|--|

Value

An H2OFrame object containing the combined ... arguments row-wise.

See Also

[rbind](#) for the base R method.

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
prostate.cbind <- h2o.rbind(prostate.hex, prostate.hex)
head(prostate.cbind)
```

h2o.reconstruct

Reconstruct Training Data via H2O GLRM Model

Description

Reconstruct the training data and impute missing values from the H2O GLRM model by computing the matrix product of X and Y, and transforming back to the original feature space by minimizing each column's loss function.

Usage

```
h2o.reconstruct(object, data, reverse_transform = FALSE)
```

Arguments

| | |
|-------------------|---|
| object | An H2ODimReductionModel object that represents the model to be used for reconstruction. |
| data | An H2OFrame object representing the training data for the H2O GLRM model. Used to set the domain of each column in the reconstructed frame. |
| reverse_transform | (Optional) A logical value indicating whether to reverse the transformation from model-building by re-scaling columns and adding back the offset to each column of the reconstructed frame. |

Value

Returns an H2OFrame object containing the approximate reconstruction of the training data;

See Also

[h2o.glm](#) for making an H2ODimReductionModel.

Examples

```
library(h2o)
h2o.init()
irisPath <- system.file("extdata", "iris_wheader.csv", package="h2o")
iris.hex <- h2o.uploadFile(path = irisPath)
iris.glm <- h2o.glm(training_frame = iris.hex, k = 4, transform = "STANDARDIZE",
                  loss = "Quadratic", multi_loss = "Categorical", max_iterations = 1000)
iris.rec <- h2o.reconstruct(iris.glm, iris.hex, reverse_transform = TRUE)
head(iris.rec)
```

| | |
|-------------|---|
| h2o.relevel | <i>Reorders levels of an H2O factor, similarly to standard R's relevel.</i> |
|-------------|---|

Description

The levels of a factor are reordered so that the reference level is at level 0, remaining levels are moved down as needed.

Usage

```
h2o.relevel(x, y)
```

Arguments

| | |
|---|----------------------------|
| x | factor column in h2o frame |
| y | reference level (string) |

Value

new reordered factor column

| | |
|---------------|--|
| h2o.removeAll | <i>Remove All Objects on the H2O Cluster</i> |
|---------------|--|

Description

Removes the data from the h2o cluster, but does not remove the local references.

Usage

```
h2o.removeAll(timeout_secs = 0)
```

Arguments

| | |
|--------------|--|
| timeout_secs | Timeout in seconds. Default is no timeout. |
|--------------|--|

See Also

[h2o.rm](#)

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package = "h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
h2o.ls()
h2o.removeAll()
h2o.ls()
```

| | |
|----------------|--|
| h2o.removeVecs | <i>Delete Columns from an H2OFrame</i> |
|----------------|--|

Description

Delete the specified columns from the H2OFrame. Returns an H2OFrame without the specified columns.

Usage

```
h2o.removeVecs(data, cols)
```

Arguments

| | |
|------|------------------------|
| data | The H2OFrame. |
| cols | The columns to remove. |

| | |
|-------------|--|
| h2o.rep_len | <i>Replicate Elements of Vectors or Lists into H2O</i> |
|-------------|--|

Description

h2o.rep_len performs just as rep does. It replicates the values in x in the H2O backend.

Usage

```
h2o.rep_len(x, length.out)
```

Arguments

| | |
|------------|--|
| x | an H2O frame |
| length.out | non negative integer. The desired length of the output vector. |

Value

Creates an H2OFrame of the same type as x

h2o.residual_deviance *Retrieve the residual deviance*

Description

If "train", "valid", and "xval" parameters are FALSE (default), then the training residual deviance value is returned. If more than one parameter is set to TRUE, then a named vector of residual deviances are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.residual_deviance(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|--|
| object | An H2OModel or H2OModelMetrics |
| train | Retrieve the training residual deviance |
| valid | Retrieve the validation residual deviance |
| xval | Retrieve the cross-validation residual deviance |

h2o.residual_dof *Retrieve the residual degrees of freedom*

Description

If "train", "valid", and "xval" parameters are FALSE (default), then the training residual degrees of freedom value is returned. If more than one parameter is set to TRUE, then a named vector of residual degrees of freedom are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.residual_dof(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|--|
| object | An H2OModel or H2OModelMetrics |
| train | Retrieve the training residual degrees of freedom |
| valid | Retrieve the validation residual degrees of freedom |
| xval | Retrieve the cross-validation residual degrees of freedom |

h2o.rm *Delete Objects In H2O*

Description

Remove the h2o Big Data object(s) having the key name(s) from ids.

Usage

```
h2o.rm(ids)
```

Arguments

| | |
|-----|--|
| ids | The object or hex key associated with the object to be removed or a vector/list of those things. |
|-----|--|

See Also

[h2o.assign](#), [h2o.ls](#)

h2o.rmse *Retrieves Root Mean Squared Error Value*

Description

Retrieves the root mean squared error value from an [H2OModelMetrics](#) object. If "train", "valid", and "xval" parameters are FALSE (default), then the training RMSE value is returned. If more than one parameter is set to TRUE, then a named vector of RMSEs are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.rmse(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|--|
| object | An H2OModelMetrics object of the correct type. |
| train | Retrieve the training RMSE |
| valid | Retrieve the validation RMSE |
| xval | Retrieve the cross-validation RMSE |

Details

This function only supports [H2OBinomialMetrics](#), [H2OMultinomialMetrics](#), and [H2ORegressionMetrics](#) objects.

See Also

[h2o.auc](#) for AUC, [h2o.mse](#) for RMSE, and [h2o.metric](#) for the various threshold metrics. See [h2o.performance](#) for creating [H2OModelMetrics](#) objects.

Examples

```
library(h2o)
h2o.init()

prosPath <- system.file("extdata", "prostate.csv", package="h2o")
hex <- h2o.uploadFile(prosPath)

hex[,2] <- as.factor(hex[,2])
model <- h2o.gbm(x = 3:9, y = 2, training_frame = hex, distribution = "bernoulli")
perf <- h2o.performance(model, hex)
h2o.rmse(perf)
```

h2o.rmsle

Retrieve the Root Mean Squared Log Error

Description

Retrieves the root mean squared log error (RMSLE) value from an H2O model. If "train", "valid", and "xval" parameters are FALSE (default), then the training rmsle value is returned. If more than one parameter is set to TRUE, then a named vector of rmsles are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.rmsle(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|--|
| object | An H2OModel object. |
| train | Retrieve the training rmsle |
| valid | Retrieve the validation set rmsle if a validation set was passed in during model build time. |
| xval | Retrieve the cross-validation rmsle |

Examples

```
library(h2o)

h <- h2o.init()
fr <- as.h2o(iris)

m <- h2o.deeplearning(x=2:5,y=1,training_frame=fr)

h2o.rmsle(m)
```

| | |
|-----------|--|
| h2o.round | <i>Round doubles/floats to the given number of decimal places.</i> |
|-----------|--|

Description

Round doubles/floats to the given number of decimal places.

Usage

```
h2o.round(x, digits = 0)
```

```
round(x, digits = 0)
```

Arguments

| | |
|--------|--|
| x | An H2OFrame object. |
| digits | Number of decimal places to round doubles/floats. Rounding to a negative number of decimal places is |

See Also

[round](#) for the base R implementation.

| | |
|------------|-----------------------------|
| h2o.rstrip | <i>Strip set from right</i> |
|------------|-----------------------------|

Description

Return a copy of the target column with trailing characters removed. The set argument is a string specifying the set of characters to be removed. If omitted, the set argument defaults to removing whitespace.

Usage

```
h2o.rstrip(x, set = " ")
```

Arguments

| | |
|-----|---|
| x | The column whose strings should be rstrip-ed. |
| set | string of characters to be removed |

Examples

```
library(h2o)
h2o.init()
string_to_rstrip <- as.h2o("1234567890")
rstrip_string <- h2o.rstrip(string_to_rstrip,"890") #Remove "890"
```

| | |
|-----------|---|
| h2o.runif | <i>Produce a Vector of Random Uniform Numbers</i> |
|-----------|---|

Description

Creates a vector of random uniform numbers equal in length to the length of the specified H2O dataset.

Usage

```
h2o.runif(x, seed = -1)
```

Arguments

| | |
|------|---|
| x | An H2OFrame object. |
| seed | A random seed used to generate draws from the uniform distribution. |

Value

A vector of random, uniformly distributed numbers. The elements are between 0 and 1.

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.importFile(path = prosPath, destination_frame = "prostate.hex")
s <- h2o.runif(prostate.hex)
summary(s)

prostate.train <- prostate.hex[s <= 0.8,]
prostate.train <- h2o.assign(prostate.train, "prostate.train")
prostate.test <- prostate.hex[s > 0.8,]
prostate.test <- h2o.assign(prostate.test, "prostate.test")
nrow(prostate.train) + nrow(prostate.test)
```

| | |
|---------------|---|
| h2o.saveModel | <i>Save an H2O Model Object to Disk</i> |
|---------------|---|

Description

Save an [H2OModel](#) to disk. (Note that ensemble binary models can be saved.)

Usage

```
h2o.saveModel(object, path = "", force = FALSE)
```

Arguments

| | |
|--------|---|
| object | an H2OModel object. |
| path | string indicating the directory the model will be written to. |
| force | logical, indicates how to deal with files that already exist. |

Details

In the case of existing files `force = TRUE` will overwrite the file. Otherwise, the operation will fail.

See Also

[h2o.loadModel](#) for loading a model to H2O from disk

Examples

```
## Not run:
# library(h2o)
# h2o.init()
# prostate.hex <- h2o.importFile(path = paste("https://raw.githubusercontent.com",
# "h2oai/h2o-2/master/smalldata/logreg/prostate.csv", sep = "/"),
# destination_frame = "prostate.hex")
# prostate.glm <- h2o.glm(y = "CAPSULE", x = c("AGE", "RACE", "PSA", "DCAPS"),
# training_frame = prostate.hex, family = "binomial", alpha = 0.5)
# h2o.saveModel(object = prostate.glm, path = "/Users/UserName/Desktop", force=TRUE)

## End(Not run)
```

h2o.saveModelDetails *Save an H2O Model Details*

Description

Save Model Details of an H2O Model in JSON Format

Usage

```
h2o.saveModelDetails(object, path = "", force = FALSE)
```

Arguments

| | |
|--------|---|
| object | an H2OModel object. |
| path | string indicating the directory the model details will be written to. |
| force | logical, indicates how to deal with files that already exist. |

Details

Model Details will download as a JSON file. In the case of existing files `force = TRUE` will overwrite the file. Otherwise, the operation will fail.

Examples

```
## Not run:
# library(h2o)
# h2o.init()
# prostate.hex <- h2o.uploadFile(path = system.file("extdata", "prostate.csv", package="h2o"))
# prostate.glm <- h2o.glm(y = "CAPSULE", x = c("AGE", "RACE", "PSA", "DCAPS"),
#                               training_frame = prostate.hex, family = "binomial", alpha = 0.5)
# h2o.saveModelDetails(object = prostate.glm, path = "/Users/UserName/Desktop", force=TRUE)

## End(Not run)
```

h2o.saveMojo

Save an H2O Model Object as Mojo to Disk

Description

Save an MOJO (Model Object, Optimized) to disk.

Usage

```
h2o.saveMojo(object, path = "", force = FALSE)
```

Arguments

| | |
|--------|---|
| object | an H2OModel object. |
| path | string indicating the directory the model will be written to. |
| force | logical, indicates how to deal with files that already exist. |

Details

MOJO will download as a zip file. In the case of existing files `force = TRUE` will overwrite the file. Otherwise, the operation will fail.

See Also

[h2o.saveModel](#) for saving a model to disk as a binary object.

Examples

```
## Not run:
# library(h2o)
# h2o.init()
# prostate.hex <- h2o.uploadFile(path = system.file("extdata", "prostate.csv", package="h2o"))
# prostate.glm <- h2o.glm(y = "CAPSULE", x = c("AGE", "RACE", "PSA", "DCAPS"),
#                               training_frame = prostate.hex, family = "binomial", alpha = 0.5)
# h2o.saveMojo(object = prostate.glm, path = "/Users/UserName/Desktop", force=TRUE)

## End(Not run)
```

| | |
|-----------|---|
| h2o.scale | <i>Scaling and Centering of an H2OFrame</i> |
|-----------|---|

Description

Centers and/or scales the columns of an H2O dataset.

Usage

```
h2o.scale(x, center = TRUE, scale = TRUE)
```

```
## S3 method for class 'H2OFrame'
scale(x, center = TRUE, scale = TRUE)
```

Arguments

| | |
|--------|---|
| x | An H2OFrame object. |
| center | either a logical value or numeric vector of length equal to the number of columns of x. |
| scale | either a logical value or numeric vector of length equal to the number of columns of x. |

Examples

```
library(h2o)
h2o.init()
irisPath <- system.file("extdata", "iris_wheader.csv", package="h2o")
iris.hex <- h2o.uploadFile(path = irisPath, destination_frame = "iris.hex")
summary(iris.hex)

# Scale and center all the numeric columns in iris data set
scale(iris.hex[, 1:4])
```

| | |
|------------------|-------------------------------------|
| h2o.scoreHistory | <i>Retrieve Model Score History</i> |
|------------------|-------------------------------------|

Description

Retrieve Model Score History

Usage

```
h2o.scoreHistory(object)
```

Arguments

| | |
|--------|-------------------------------------|
| object | An H2OModel object. |
|--------|-------------------------------------|

| | |
|--------|--|
| h2o.sd | <i>Standard Deviation of a column of data.</i> |
|--------|--|

Description

Obtain the standard deviation of a column of data.

Usage

```
h2o.sd(x, na.rm = FALSE)
```

```
sd(x, na.rm = FALSE)
```

Arguments

| | |
|-------|--|
| x | An H2OFrame object. |
| na.rm | logical. Should missing values be removed? |

See Also

[h2o.var](#) for variance, and [sd](#) for the base R implementation.

Examples

```
h2o.init()  
prosPath <- system.file("extdata", "prostate.csv", package="h2o")  
prostate.hex <- h2o.uploadFile(path = prosPath)  
sd(prostate.hex$AGE)
```

| | |
|----------|---|
| h2o.sdev | <i>Retrieve the standard deviations of principal components</i> |
|----------|---|

Description

Retrieve the standard deviations of principal components

Usage

```
h2o.sdev(object)
```

Arguments

| | |
|--------|---|
| object | An H2ODimReductionModel object. |
|--------|---|

h2o.setLevels *Set Levels of H2O Factor Column*

Description

Works on a single categorical vector. New domains must be aligned with the old domains. This call has SIDE EFFECTS and mutates the column in place (change of the levels will also affect all the frames that are referencing this column). If you want to make a copy of the column instead, use parameter `in.place = FALSE`.

Usage

```
h2o.setLevels(x, levels, in.place = TRUE)
```

Arguments

| | |
|----------|--|
| x | A single categorical column. |
| levels | A character vector specifying the new levels. The number of new levels must match the number of old levels. |
| in.place | Indicates whether new domain will be directly applied to the column (in place change) or if a copy of the column will be created with the given domain levels. |

Examples

```
h2o.init()
iris.hex <- as.h2o(iris)
new.levels <- c("setosa", "versicolor", "caroliniana")
iris.hex$Species <- h2o.setLevels(iris.hex$Species, new.levels, in.place = FALSE)
h2o.levels(iris.hex$Species)
```

h2o.setTimezone *Set the Time Zone on the H2O Cloud*

Description

Set the Time Zone on the H2O Cloud

Usage

```
h2o.setTimezone(tz)
```

Arguments

| | |
|----|-----------------------|
| tz | The desired timezone. |
|----|-----------------------|

| | |
|-------------------|----------------------------|
| h2o.show_progress | <i>Enable Progress Bar</i> |
|-------------------|----------------------------|

Description

Enable Progress Bar

Usage

```
h2o.show_progress()
```

| | |
|--------------|-------------------------------|
| h2o.shutdown | <i>Shut Down H2O Instance</i> |
|--------------|-------------------------------|

Description

Shut down the specified instance. All data will be lost.

Usage

```
h2o.shutdown(prompt = TRUE)
```

Arguments

| | |
|--------|--|
| prompt | A logical value indicating whether to prompt the user before shutting down the H2O server. |
|--------|--|

Details

This method checks if H2O is running at the specified IP address and port, and if it is, shuts down that H2O instance.

WARNING

All data, models, and other values stored on the server will be lost! Only call this function if you and all other clients connected to the H2O server are finished and have saved your work.

Note

Users must call h2o.shutdown explicitly in order to shut down the local H2O instance started by R. If R is closed before H2O, then an attempt will be made to automatically shut down H2O. This only applies to local instances started with h2o.init, not remote H2O servers.

See Also

[h2o.init](#)

Examples

```
# Don't run automatically to prevent accidentally shutting down a cloud
## Not run:
library(h2o)
h2o.init()
h2o.shutdown()

## End(Not run)
```

| | |
|------------|--|
| h2o.signif | <i>Round doubles/floats to the given number of significant digits.</i> |
|------------|--|

Description

Round doubles/floats to the given number of significant digits.

Usage

```
h2o.signif(x, digits = 6)
```

```
signif(x, digits = 6)
```

Arguments

| | |
|--------|---|
| x | An H2OFrame object. |
| digits | Number of significant digits to round doubles/floats. |

See Also

[signif](#) for the base R implementation.

| | |
|---------|------------------------------|
| h2o.sin | <i>Compute the sine of x</i> |
|---------|------------------------------|

Description

Compute the sine of x

Usage

```
h2o.sin(x)
```

Arguments

| | |
|---|---------------------|
| x | An H2OFrame object. |
|---|---------------------|

See Also

[sin](#) for the base R implementation.

| | |
|--------------|-----------------------------|
| h2o.skewness | <i>Skewness of a column</i> |
|--------------|-----------------------------|

Description

Obtain the skewness of a column of a parsed H2O data object.

Usage

```
h2o.skewness(x, ..., na.rm = TRUE)
```

```
skewness.H2OFrame(x, ..., na.rm = TRUE)
```

Arguments

| | |
|-------|--|
| x | An H2OFrame object. |
| ... | Further arguments to be passed from or to other methods. |
| na.rm | A logical value indicating whether NA or missing values should be stripped before the computation. |

Value

Returns a list containing the skewness for each column (NaN for non-numeric columns).

Examples

```
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
h2o.skewness(prostate.hex$AGE)
```

| | |
|----------------|------------------------------|
| h2o.splitFrame | <i>Split an H2O Data Set</i> |
|----------------|------------------------------|

Description

Split an existing H2O data set according to user-specified ratios. The number of subsets is always 1 more than the number of given ratios. Note that this does not give an exact split. H2O is designed to be efficient on big data using a probabilistic splitting method rather than an exact split. For example, when specifying a split of 0.75/0.25, H2O will produce a test/train split with an expected value of 0.75/0.25 rather than exactly 0.75/0.25. On small datasets, the sizes of the resulting splits will deviate from the expected value more than on big data, where they will be very close to exact.

Usage

```
h2o.splitFrame(data, ratios = 0.75, destination_frames, seed = -1)
```

Arguments

| | |
|--------------------|--|
| data | An H2OFrame object representing the data to split. |
| ratios | A numeric value or array indicating the ratio of total rows contained in each split. Must total up to less than 1. |
| destination_frames | An array of frame IDs equal to the number of ratios specified plus one. |
| seed | Random seed. |

Value

Returns a list of split H2OFrame's

Examples

```
library(h2o)
h2o.init()
irisPath <- system.file("extdata", "iris.csv", package = "h2o")
iris.hex <- h2o.importFile(path = irisPath)
iris.split <- h2o.splitFrame(iris.hex, ratios = c(0.2, 0.5))
head(iris.split[[1]])
summary(iris.split[[1]])
```

h2o.sqrt

Compute the square root of x

Description

Compute the square root of x

Usage

```
h2o.sqrt(x)
```

Arguments

| | |
|---|---------------------|
| x | An H2OFrame object. |
|---|---------------------|

See Also

[sqrt](#) for the base R implementation.

h2o.stackedEnsemble *Builds a Stacked Ensemble*

Description

Build a stacked ensemble (aka. Super Learner) using the H2O base learning algorithms specified by the user.

Usage

```
h2o.stackedEnsemble(x, y, training_frame, model_id = NULL,
  validation_frame = NULL, base_models = list(),
  metalearner_algorithm = c("AUTO", "glm", "gbm", "drf", "deeplearning"),
  metalearner_nfolds = 0, metalearner_fold_assignment = c("AUTO", "Random",
  "Modulo", "Stratified"), metalearner_fold_column = NULL,
  keep_levelone_frame = FALSE, seed = -1, metalearner_params = NULL)
```

Arguments

- x (Optional). A vector containing the names or indices of the predictor variables to use in building the model. If x is missing, then all columns except y are used. Training frame is used only to compute ensemble training metrics.
- y The name or column index of the response variable in the data. The response must be either a numeric or a categorical/factor variable. If the response is numeric, then a regression model will be trained, otherwise it will train a classification model.
- training_frame Id of the training data frame.
- model_id Destination id for this model; auto-generated if not specified.
- validation_frame Id of the validation data frame.
- base_models List of models (or model ids) to ensemble/stack together. Models must have been cross-validated using nfolds > 1, and folds must be identical across models. Defaults to [].
- metalearner_algorithm Type of algorithm to use as the metalearner. Options include 'AUTO' (GLM with non negative weights; if validation_frame is present, a lambda search is performed), 'glm' (GLM with default parameters), 'gbm' (GBM with default parameters), 'drf' (Random Forest with default parameters), or 'deeplearning' (Deep Learning with default parameters). Must be one of: "AUTO", "glm", "gbm", "drf", "deeplearning". Defaults to AUTO.
- metalearner_nfolds Number of folds for K-fold cross-validation of the metalearner algorithm (0 to disable or >= 2). Defaults to 0.
- metalearner_fold_assignment Cross-validation fold assignment scheme for metalearner cross-validation. Defaults to AUTO (which is currently set to Random). The 'Stratified' option will stratify the folds based on the response variable, for classification problems. Must be one of: "AUTO", "Random", "Modulo", "Stratified".

| | |
|-------------------------|--|
| metalearner_fold_column | Column with cross-validation fold index assignment per observation for cross-validation of the metalearner. |
| keep_levelone_frame | Logical. Keep level one frame used for metalearner training. Defaults to FALSE. |
| seed | Seed for random numbers; passed through to the metalearner algorithm. Defaults to -1 (time-based random number) Defaults to -1 (time-based random number). |
| metalearner_params | Parameters for metalearner algorithm Defaults to NULL. |

Examples

```
# See example R code here:
# http://docs.h2o.ai/h2o/latest-stable/h2o-docs/data-science/stacked-ensembles.html
```

| | |
|------------------|---------------------------------|
| h2o.startLogging | <i>Start Writing H2O R Logs</i> |
|------------------|---------------------------------|

Description

Begin logging H2o R POST commands and error responses to local disk. Used primarily for debugging purposes.

Usage

```
h2o.startLogging(file)
```

Arguments

file a character string name for the file, automatically generated

See Also

[h2o.stopLogging](#), [h2o.clearLog](#), [h2o.openLog](#)

Examples

```
library(h2o)
h2o.init()
h2o.startLogging()
ausPath = system.file("extdata", "australia.csv", package="h2o")
australia.hex = h2o.importFile(path = ausPath)
h2o.stopLogging()
```

h2o.std_coef_plot *Plot Standardized Coefficient Magnitudes*

Description

Plot a GLM model's standardized coefficient magnitudes.

Usage

```
h2o.std_coef_plot(model, num_of_features = NULL)
```

Arguments

model A trained generalized linear model
num_of_features The number of features to be shown in the plot

See Also

[h2o.varimp_plot](#) for variable importances plot of random forest, GBM, deep learning.

Examples

```
library(h2o)
h2o.init()

prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.importFile(prosPath)
prostate.hex[,2] <- as.factor(prostate.hex[,2])
prostate.glm <- h2o.glm(y = "CAPSULE", x = c("AGE", "RACE", "PSA", "DCAPS"),
                       training_frame = prostate.hex, family = "binomial",
                       nfold = 0, alpha = 0.5, lambda_search = FALSE)
h2o.std_coef_plot(prostate.glm)
```

h2o.stopLogging *Stop Writing H2O R Logs*

Description

Halt logging of H2O R POST commands and error responses to local disk. Used primarily for debugging purposes.

Usage

```
h2o.stopLogging()
```

See Also

[h2o.startLogging](#), [h2o.clearLog](#), [h2o.openLog](#)

Examples

```
library(h2o)
h2o.init()
h2o.startLogging()
ausPath = system.file("extdata", "australia.csv", package="h2o")
australia.hex = h2o.importFile(path = ausPath)
h2o.stopLogging()
```

| | |
|---------|--|
| h2o.str | <i>Display the structure of an H2OFrame object</i> |
|---------|--|

Description

Display the structure of an H2OFrame object

Usage

```
h2o.str(object, ..., cols = FALSE)
```

Arguments

| | |
|--------|--|
| object | An H2OFrame. |
| ... | Further arguments to be passed from or to other methods. |
| cols | Print the per-column str for the H2OFrame |

| | |
|----------------|--|
| h2o.stringdist | <i>Compute element-wise string distances between two H2OFrames</i> |
|----------------|--|

Description

Compute element-wise string distances between two H2OFrames. Both frames need to have the same shape (N x M) and only contain string/factor columns. Return a matrix (H2OFrame) of shape N x M.

Usage

```
h2o.stringdist(x, y, method = c("lv", "lcs", "qgram", "jaccard", "jw",
"soundex"), compare_empty = TRUE)
```

Arguments

| | |
|---------------|--|
| x | An H2OFrame |
| y | A comparison H2OFrame |
| method | A string identifier indicating what string distance measure to use. Must be one of: "lv" - Levenshtein distance "lcs" - Longest common substring distance "qgram" - q-gram distance "jaccard" - Jaccard distance between q-gram profiles "jw" - Jaro, or Jaro-Winker distance "soundex" - Distance based on soundex encoding |
| compare_empty | if set to FALSE, empty strings will be handled as NaNs |

Examples

```

h2o.init()
x <- as.h2o(c("Martha", "Dwayne", "Dixon"))
y <- as.character(as.h2o(c("Marhta", "Duane", "Dicksonx")))
h2o.stringdist(x, y, method = "jw")

```

h2o.strsplit

String Split

Description

String Split

Usage

```
h2o.strsplit(x, split)
```

Arguments

x The column whose strings must be split.
split The pattern to split on.

Value

An H2OFrame where each column is the outcome of the string split.

Examples

```

library(h2o)
h2o.init()
string_to_split <- as.h2o("Split at every character.")
split_string <- h2o.strsplit(string_to_split, "")

```

h2o.sub

String Substitute

Description

Creates a copy of the target column in which each string has the first occurrence of the regex pattern replaced with the replacement substring.

Usage

```
h2o.sub(pattern, replacement, x, ignore.case = FALSE)
```

Arguments

| | |
|-------------|---------------------------------|
| pattern | The pattern to replace. |
| replacement | The replacement pattern. |
| x | The column on which to operate. |
| ignore.case | Case sensitive or not |

Examples

```
library(h2o)
h2o.init()
string_to_sub <- as.h2o("r tutorial")
sub_string <- h2o.sub("r ", "H2O ", string_to_sub)
```

| | |
|---------------|------------------|
| h2o.substring | <i>Substring</i> |
|---------------|------------------|

Description

Returns a copy of the target column that is a substring at the specified start and stop indices, inclusive. If the stop index is not specified, then the substring extends to the end of the original string. If start is longer than the number of characters in the original string, or is greater than stop, an empty string is returned. Negative start is coerced to 0.

Usage

```
h2o.substring(x, start, stop = "[ ]")
```

```
h2o.substr(x, start, stop = "[ ]")
```

Arguments

| | |
|-------|--|
| x | The column on which to operate. |
| start | The index of the first element to be included in the substring. |
| stop | Optional, The index of the last element to be included in the substring. |

Examples

```
library(h2o)
h2o.init()
string_to_substring <- as.h2o("1234567890")
substr <- h2o.substring(string_to_substring,2) #Get substring from second index onwards
```

| | |
|---------|---|
| h2o.sum | <i>Compute the frame's sum by-column (or by-row).</i> |
|---------|---|

Description

Compute the frame's sum by-column (or by-row).

Usage

```
h2o.sum(x, na.rm = FALSE, axis = 0, return_frame = FALSE)
```

Arguments

| | |
|--------------|--|
| x | An H2OFrame object. |
| na.rm | logical. indicating whether missing values should be removed. |
| axis | An int that indicates whether to do down a column (0) or across a row (1). |
| return_frame | A boolean that indicates whether to return an H2O frame or a list. Default is FALSE. |

See Also

[sum](#) for the base R implementation.

| | |
|-------------|---|
| h2o.summary | <i>Summarizes the columns of an H2OFrame.</i> |
|-------------|---|

Description

A method for the [summary](#) generic. Summarizes the columns of an H2O data frame or subset of columns and rows using vector notation (e.g. dataset[row, col]).

Usage

```
h2o.summary(object, factors = 6L, exact_quantiles = FALSE, ...)
```

```
## S3 method for class 'H2OFrame'
summary(object, factors, exact_quantiles, ...)
```

Arguments

| | |
|-----------------|--|
| object | An H2OFrame object. |
| factors | The number of factors to return in the summary. Default is the top 6. |
| exact_quantiles | Compute exact quantiles or use approximation. Default is to use approximation. |
| ... | Further arguments passed to or from other methods. |

Details

By default it uses approximated version of quantiles computation, however, user can modify this behavior by setting up `exact_quantiles` argument to true.

Value

A table displaying the minimum, 1st quartile, median, mean, 3rd quartile and maximum for each numeric column, and the levels and category counts of the levels in each categorical column.

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.importFile(path = prosPath)
summary(prostate.hex)
summary(prostate.hex$GLEASON)
summary(prostate.hex[,4:6])
summary(prostate.hex, exact_quantiles=TRUE)
```

h2o.svd

Singular value decomposition of an H2O data frame using the power method

Description

Singular value decomposition of an H2O data frame using the power method

Usage

```
h2o.svd(training_frame, x, destination_key, model_id = NULL,
  validation_frame = NULL, ignore_const_cols = TRUE,
  score_each_iteration = FALSE, transform = c("NONE", "STANDARDIZE",
  "NORMALIZE", "DEMEAN", "DESCALE"), svd_method = c("GramSVD", "Power",
  "Randomized"), nv = 1, max_iterations = 1000, seed = -1,
  keep_u = TRUE, u_name = NULL, use_all_factor_levels = TRUE,
  max_runtime_secs = 0)
```

Arguments

`training_frame` Id of the training data frame.

`x` A vector containing the character names of the predictors in the model.

`destination_key`
(Optional) The unique hex key assigned to the resulting model. Automatically generated if none is provided.

`model_id` Destination id for this model; auto-generated if not specified.

`validation_frame`
Id of the validation data frame.

| | |
|-----------------------|---|
| ignore_const_cols | Logical. Ignore constant columns. Defaults to TRUE. |
| score_each_iteration | Logical. Whether to score during each iteration of model training. Defaults to FALSE. |
| transform | Transformation of training data Must be one of: "NONE", "STANDARDIZE", "NORMALIZE", "DEMEAN", "DESCALE". Defaults to NONE. |
| svd_method | Method for computing SVD (Caution: Randomized is currently experimental and unstable) Must be one of: "GramSVD", "Power", "Randomized". Defaults to GramSVD. |
| nv | Number of right singular vectors Defaults to 1. |
| max_iterations | Maximum iterations Defaults to 1000. |
| seed | Seed for random numbers (affects certain parts of the algo that are stochastic and those might or might not be enabled by default) Defaults to -1 (time-based random number). |
| keep_u | Logical. Save left singular vectors? Defaults to TRUE. |
| u_name | Frame key to save left singular vectors |
| use_all_factor_levels | Logical. Whether first factor level is included in each categorical expansion Defaults to TRUE. |
| max_runtime_secs | Maximum allowed runtime in seconds for model training. Use 0 to disable. Defaults to 0. |

Value

Returns an object of class `H2ODimReductionModel`.

References

N. Halko, P.G. Martinsson, J.A. Tropp. Finding structure with randomness: Probabilistic algorithms for constructing approximate matrix decompositions[<http://arxiv.org/abs/0909.4061>]. SIAM Rev., Survey and Review section, Vol. 53, num. 2, pp. 217-288, June 2011.

Examples

```
library(h2o)
h2o.init()
ausPath <- system.file("extdata", "australia.csv", package="h2o")
australia.hex <- h2o.uploadFile(path = ausPath)
h2o.svd(training_frame = australia.hex, nv = 8)
```

h2o.table

Cross Tabulation and Table Creation in H2O

Description

Uses the cross-classifying factors to build a table of counts at each combination of factor levels.

Usage

```
h2o.table(x, y = NULL, dense = TRUE)
```

```
table.H2OFrame(x, y = NULL, dense = TRUE)
```

Arguments

| | |
|-------|---|
| x | An H2OFrame object with at most two columns. |
| y | An H2OFrame similar to x, or NULL. |
| dense | A logical for dense representation, which lists only non-zero counts, 1 combination per row. Set to FALSE to expand counts across all combinations. |

Value

Returns a tabulated H2OFrame object.

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath, destination_frame = "prostate.hex")
summary(prostate.hex)

# Counts of the ages of all patients
head(h2o.table(prostate.hex[,3]))
h2o.table(prostate.hex[,3])

# Two-way table of ages (rows) and race (cols) of all patients
head(h2o.table(prostate.hex[,c(3,4)]))
h2o.table(prostate.hex[,c(3,4)])
```

h2o.tabulate

Tabulation between Two Columns of an H2OFrame

Description

Simple Co-Occurrence based tabulation of X vs Y, where X and Y are two Vecs in a given dataset. Uses histogram of given resolution in X and Y. Handles numerical/categorical data and missing values. Supports observation weights.

Usage

```
h2o.tabulate(data, x, y, weights_column = NULL, nbins_x = 50,  
             nbins_y = 50)
```

Arguments

| | |
|----------------|---------------------------------------|
| data | An H2OFrame object. |
| x | predictor column |
| y | response column |
| weights_column | (optional) observation weights column |
| nbins_x | number of bins for predictor column |
| nbins_y | number of bins for response column |

Value

Returns two TwoDimTables of 3 columns each count_table: X Y counts response_table: X mean Y counts

Examples

```
library(h2o)  
h2o.init()  
df <- as.h2o(iris)  
tab <- h2o.tabulate(data = df, x = "Sepal.Length", y = "Petal.Width",  
                   weights_column = NULL, nbins_x = 10, nbins_y = 10)  
plot(tab)
```

| | |
|---------|---------------------------------|
| h2o.tan | <i>Compute the tangent of x</i> |
|---------|---------------------------------|

Description

Compute the tangent of x

Usage

```
h2o.tan(x)
```

Arguments

| | |
|---|---------------------|
| x | An H2OFrame object. |
|---|---------------------|

See Also

[tan](#) for the base R implementation.

| | |
|----------|--|
| h2o.tanh | <i>Compute the hyperbolic tangent of x</i> |
|----------|--|

Description

Compute the hyperbolic tangent of x

Usage

```
h2o.tanh(x)
```

Arguments

| | |
|---|---------------------|
| x | An H2OFrame object. |
|---|---------------------|

See Also

[tanh](#) for the base R implementation.

| | |
|-------------------------|---|
| h2o.target_encode_apply | <i>Apply Target Encoding Map to Frame</i> |
|-------------------------|---|

Description

Applies a target encoding map to an H2OFrame object. Computing target encoding for high cardinality categorical columns can improve performance of supervised learning models.

Usage

```
h2o.target_encode_apply(data, x, y, target_encode_map, holdout_type,
  fold_column = NULL, blended_avg = TRUE, noise_level = NULL, seed = -1)
```

Arguments

| | |
|-------------------|---|
| data | An H2OFrame object with which to apply the target encoding map. |
| x | A list containing the names or indices of the variables to encode. A target encoding column will be created for each element in the list. Items in the list can be multiple columns. For example, if 'x = list(c("A"), c("B", "C"))', then the resulting frame will have a target encoding column for A and a target encoding column for B & C (in this case, we group by two columns). |
| y | The name or column index of the response variable in the data. The response variable can be either numeric or binary. |
| target_encode_map | A list of H2OFrame objects that is the results of the h2o.target_encode_create function. |
| holdout_type | The holdout type used. Must be one of: "LeaveOneOut", "KFold", "None". |
| fold_column | (Optional) The name or column index of the fold column in the data. Defaults to NULL (no 'fold_column'). Only required if 'holdout_type' = "KFold". |

| | |
|-------------|--|
| blended_avg | Logical. (Optional) Whether to perform blended average. |
| noise_level | (Optional) The amount of random noise added to the target encoding. This helps prevent overfitting. Defaults to 0.01 * range of y. |
| seed | (Optional) A random seed used to generate draws from the uniform distribution for random noise. Defaults to -1. |

Value

Returns an H2OFrame object containing the target encoding per record.

See Also

[h2o.target_encode_create](#) for creating the target encoding map

Examples

```
library(h2o)
h2o.init()

# Get Target Encoding Frame on bank-additional-full data with numeric `y`
data <- h2o.importFile(
  path = "https://s3.amazonaws.com/h2o-public-test-data/smalldata/demos/bank-additional-full.csv",
  destination_frame = "data")
splits <- h2o.splitFrame(data, seed = 1234)
train <- splits[[1]]
test <- splits[[2]]
mapping <- h2o.target_encode_create(data = train, x = list(c("job"), c("job", "marital")),
  y = "age")

# Apply mapping to the training dataset
train_encode <- h2o.target_encode_apply(data = train, x = list(c("job"), c("job", "marital")),
  y = "age", mapping, holdout_type = "LeaveOneOut")
# Apply mapping to a test dataset
test_encode <- h2o.target_encode_apply(data = test, x = list(c("job"), c("job", "marital")),
  y = "age", target_encode_map = mapping, holdout_type = "None")
```

h2o.target_encode_create

Create Target Encoding Map

Description

Creates a target encoding map based on group-by columns ('x') and a numeric or binary target column ('y'). Computing target encoding for high cardinality categorical columns can improve performance of supervised learning models.

Usage

```
h2o.target_encode_create(data, x, y, fold_column = NULL)
```

Arguments

| | |
|-------------|--|
| data | An H2OFrame object with which to create the target encoding map. |
| x | A list containing the names or indices of the variables to encode. A target encoding map will be created for each element in the list. Items in the list can be multiple columns. For example, if 'x = list(c("A"), c("B", "C"))', then there will be one mapping frame for A and one mapping frame for B & C (in this case, we group by two columns). |
| y | The name or column index of the response variable in the data. The response variable can be either numeric or binary. |
| fold_column | (Optional) The name or column index of the fold column in the data. Defaults to NULL (no 'fold_column'). |

Value

Returns a list of H2OFrame objects containing the target encoding mapping for each column in 'x'.

See Also

[h2o.target_encode_apply](#) for applying the target encoding mapping to a frame.

Examples

```
library(h2o)
h2o.init()

# Get Target Encoding Map on bank-additional-full data with numeric response
data <- h2o.importFile(
  path = "https://s3.amazonaws.com/h2o-public-test-data/smalldata/demos/bank-additional-full.csv",
  destination_frame = "data")
mapping_age <- h2o.target_encode_create(data = data, x = list(c("job"), c("job", "marital")),
  y = "age")
head(mapping_age)

# Get Target Encoding Map on bank-additional-full data with binary response
mapping_y <- h2o.target_encode_create(data = data, x = list(c("job"), c("job", "marital")),
  y = "y")
head(mapping_y)
```

h2o.toFrame

Convert a word2vec model into an H2OFrame

Description

Converts a given word2vec model into an H2OFrame. The frame represents learned word embeddings

Usage

```
h2o.toFrame(word2vec)
```

Arguments

word2vec A word2vec model.

Examples

```
h2o.init()

# Build a dummy word2vec model
data <- as.character(as.h2o(c("a", "b", "a")))
w2v.model <- h2o.word2vec(data, sent_sample_rate = 0, min_word_freq = 0, epochs = 1, vec_size = 2)

# Transform words to vectors and return average vector for each sentence
h2o.toFrame(w2v.model) # -> Frame made of 2 rows and 2 columns
```

| | |
|--------------|------------------------|
| h2o.tokenize | <i>Tokenize String</i> |
|--------------|------------------------|

Description

h2o.tokenize is similar to h2o.strsplit, the difference between them is that h2o.tokenize will store the tokenized text into a single column making it easier for additional processing (filtering stop words, word2vec algo, ...).

Usage

```
h2o.tokenize(x, split)
```

Arguments

x The column or columns whose strings to tokenize.
split The regular expression to split on.

Value

An H2OFrame with a single column representing the tokenized Strings. Original rows of the input DF are separated by NA.

Examples

```
library(h2o)
h2o.init()
string_to_tokenize <- as.h2o("Split at every character and tokenize.")
tokenize_string <- h2o.tokenize(as.character(string_to_tokenize), "")
```

| | |
|-------------|-------------------------------------|
| h2o.toLower | <i>Convert strings to lowercase</i> |
|-------------|-------------------------------------|

Description

Convert strings to lowercase

Usage

```
h2o.toLower(x)
```

Arguments

x An H2OFrame object whose strings should be lower cased

Value

An H2OFrame with all entries in lowercase format

Examples

```
library(h2o)
h2o.init()
string_to_lower <- as.h2o("ABCDE")
lowered_string <- h2o.toLower(string_to_lower)
```

| | |
|----------|-----------------|
| h2o.topN | <i>H2O topN</i> |
|----------|-----------------|

Description

Extract the top N percent of values of a column and return it in a H2OFrame.

Usage

```
h2o.topN(x, column, nPercent)
```

Arguments

x an H2OFrame
column is a column name or column index to grab the top N percent value from
nPercent is a top percentage value to grab

Value

An H2OFrame with 2 columns. The first column is the original row indices, second column contains the topN values

| | |
|-----------|--------------------------------------|
| h2o.totss | <i>Get the total sum of squares.</i> |
|-----------|--------------------------------------|

Description

If "train", "valid", and "xval" parameters are FALSE (default), then the training totss value is returned. If more than one parameter is set to TRUE, then a named vector of totss' are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.totss(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|--|
| object | An H2OClusteringModel object. |
| train | Retrieve the training total sum of squares |
| valid | Retrieve the validation total sum of squares |
| xval | Retrieve the cross-validation total sum of squares |

| | |
|------------------|---|
| h2o.tot_withinss | <i>Get the total within cluster sum of squares.</i> |
|------------------|---|

Description

If "train", "valid", and "xval" parameters are FALSE (default), then the training tot_withinss value is returned. If more than one parameter is set to TRUE, then a named vector of tot_withinss' are returned, where the names are "train", "valid" or "xval".

Usage

```
h2o.tot_withinss(object, train = FALSE, valid = FALSE, xval = FALSE)
```

Arguments

| | |
|--------|---|
| object | An H2OClusteringModel object. |
| train | Retrieve the training total within cluster sum of squares |
| valid | Retrieve the validation total within cluster sum of squares |
| xval | Retrieve the cross-validation total within cluster sum of squares |

| | |
|-------------|-------------------------------------|
| h2o.toupper | <i>Convert strings to uppercase</i> |
|-------------|-------------------------------------|

Description

Convert strings to uppercase

Usage

```
h2o.toupper(x)
```

Arguments

x An H2OFrame object whose strings should be upper cased

Value

An H2OFrame with all entries in uppercase format

Examples

```
library(h2o)
h2o.init()
string_to_upper <- as.h2o("abcde")
upper_string <- h2o.toupper(string_to_upper)
```

| | |
|---------------|---|
| h2o.transform | <i>Transform words (or sequences of words) to vectors using a word2vec model.</i> |
|---------------|---|

Description

Transform words (or sequences of words) to vectors using a word2vec model.

Usage

```
h2o.transform(word2vec, words, aggregate_method = c("NONE", "AVERAGE"))
```

Arguments

word2vec A word2vec model.

words An H2OFrame made of a single column containing source words.

aggregate_method

Specifies how to aggregate sequences of words. If method is 'NONE' then no aggregation is performed and each input word is mapped to a single word-vector. If method is 'AVERAGE' then input is treated as sequences of words delimited by NA. Each word of a sequences is internally mapped to a vector and vectors belonging to the same sentence are averaged and returned in the result.

Examples

```

h2o.init()

# Build a dummy word2vec model
data <- as.character(as.h2o(c("a", "b", "a")))
w2v.model <- h2o.word2vec(data, sent_sample_rate = 0, min_word_freq = 0, epochs = 1, vec_size = 2)

# Transform words to vectors without aggregation
sentences <- as.character(as.h2o(c("b", "c", "a", NA, "b")))
h2o.transform(w2v.model, sentences) # -> 5 rows total, 2 rows NA ("c" is not in the vocabulary)

# Transform words to vectors and return average vector for each sentence
h2o.transform(w2v.model, sentences, aggregate_method = "AVERAGE") # -> 2 rows

```

h2o.trim

Trim Space

Description

Trim Space

Usage

```
h2o.trim(x)
```

Arguments

x The column whose strings should be trimmed.

Examples

```

library(h2o)
h2o.init()
string_to_trim <- as.h2o("r tutorial")
trim_string <- h2o.trim(string_to_trim)

```

h2o.trunc

Truncate values in x toward 0

Description

trunc takes a single numeric argument x and returns a numeric vector containing the integers formed by truncating the values in x toward 0.

Usage

```
h2o.trunc(x)
```

Arguments

x An H2OFrame object.

See Also

[trunc](#) for the base R implementation.

| | |
|------------|-------------------|
| h2o.unique | <i>H2O Unique</i> |
|------------|-------------------|

Description

Extract unique values in the column.

Usage

```
h2o.unique(x)
```

Arguments

x An H2OFrame object.

Value

Returns an H2OFrame object.

| | |
|---------|---|
| h2o.var | <i>Variance of a column or covariance of columns.</i> |
|---------|---|

Description

Compute the variance or covariance matrix of one or two H2OFrames.

Usage

```
h2o.var(x, y = NULL, na.rm = FALSE, use)
```

```
var(x, y = NULL, na.rm = FALSE, use)
```

Arguments

x An H2OFrame object.

y NULL (default) or an H2OFrame. The default is equivalent to y = x.

na.rm logical. Should missing values be removed?

use An optional character string indicating how to handle missing values. This must be one of the following: "everything" - outputs NaNs whenever one of its contributing observations is missing "all.obs" - presence of missing observations will throw an error "complete.obs" - discards missing values along with all observations in their rows so that only complete observations are used

See Also

[var](#) for the base R implementation. [h2o.sd](#) for standard deviation.

Examples

```
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
var(prostate.hex$AGE)
```

| | |
|------------|--|
| h2o.varimp | <i>Retrieve the variable importance.</i> |
|------------|--|

Description

Retrieve the variable importance.

Usage

```
h2o.varimp(object)
```

Arguments

object An [H2OModel](#) object.

| | |
|-----------------|----------------------------------|
| h2o.varimp_plot | <i>Plot Variable Importances</i> |
|-----------------|----------------------------------|

Description

Plot Variable Importances

Usage

```
h2o.varimp_plot(model, num_of_features = NULL)
```

Arguments

model A trained model (accepts a trained random forest, GBM, or deep learning model, will use [h2o.std_coef_plot](#) for a trained GLM)

num_of_features The number of features shown in the plot (default is 10 or all if less than 10).

See Also

[h2o.std_coef_plot](#) for GLM.

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
hex <- h2o.importFile(prosPath)
hex[,2] <- as.factor(hex[,2])
model <- h2o.gbm(x = 3:9, y = 2, training_frame = hex, distribution = "bernoulli")
h2o.varimp_plot(model)

# for deep learning set the variable_importance parameter to TRUE
iris.hex <- as.h2o(iris)
iris.dl <- h2o.deeplearning(x = 1:4, y = 5, training_frame = iris.hex,
variable_importances = TRUE)
h2o.varimp_plot(iris.dl)
```

h2o.week

Convert Milliseconds to Week of Week Year in H2O Datasets

Description

Converts the entries of an H2OFrame object from milliseconds to weeks of the week year (starting from 1).

Usage

```
h2o.week(x)
```

```
week(x)
```

```
## S3 method for class 'H2OFrame'
week(x)
```

Arguments

x An H2OFrame object.

Value

An H2OFrame object containing the entries of x converted to weeks of the week year.

See Also

[h2o.month](#)

| | |
|-------------|--|
| h2o.weights | <i>Retrieve the respective weight matrix</i> |
|-------------|--|

Description

Retrieve the respective weight matrix

Usage

```
h2o.weights(object, matrix_id = 1)
```

Arguments

| | |
|-----------|---|
| object | An H2OModel or H2OModelMetrics |
| matrix_id | An integer, ranging from 1 to number of layers + 1, that specifies the weight matrix to return. |

| | |
|-----------|--------------------------------|
| h2o.which | <i>Which indices are TRUE?</i> |
|-----------|--------------------------------|

Description

Give the TRUE indices of a logical object, allowing for array indices.

Usage

```
h2o.which(x)
```

Arguments

| | |
|---|---------------------|
| x | An H2OFrame object. |
|---|---------------------|

Value

Returns an H2OFrame object.

See Also

[which](#) for the base R method.

Examples

```
h2o.init()
iris.hex <- as.h2o(iris)
h2o.which(iris.hex[,1]==4.4)
```

| | |
|---------------|---|
| h2o.which_max | <i>Which indice contains the max value?</i> |
|---------------|---|

Description

Get the index of the max value in a column or row

Usage

```
h2o.which_max(x, na.rm = TRUE, axis = 0)
```

```
which.max.H2OFrame(x, na.rm = TRUE, axis = 0)
```

```
which.min.H2OFrame(x, na.rm = TRUE, axis = 0)
```

Arguments

| | |
|-------|--|
| x | An H2OFrame object. |
| na.rm | logical. Indicate whether missing values should be removed. |
| axis | integer. Indicate whether to calculate the mean down a column (0) or across a row (1). |

Value

Returns an H2OFrame object.

See Also

[which.max](#) for the base R method.

| | |
|---------------|--|
| h2o.which_min | <i>Which index contains the min value?</i> |
|---------------|--|

Description

Get the index of the min value in a column or row

Usage

```
h2o.which_min(x, na.rm = TRUE, axis = 0)
```

Arguments

| | |
|-------|--|
| x | An H2OFrame object. |
| na.rm | logical. Indicate whether missing values should be removed. |
| axis | integer. Indicate whether to calculate the mean down a column (0) or across a row (1). |

Value

Returns an H2OFrame object.

See Also

[which.min](#) for the base R method.

| | |
|--------------|--------------------------|
| h2o.withinss | <i>Get the Within SS</i> |
|--------------|--------------------------|

Description

Get the Within SS

Usage

```
h2o.withinss(object)
```

Arguments

object An [H2OClusteringModel](#) object.

| | |
|--------------|--|
| h2o.word2vec | <i>Trains a word2vec model on a String column of an H2O data frame</i> |
|--------------|--|

Description

Trains a word2vec model on a String column of an H2O data frame

Usage

```
h2o.word2vec(training_frame = NULL, model_id = NULL, min_word_freq = 5,
             word_model = c("SkipGram"), norm_model = c("HSM"), vec_size = 100,
             window_size = 5, sent_sample_rate = 0.001, init_learning_rate = 0.025,
             epochs = 5, pre_trained = NULL, max_runtime_secs = 0)
```

Arguments

| | |
|----------------|---|
| training_frame | Id of the training data frame. |
| model_id | Destination id for this model; auto-generated if not specified. |
| min_word_freq | This will discard words that appear less than <int> times Defaults to 5. |
| word_model | Use the Skip-Gram model Must be one of: "SkipGram". Defaults to SkipGram. |
| norm_model | Use Hierarchical Softmax Must be one of: "HSM". Defaults to HSM. |
| vec_size | Set size of word vectors Defaults to 100. |
| window_size | Set max skip length between words Defaults to 5. |

| | |
|--------------------|---|
| sent_sample_rate | Set threshold for occurrence of words. Those that appear with higher frequency in the training data will be randomly down-sampled; useful range is (0, 1e-5) Defaults to 0.001. |
| init_learning_rate | Set the starting learning rate Defaults to 0.025. |
| epochs | Number of training iterations to run Defaults to 5. |
| pre_trained | Id of a data frame that contains a pre-trained (external) word2vec model |
| max_runtime_secs | Maximum allowed runtime in seconds for model training. Use 0 to disable. Defaults to 0. |

h2o.xgboost

Build an eXtreme Gradient Boosting model

Description

Builds a eXtreme Gradient Boosting model using the native XGBoost backend.

Usage

```
h2o.xgboost(x, y, training_frame, model_id = NULL, validation_frame = NULL,
  nfolds = 0, keep_cross_validation_predictions = FALSE,
  keep_cross_validation_fold_assignment = FALSE,
  score_each_iteration = FALSE, fold_assignment = c("AUTO", "Random",
  "Modulo", "Stratified"), fold_column = NULL, ignore_const_cols = TRUE,
  offset_column = NULL, weights_column = NULL, stopping_rounds = 0,
  stopping_metric = c("AUTO", "deviance", "logloss", "MSE", "RMSE", "MAE",
  "RMSLE", "AUC", "lift_top_group", "misclassification",
  "mean_per_class_error"), stopping_tolerance = 0.001, max_runtime_secs = 0,
  seed = -1, distribution = c("AUTO", "bernoulli", "multinomial",
  "gaussian", "poisson", "gamma", "tweedie", "laplace", "quantile", "huber"),
  tweedie_power = 1.5, categorical_encoding = c("AUTO", "Enum",
  "OneHotInternal", "OneHotExplicit", "Binary", "Eigen", "LabelEncoder",
  "SortByResponse", "EnumLimited"), quiet_mode = TRUE, ntrees = 50,
  max_depth = 6, min_rows = 1, min_child_weight = 1, learn_rate = 0.3,
  eta = 0.3, sample_rate = 1, subsample = 1, col_sample_rate = 1,
  colsample_bylevel = 1, col_sample_rate_per_tree = 1,
  colsample_bytree = 1, max_abs_leafnode_pred = 0, max_delta_step = 0,
  score_tree_interval = 0, min_split_improvement = 0, gamma = 0,
  max_bins = 256, max_leaves = 0, min_sum_hessian_in_leaf = 100,
  min_data_in_leaf = 0, sample_type = c("uniform", "weighted"),
  normalize_type = c("tree", "forest"), rate_drop = 0, one_drop = FALSE,
  skip_drop = 0, tree_method = c("auto", "exact", "approx", "hist"),
  grow_policy = c("depthwise", "lossguide"), booster = c("gbtree",
  "gblinear", "dart"), reg_lambda = 0, reg_alpha = 0,
  dmatrix_type = c("auto", "dense", "sparse"), backend = c("auto", "gpu",
  "cpu"), gpu_id = 0, verbose = FALSE)
```

Arguments

| | |
|--|---|
| <code>x</code> | (Optional) A vector containing the names or indices of the predictor variables to use in building the model. If <code>x</code> is missing, then all columns except <code>y</code> are used. |
| <code>y</code> | The name or column index of the response variable in the data. The response must be either a numeric or a categorical/factor variable. If the response is numeric, then a regression model will be trained, otherwise it will train a classification model. |
| <code>training_frame</code> | Id of the training data frame. |
| <code>model_id</code> | Destination id for this model; auto-generated if not specified. |
| <code>validation_frame</code> | Id of the validation data frame. |
| <code>nfolds</code> | Number of folds for K-fold cross-validation (0 to disable or ≥ 2). Defaults to 0. |
| <code>keep_cross_validation_predictions</code> | Logical. Whether to keep the predictions of the cross-validation models. Defaults to FALSE. |
| <code>keep_cross_validation_fold_assignment</code> | Logical. Whether to keep the cross-validation fold assignment. Defaults to FALSE. |
| <code>score_each_iteration</code> | Logical. Whether to score during each iteration of model training. Defaults to FALSE. |
| <code>fold_assignment</code> | Cross-validation fold assignment scheme, if <code>fold_column</code> is not specified. The 'Stratified' option will stratify the folds based on the response variable, for classification problems. Must be one of: "AUTO", "Random", "Modulo", "Stratified". Defaults to AUTO. |
| <code>fold_column</code> | Column with cross-validation fold index assignment per observation. |
| <code>ignore_const_cols</code> | Logical. Ignore constant columns. Defaults to TRUE. |
| <code>offset_column</code> | Offset column. This will be added to the combination of columns before applying the link function. |
| <code>weights_column</code> | Column with observation weights. Giving some observation a weight of zero is equivalent to excluding it from the dataset; giving an observation a relative weight of 2 is equivalent to repeating that row twice. Negative weights are not allowed. Note: Weights are per-row observation weights and do not increase the size of the data frame. This is typically the number of times a row is repeated, but non-integer values are supported as well. During training, rows with higher weights matter more, due to the larger loss function pre-factor. |
| <code>stopping_rounds</code> | Early stopping based on convergence of <code>stopping_metric</code> . Stop if simple moving average of length <code>k</code> of the <code>stopping_metric</code> does not improve for <code>k:=stopping_rounds</code> scoring events (0 to disable) Defaults to 0. |
| <code>stopping_metric</code> | Metric to use for early stopping (AUTO: logloss for classification, deviance for regression) Must be one of: "AUTO", "deviance", "logloss", "MSE", "RMSE", "MAE", "RMSLE", "AUC", "lift_top_group", "misclassification", "mean_per_class_error". Defaults to AUTO. |

| | |
|--------------------------|---|
| stopping_tolerance | Relative tolerance for metric-based stopping criterion (stop if relative improvement is not at least this much) Defaults to 0.001. |
| max_runtime_secs | Maximum allowed runtime in seconds for model training. Use 0 to disable. Defaults to 0. |
| seed | Seed for random numbers (affects certain parts of the algo that are stochastic and those might or might not be enabled by default) Defaults to -1 (time-based random number). |
| distribution | Distribution function Must be one of: "AUTO", "bernoulli", "multinomial", "gaussian", "poisson", "gamma", "tweedie", "laplace", "quantile", "huber". Defaults to AUTO. |
| tweedie_power | Tweedie power for Tweedie regression, must be between 1 and 2. Defaults to 1.5. |
| categorical_encoding | Encoding scheme for categorical features Must be one of: "AUTO", "Enum", "OneHotInternal", "OneHotExplicit", "Binary", "Eigen", "LabelEncoder", "Sort-ByResponse", "EnumLimited". Defaults to AUTO. |
| quiet_mode | Logical. Enable quiet mode Defaults to TRUE. |
| ntrees | (same as n_estimators) Number of trees. Defaults to 50. |
| max_depth | Maximum tree depth. Defaults to 6. |
| min_rows | (same as min_child_weight) Fewest allowed (weighted) observations in a leaf. Defaults to 1. |
| min_child_weight | (same as min_rows) Fewest allowed (weighted) observations in a leaf. Defaults to 1. |
| learn_rate | (same as eta) Learning rate (from 0.0 to 1.0) Defaults to 0.3. |
| eta | (same as learn_rate) Learning rate (from 0.0 to 1.0) Defaults to 0.3. |
| sample_rate | (same as subsample) Row sample rate per tree (from 0.0 to 1.0) Defaults to 1. |
| subsample | (same as sample_rate) Row sample rate per tree (from 0.0 to 1.0) Defaults to 1. |
| col_sample_rate | (same as colsample_bylevel) Column sample rate (from 0.0 to 1.0) Defaults to 1. |
| colsample_bylevel | (same as col_sample_rate) Column sample rate (from 0.0 to 1.0) Defaults to 1. |
| col_sample_rate_per_tree | (same as colsample_bytree) Column sample rate per tree (from 0.0 to 1.0) Defaults to 1. |
| colsample_bytree | (same as col_sample_rate_per_tree) Column sample rate per tree (from 0.0 to 1.0) Defaults to 1. |
| max_abs_leafnode_pred | (same as max_delta_step) Maximum absolute value of a leaf node prediction Defaults to 0.0. |
| max_delta_step | (same as max_abs_leafnode_pred) Maximum absolute value of a leaf node prediction Defaults to 0.0. |
| score_tree_interval | Score the model after every so many trees. Disabled if set to 0. Defaults to 0. |

| | |
|-------------------------|---|
| min_split_improvement | (same as gamma) Minimum relative improvement in squared error reduction for a split to happen Defaults to 0.0. |
| gamma | (same as min_split_improvement) Minimum relative improvement in squared error reduction for a split to happen Defaults to 0.0. |
| max_bins | For tree_method=hist only: maximum number of bins Defaults to 256. |
| max_leaves | For tree_method=hist only: maximum number of leaves Defaults to 0. |
| min_sum_hessian_in_leaf | For tree_method=hist only: the minimum sum of hessian in a leaf to keep splitting Defaults to 100.0. |
| min_data_in_leaf | For tree_method=hist only: the minimum data in a leaf to keep splitting Defaults to 0.0. |
| sample_type | For booster=dart only: sample_type Must be one of: "uniform", "weighted". Defaults to uniform. |
| normalize_type | For booster=dart only: normalize_type Must be one of: "tree", "forest". Defaults to tree. |
| rate_drop | For booster=dart only: rate_drop (0..1) Defaults to 0.0. |
| one_drop | Logical. For booster=dart only: one_drop Defaults to FALSE. |
| skip_drop | For booster=dart only: skip_drop (0..1) Defaults to 0.0. |
| tree_method | Tree method Must be one of: "auto", "exact", "approx", "hist". Defaults to auto. |
| grow_policy | Grow policy - depthwise is standard GBM, lossguide is LightGBM Must be one of: "depthwise", "lossguide". Defaults to depthwise. |
| booster | Booster type Must be one of: "gbtree", "gblinear", "dart". Defaults to gbtree. |
| reg_lambda | L2 regularization Defaults to 0.0. |
| reg_alpha | L1 regularization Defaults to 0.0. |
| dmatrix_type | Type of DMatrix. For sparse, NAs and 0 are treated equally. Must be one of: "auto", "dense", "sparse". Defaults to auto. |
| backend | Backend. By default (auto), a GPU is used if available. Must be one of: "auto", "gpu", "cpu". Defaults to auto. |
| gpu_id | Which GPU to use. Defaults to 0. |
| verbose | Logical. Print scoring history to the console (Metrics per tree for GBM, DRF, & XGBoost. Metrics per epoch for Deep Learning). Defaults to FALSE. |

h2o.xgboost.available *Determines whether an XGBoost model can be built*

Description

Ask the H2O server whether a XGBoost model can be built. (Depends on availability of native backend.) Returns True if a XGBoost model can be built, or False otherwise.

Usage

```
h2o.xgboost.available()
```

| | |
|----------|--|
| h2o.year | <i>Convert Milliseconds to Years in H2O Datasets</i> |
|----------|--|

Description

Convert the entries of an H2OFrame object from milliseconds to years, indexed starting from 1900.

Usage

```
h2o.year(x)
```

```
year(x)
```

```
## S3 method for class 'H2OFrame'  
year(x)
```

Arguments

x An H2OFrame object.

Details

This method calls the function of the MutableDateTime class in Java.

Value

An H2OFrame object containing the entries of x converted to years

See Also

[h2o.month](#)

| | |
|-----------------|----------------------------|
| H2OAutoML-class | <i>The H2OAutoML class</i> |
|-----------------|----------------------------|

Description

This class represents an H2OAutoML object

H2OClusteringModel-class

The H2OClusteringModel object.

Description

This virtual class represents a clustering model built by H2O.

Details

This object has slots for the key, which is a character string that points to the model key existing in the H2O cloud, the data used to build the model (an object of class H2OFrame).

Slots

model_id A character string specifying the key for the model fit in the H2O cloud's key-value store.

algorithm A character string specifying the algorithm that was used to fit the model.

parameters A list containing the parameter settings that were used to fit the model that differ from the defaults.

allparameters A list containing all parameters used to fit the model.

model A list containing the characteristics of the model returned by the algorithm.

size The number of points in each cluster.

totss Total sum of squared error to grand mean.

withinss A vector of within-cluster sum of squared error.

tot_withinss Total within-cluster sum of squared error.

betweenss Between-cluster sum of squared error.

H2OConnection-class *The H2OConnection class.*

Description

This class represents a connection to an H2O cloud.

Usage

```
## S4 method for signature 'H2OConnection'
show(object)
```

Arguments

object an H2OConnection object.

Details

Because H2O is not a master-slave architecture, there is no restriction on which H2O node is used to establish the connection between R (the client) and H2O (the server).

A new H2O connection is established via the `h2o.init()` function, which takes as parameters the ‘ip’ and ‘port’ of the machine running an instance to connect with. The default behavior is to connect with a local instance of H2O at port 54321, or to boot a new local instance if one is not found at port 54321.

Slots

`ip` A character string specifying the IP address of the H2O cloud.

`port` A numeric value specifying the port number of the H2O cloud.

`proxy` A character specifying the proxy path of the H2O cloud.

`https` Set this to TRUE to use https instead of http.

`insecure` Set this to TRUE to disable SSL certificate checking.

`username` Username to login with.

`password` Password to login with.

`cookies` Cookies to add to request

`context_path` Context path which is appended to H2O server location.

`mutable` An `H2OConnectionMutableState` object to hold the mutable state for the H2O connection.

`H2OConnectionMutableState`

The H2OConnectionMutableState class

Description

This class represents the mutable aspects of a connection to an H2O cloud.

Slots

`session_id` A character string specifying the H2O session identifier.

`key_count` A integer value specifying count for the number of keys generated for the `session_id`.

`H2OCoxPHModel-class`

The H2OCoxPHModel object.

Description

Virtual object representing H2O’s CoxPH Model.

Usage

```
## S4 method for signature 'H2OCoxPHModel'
show(object)
```

Arguments

`object` an `H2OCoxPHModel` object.

 H2OCoxPHModelSummary-class

The H2OCoxPHModelSummary object.

Description

Wrapper object for summary information compatible with survival package.

Slots

summary A list containing the a summary compatible with CoxPH summary used in the survival package.

 H2OFrame-class

The H2OFrame class

Description

This class represents an H2OFrame object

 H2OFrame-Extract

Extract or Replace Parts of an H2OFrame Object

Description

Operators to extract or replace parts of H2OFrame objects.

Usage

```
## S3 method for class 'H2OFrame'
data[row, col, drop = TRUE]
```

```
## S3 method for class 'H2OFrame'
x$name
```

```
## S3 method for class 'H2OFrame'
x[[i, exact = TRUE]]
```

```
## S3 method for class 'H2OFrame'
x$name
```

```
## S3 method for class 'H2OFrame'
x[[i, exact = TRUE]]
```

```
## S3 replacement method for class 'H2OFrame'
data[row, col, ...] <- value
```

```
## S3 replacement method for class 'H2OFrame'
data$name <- value
```

```
## S3 replacement method for class 'H2OFrame'
data[[name]] <- value
```

Arguments

| | |
|-------|---|
| data | object from which to extract element(s) or in which to replace element(s). |
| row | index specifying row element(s) to extract or replace. Indices are numeric or character vectors or empty (missing) or will be matched to the names. |
| col | index specifying column element(s) to extract or replace. |
| drop | Unused |
| x | An H2OFrame |
| name | a literal character string or a name (possibly backtick quoted). |
| i | index |
| exact | controls possible partial matching of [] when extracting a character |
| ... | Further arguments passed to or from other methods. |
| value | To be assigned |

H2OGrid-class

H2O Grid

Description

A class to contain the information about grid results
 Format grid object in user-friendly way

Usage

```
## S4 method for signature 'H2OGrid'
show(object)
```

Arguments

| | |
|--------|--------------------|
| object | an H2OGrid object. |
|--------|--------------------|

Slots

| | |
|----------------------|---|
| grid_id | the final identifier of grid |
| model_ids | list of model IDs which are included in the grid object |
| hyper_names | list of parameter names used for grid search |
| failed_params | list of model parameters which caused a failure during model building, it can contain a null value |
| failure_details | list of detailed messages which correspond to failed parameters field |
| failure_stack_traces | list of stack traces corresponding to model failures reported by failed_params and failure_details fields |
| failed_raw_params | list of failed raw parameters |
| summary_table | table of models built with parameters and metric information. |

See Also

[H2OModel](#) for the final model types.

| | |
|----------------|-----------------------------|
| H2OModel-class | <i>The H2OModel object.</i> |
|----------------|-----------------------------|

Description

This virtual class represents a model built by H2O.

Usage

```
## S4 method for signature 'H2OModel'
show(object)
```

Arguments

object an H2OModel object.

Details

This object has slots for the key, which is a character string that points to the model key existing in the H2O cloud, the data used to build the model (an object of class H2OFrame).

Slots

model_id A character string specifying the key for the model fit in the H2O cloud's key-value store.

algorithm A character string specifying the algorithm that were used to fit the model.

parameters A list containing the parameter settings that were used to fit the model that differ from the defaults.

allparameters A list containg all parameters used to fit the model.

have_pojo A logical indicating whether export to POJO is supported

have_mojo A logical indicating whether export to MOJO is supported

model A list containing the characteristics of the model returned by the algorithm.

| | |
|----------------------|-------------------------|
| H2OModelFuture-class | <i>H2O Future Model</i> |
|----------------------|-------------------------|

Description

A class to contain the information for background model jobs.

Slots

job_key a character key representing the identification of the job process.

model_id the final identifier for the model

See Also

[H2OModel](#) for the final model types.

H20ModelMetrics-class *The H20ModelMetrics Object.*

Description

A class for constructing performance measures of H2O models.

Usage

```
## S4 method for signature 'H20ModelMetrics'
show(object)

## S4 method for signature 'H20BinomialMetrics'
show(object)

## S4 method for signature 'H20MultinomialMetrics'
show(object)

## S4 method for signature 'H20OrdinalMetrics'
show(object)

## S4 method for signature 'H20RegressionMetrics'
show(object)

## S4 method for signature 'H20ClusteringMetrics'
show(object)

## S4 method for signature 'H20AutoEncoderMetrics'
show(object)

## S4 method for signature 'H20DimReductionMetrics'
show(object)
```

Arguments

object An H20ModelMetrics object

housevotes

United States Congressional Voting Records 1984

Description

This data set includes votes for each of the U.S. House of Representatives Congressmen on the 16 key votes identified by the CQA. The CQA lists nine different types of votes: voted for, paired for, and announced for (these three simplified to yea), voted against, paired against, and announced against (these three simplified to nay), voted present, voted present to avoid conflict of interest, and did not vote or otherwise make a position known (these three simplified to an unknown disposition).

Format

A data frame with 435 rows and 17 columns

Source

Congressional Quarterly Almanac, 98th Congress, 2nd session 1984, Volume XL: Congressional Quarterly Inc., Washington, D.C., 1985

References

Newman, D.J. & Hettich, S. & Blake, C.L. & Merz, C.J. (1998). UCI Repository of machine learning databases [<http://www.ics.uci.edu/~mlearn/MLRepository.html>]. Irvine, CA: University of California, Department of Information and Computer Science.

iris

Edgar Anderson's Iris Data

Description

Measurements in centimeters of the sepal length and width and petal length and width, respectively, for three species of iris flowers.

Format

A data frame with 150 rows and 5 columns

Source

Fisher, R. A. (1936) The use of multiple measurements in taxonomic problems. *Annals of Eugenics*, 7, Part II, 179-188.

The data were collected by Anderson, Edgar (1935). The irises of the Gaspe Peninsula, *Bulletin of the American Iris Society*, 59, 2-5.

is.character

Check if character

Description

Check if character

Usage

is.character(x)

Arguments

x An H2OFrame object

| | |
|-----------|------------------------|
| is.factor | <i>Check if factor</i> |
|-----------|------------------------|

Description

Check if factor

Usage

```
is.factor(x)
```

Arguments

| | |
|---|--------------------|
| x | An H2OFrame object |
|---|--------------------|

| | |
|--------|----------------------------|
| is.h2o | <i>Is H2O Frame object</i> |
|--------|----------------------------|

Description

Test if object is H2O Frame.

Usage

```
is.h2o(x)
```

Arguments

| | |
|---|--------------|
| x | An R object. |
|---|--------------|

| | |
|------------|-------------------------|
| is.numeric | <i>Check if numeric</i> |
|------------|-------------------------|

Description

Check if numeric

Usage

```
is.numeric(x)
```

Arguments

| | |
|---|--------------------|
| x | An H2OFrame object |
|---|--------------------|

| | |
|------------|---------------------------------|
| Logical-or | <i>Logical or for H2OFrames</i> |
|------------|---------------------------------|

Description

Logical or for H2OFrames

Usage

"||"(x, y)

Arguments

| | |
|---|--------------------|
| x | An H2OFrame object |
| y | An H2OFrame object |

| | |
|----------------|---|
| ModelAccessors | <i>Accessor Methods for H2OModel Object</i> |
|----------------|---|

Description

Function accessor methods for various H2O output fields.

Usage

```

getParms(object)

## S4 method for signature 'H2OModel'
getParms(object)

getCenters(object)

getCentersStd(object)

getWithinSS(object)

getTotWithinSS(object)

getBetweenSS(object)

getTotSS(object)

getIterations(object)

getClusterSizes(object)

## S4 method for signature 'H2OClusteringModel'
getCenters(object)

```

```

## S4 method for signature 'H2OClusteringModel'
getCentersStd(object)

## S4 method for signature 'H2OClusteringModel'
getWithinSS(object)

## S4 method for signature 'H2OClusteringModel'
getTotWithinSS(object)

## S4 method for signature 'H2OClusteringModel'
getBetweenSS(object)

## S4 method for signature 'H2OClusteringModel'
getTotSS(object)

## S4 method for signature 'H2OClusteringModel'
getIterations(object)

## S4 method for signature 'H2OClusteringModel'
getClusterSizes(object)

```

Arguments

object an [H2OModel](#) class object.

| | |
|----------------|------------------------------------|
| names.H2OFrame | <i>Column names of an H2OFrame</i> |
|----------------|------------------------------------|

Description

Column names of an H2OFrame

Usage

```

## S3 method for class 'H2OFrame'
names(x)

```

Arguments

x An H2OFrame

| | |
|--------------|---|
| Ops.H2OFrame | <i>S3 Group Generic Functions for H2O</i> |
|--------------|---|

Description

Methods for group generic functions and H2O objects.

Usage

```
## S3 method for class 'H2OFrame'  
Ops(e1, e2)  
  
## S3 method for class 'H2OFrame'  
Math(x, ...)  
  
## S3 method for class 'H2OFrame'  
Math(x, ...)  
  
## S3 method for class 'H2OFrame'  
Math(x, ...)  
  
## S3 method for class 'H2OFrame'  
Summary(x, ..., na.rm)  
  
## S3 method for class 'H2OFrame'  
!x  
  
## S3 method for class 'H2OFrame'  
is.na(x)  
  
## S3 method for class 'H2OFrame'  
t(x)  
  
log(x, ...)  
  
log10(x)  
  
log2(x)  
  
log1p(x)  
  
trunc(x, ...)  
  
x %% y  
  
nrow.H2OFrame(x)  
  
ncol.H2OFrame(x)  
  
## S3 method for class 'H2OFrame'  
length(x)  
  
h2o.length(x)  
  
## S3 replacement method for class 'H2OFrame'  
names(x) <- value  
  
colnames(x) <- value
```

Arguments

| | |
|-------|--|
| e1 | object |
| e2 | object |
| x | object |
| ... | Further arguments passed to or from other methods. |
| na.rm | logical. whether or not missing values should be removed |
| y | object |
| value | To be assigned |

| | |
|---------------|--------------------------|
| plot.H2OModel | <i>Plot an H2O Model</i> |
|---------------|--------------------------|

Description

Plots training set (and validation set if available) scoring history for an H2O Model

Usage

```
## S3 method for class 'H2OModel'
plot(x, timestep = "AUTO", metric = "AUTO", ...)
```

Arguments

| | |
|----------|---|
| x | A fitted H2OModel object for which the scoring history plot is desired. |
| timestep | A unit of measurement for the x-axis. |
| metric | A unit of measurement for the y-axis. |
| ... | additional arguments to pass on. |

Details

This method dispatches on the type of H2O model to select the correct scoring history. The timestep and metric arguments are restricted to what is available in the scoring history for a particular type of model.

Value

Returns a scoring history plot.

See Also

[h2o.deeplearning](#), [h2o.gbm](#), [h2o.glm](#), [h2o.randomForest](#) for model generation in h2o.

Examples

```

if (requireNamespace("mlbench", quietly=TRUE)) {
  library(h2o)
  h2o.init()

  df <- as.h2o(mlbench::mlbench.friedman1(10000,1))
  rng <- h2o.runif(df, seed=1234)
  train <- df[rng<0.8,]
  valid <- df[rng>=0.8,]

  gbm <- h2o.gbm(x = 1:10, y = "y", training_frame = train, validation_frame = valid,
                ntrees=500, learn_rate=0.01, score_each_iteration = TRUE)

  plot(gbm)
  plot(gbm, timestep = "duration", metric = "deviance")
  plot(gbm, timestep = "number_of_trees", metric = "deviance")
  plot(gbm, timestep = "number_of_trees", metric = "rmse")
  plot(gbm, timestep = "number_of_trees", metric = "mae")
}

```

plot.H2OTabulate

*Plot an H2O Tabulate Heatmap***Description**

Plots the simple co-occurrence based tabulation of X vs Y as a heatmap, where X and Y are two Vectors in a given dataset. This function requires suggested ggplot2 package.

Usage

```

## S3 method for class 'H2OTabulate'
plot(x, xlab = x$cols[1], ylab = x$cols[2],
     base_size = 12, ...)

```

Arguments

| | |
|-----------|--|
| x | An H2OTabulate object for which the heatmap plot is desired. |
| xlab | A title for the x-axis. Defaults to what is specified in the given H2OTabulate object. |
| ylab | A title for the y-axis. Defaults to what is specified in the given H2OTabulate object. |
| base_size | Base font size for plot. |
| ... | additional arguments to pass on. |

Value

Returns a ggplot2-based heatmap of co-occurrence.

See Also

`link{h2o.tabulate}`

Examples

```
library(h2o)
h2o.init()
df <- as.h2o(iris)
tab <- h2o.tabulate(data = df, x = "Sepal.Length", y = "Petal.Width",
  weights_column = NULL, nbins_x = 10, nbins_y = 10)
plot(tab)
```

predict.H2OAutoML *Predict on an AutoML object*

Description

Obtains predictions from an AutoML object.

Usage

```
## S3 method for class 'H2OAutoML'
predict(object, newdata, ...)
```

Arguments

| | |
|---------|---|
| object | a fitted H2OAutoML object for which prediction is desired |
| newdata | An H2OFrame object in which to look for variables with which to predict. |
| ... | additional arguments to pass on. |

Details

This method generated predictions on the leader model from an AutoML run. The order of the rows in the results is the same as the order in which the data was loaded, even if some rows fail (for example, due to missing values or unseen factor levels).

Value

Returns an H2OFrame object with probabilities and default predictions.

predict.H2OModel *Predict on an H2O Model*

Description

Obtains predictions from various fitted H2O model objects.

Usage

```
## S3 method for class 'H2OModel'
predict(object, newdata, ...)

h2o.predict(object, newdata, ...)
```

Arguments

| | |
|---------|--|
| object | a fitted H2OModel object for which prediction is desired |
| newdata | An H2OFrame object in which to look for variables with which to predict. |
| ... | additional arguments to pass on. |

Details

This method dispatches on the type of H2O model to select the correct prediction/scoring algorithm. The order of the rows in the results is the same as the order in which the data was loaded, even if some rows fail (for example, due to missing values or unseen factor levels).

Value

Returns an H2OFrame object with probabilities and default predictions.

See Also

[h2o.deeplearning](#), [h2o.gbm](#), [h2o.glm](#), [h2o.randomForest](#) for model generation in h2o.

predict_leaf_node_assignment.H2OModel

Predict the Leaf Node Assignment on an H2O Model

Description

Obtains leaf node assignment from fitted H2O model objects.

Usage

```
predict_leaf_node_assignment.H2OModel(object, newdata, ...)
```

```
h2o.predict_leaf_node_assignment(object, newdata, ...)
```

Arguments

| | |
|---------|--|
| object | a fitted H2OModel object for which prediction is desired |
| newdata | An H2OFrame object in which to look for variables with which to predict. |
| ... | additional arguments to pass on. |

Details

For every row in the test set, return a set of factors that identify the leaf placements of the row in all the trees in the model. The order of the rows in the results is the same as the order in which the data was loaded

Value

Returns an H2OFrame object with categorical leaf assignment identifiers for each tree in the model.

See Also

[h2o.gbm](#) and [h2o.randomForest](#) for model generation in h2o.

Examples

```
library(h2o)
h2o.init()
prosPath <- system.file("extdata", "prostate.csv", package="h2o")
prostate.hex <- h2o.uploadFile(path = prosPath)
prostate.hex$CAPSULE <- as.factor(prostate.hex$CAPSULE)
prostate.gbm <- h2o.gbm(3:9, "CAPSULE", prostate.hex)
h2o.predict(prostate.gbm, prostate.hex)
h2o.predict_leaf_node_assignment(prostate.gbm, prostate.hex)
```

| | |
|----------------|--------------------------|
| print.H2OFrame | <i>Print An H2OFrame</i> |
|----------------|--------------------------|

Description

Print An H2OFrame

Usage

```
## S3 method for class 'H2OFrame'
print(x, n = 6L, ...)
```

Arguments

| | |
|-----|--|
| x | An H2OFrame object |
| n | An (Optional) A single integer. If positive, number of rows in x to return. If negative, all but the n first/last number of rows in x. Anything bigger than 20 rows will require asking the server (first 20 rows are cached on the client). |
| ... | Further arguments to be passed from or to other methods. |

| | |
|----------------|--|
| print.H2OTable | <i>Print method for H2OTable objects</i> |
|----------------|--|

Description

This will print a truncated view of the table if there are more than 20 rows.

Usage

```
## S3 method for class 'H2OTable'
print(x, header = TRUE, ...)
```

Arguments

| | |
|--------|--|
| x | An H2OTable object |
| header | A logical value dictating whether or not the table name should be printed. |
| ... | Further arguments passed to or from other methods. |

Value

The original x object

| | |
|----------|------------------------------|
| prostate | <i>Prostate Cancer Study</i> |
|----------|------------------------------|

Description

Baseline exam results on prostate cancer patients from Dr. Donn Young at The Ohio State University Comprehensive Cancer Center.

Format

A data frame with 380 rows and 9 columns

Source

Hosmer and Lemeshow (2000) Applied Logistic Regression: Second Edition.

| | |
|----------------|-------------------------------|
| range.H2OFrame | <i>Range of an H2O Column</i> |
|----------------|-------------------------------|

Description

Range of an H2O Column

Usage

```
## S3 method for class 'H2OFrame'
range(..., na.rm = TRUE)
```

Arguments

| | |
|-------|-----------------------|
| ... | An H2OFrame object. |
| na.rm | ignore missing values |

```
show, H2OCoxPHModelSummary-method
      Print the CoxPH Model Summary
```

Description

Print the CoxPH Model Summary

Usage

```
## S4 method for signature 'H2OCoxPHModelSummary'
show(object)
```

Arguments

| | |
|--------|---|
| object | An H2OCoxPHModelSummary object. |
| ... | further arguments to be passed on (currently unimplemented) |

```
str.H2OFrame      Display the structure of an H2OFrame object
```

Description

Display the structure of an H2OFrame object

Usage

```
## S3 method for class 'H2OFrame'
str(object, ..., cols = FALSE)
```

Arguments

| | |
|--------|--|
| object | An H2OFrame. |
| ... | Further arguments to be passed from or to other methods. |
| cols | Print the per-column str for the H2OFrame |

summary,H2OCoxPHModel-method

Print the CoxPH Model Summary

Description

Print the CoxPH Model Summary

Usage

```
## S4 method for signature 'H2OCoxPHModel'  
summary(object, conf.int = 0.95, scale = 1)
```

Arguments

| | |
|----------|---|
| object | an H2OCoxPHModel object. |
| conf.int | a specification of the confidence interval. |
| scale | a scale. |

summary,H2OGrid-method

Format grid object in user-friendly way

Description

Format grid object in user-friendly way

Usage

```
## S4 method for signature 'H2OGrid'  
summary(object, show_stack_traces = FALSE)
```

Arguments

| | |
|-------------------|--|
| object | an H2OGrid object. |
| show_stack_traces | a flag to show stack traces for model failures |

summary, H2OModel-method

Print the Model Summary

Description

Print the Model Summary

Usage

```
## S4 method for signature 'H2OModel'
summary(object, ...)
```

Arguments

| | |
|--------|---|
| object | An H2OModel object. |
| ... | further arguments to be passed on (currently unimplemented) |

use.package

Use optional package

Description

Testing availability of optional package, its version, and extra global default. This function is used internally. It is exported and documented because user can control behavior of the function by global option.

Usage

```
use.package(package, version = "1.9.8"[package == "data.table"],
  use = getOption("h2o.use.data.table", FALSE)[package == "data.table"])
```

Arguments

| | |
|---------|---|
| package | character scalar name of a package that we Suggests or Enhances on. |
| version | character scalar required version of a package. |
| use | logical scalar, extra escape option, to be used as global option. |

Details

We use this function to control csv read/write with optional [data.table](#) package. Currently data.table is disabled by default, to enable it set options("h2o.use.data.table"=TRUE). It is possible to control just [fread](#) or [fwrite](#) with options("h2o.fread"=FALSE, "h2o.fwrite"=FALSE). h2o.fread and h2o.fwrite options are not handled in this function but next to *fread* and *fwrite* calls.

See Also

[as.h2o.data.frame](#), [as.data.frame.H2OFrame](#)

Examples

```

op <- options("h2o.use.data.table" = TRUE)
if (use.package("data.table")) {
  cat("optional package data.table 1.9.8+ is available\n")
} else {
  cat("optional package data.table 1.9.8+ is not available\n")
}
options(op)

```

walking

*Muscular Actuations for Walking Subject***Description**

The musculoskeletal model, experimental data, settings files, and results for three-dimensional, muscle-actuated simulations at walking speed as described in Hamner and Delp (2013). Simulations were generated using OpenSim 2.4. The data is available from https://simtk.org/project/xml/downloads.xml?group_id=603.

Format

A data frame with 151 rows and 124 columns

References

Hamner, S.R., Delp, S.L. Muscle contributions to fore-aft and vertical body mass center accelerations over a range of running speeds. *Journal of Biomechanics*, vol 46, pp 780-787. (2013)

zzz

*Shutdown H2O cloud after examples run***Description**

Shutdown H2O cloud after examples run

Examples

```

library(h2o)
h2o.init()
h2o.shutdown(prompt = FALSE)
Sys.sleep(3)

```

&&

Logical and for H2OFrames

Description

Logical and for H2OFrames

Usage

"&&"(x, y)

Arguments

| | |
|---|--------------------|
| x | An H2OFrame object |
| y | An H2OFrame object |

Index

- !.H2OFrame (Ops.H2OFrame), 208
- *Topic **datasets**
 - australia, 14
 - housevotes, 204
 - iris, 205
 - prostate, 215
 - walking, 219
- *Topic **package**
 - h2o-package, 7
- [, H2OFrame-method (H2OFrame-Extract), 201
- [.H2OFrame (H2OFrame-Extract), 201
- [<-.H2OFrame (H2OFrame-Extract), 201
- [[.H2OFrame (H2OFrame-Extract), 201
- [[<-.H2OFrame (H2OFrame-Extract), 201
- \$.H2OFrame (H2OFrame-Extract), 201
- \$<-.H2OFrame (H2OFrame-Extract), 201
- %% (Ops.H2OFrame), 208
- %in% (h2o.match), 118
- &&, 220

- aaa, 8
- abs, 16
- acos, 17
- all, 20, 21
- apply, 8, 8
- as.character, 22
- as.character.H2OFrame, 9
- as.data.frame.H2OFrame, 9, 218
- as.factor, 10, 10, 23
- as.h2o, 11
- as.h2o.data.frame, 218
- as.matrix.H2OFrame, 12
- as.numeric, 13, 23
- as.vector.H2OFrame, 13
- australia, 14

- cbind, 29
- ceiling, 30
- colMeans, 120
- colnames, 14, 34
- colnames<- (Ops.H2OFrame), 208
- cor (h2o.cor), 38
- cos, 39

- cosh, 39
- cummax, 44
- cummin, 45
- cumprod, 45
- cumsum, 46
- cut.H2OFrame (h2o.cut), 46

- data.table, 218
- day (h2o.day), 47
- dayOfWeek (h2o.dayOfWeek), 48
- ddply, 49
- dim, 15, 63
- dim.H2OFrame, 15
- dimnames, 64
- dimnames.H2OFrame, 15

- exp, 68

- floor, 73
- fread, 10, 218
- fwrite, 11, 218

- getBetweenSS (ModelAccessors), 207
- getBetweenSS, H2OClusteringModel-method (ModelAccessors), 207
- getCenters (ModelAccessors), 207
- getCenters, H2OClusteringModel-method (ModelAccessors), 207
- getCentersStd (ModelAccessors), 207
- getCentersStd, H2OClusteringModel-method (ModelAccessors), 207
- getClusterSizes (ModelAccessors), 207
- getClusterSizes, H2OClusteringModel-method (ModelAccessors), 207
- getIterations (ModelAccessors), 207
- getIterations, H2OClusteringModel-method (ModelAccessors), 207
- getParms (ModelAccessors), 207
- getParms, H2OModel-method (ModelAccessors), 207
- getTotSS (ModelAccessors), 207
- getTotSS, H2OClusteringModel-method (ModelAccessors), 207
- getTotWithinSS (ModelAccessors), 207

- getTotWithinSS, H2OClusteringModel-method (ModelAccessors), 207
- getWithinSS (ModelAccessors), 207
- getWithinSS, H2OClusteringModel-method (ModelAccessors), 207
- h2o (h2o-package), 7
- h2o-package, 7
- h2o.abs, 16
- h2o.accuracy (h2o.metric), 124
- h2o.acos, 17
- h2o.aggregated_frame, 17
- h2o.aggregator, 18
- h2o.aic, 19
- h2o.all, 20
- h2o.anomaly, 20
- h2o.any, 21
- h2o.anyFactor, 21
- h2o.arrange, 22
- h2o.as_date, 24
- h2o.ascharacter, 22
- h2o.asfactor, 23
- h2o.asnumeric, 23
- h2o.assign, 24, 156
- h2o.auc, 25, 83, 87, 125, 128, 156
- h2o.automl, 25
- h2o.betweenSS, 27, 109
- h2o.biases, 28
- h2o.bottomN, 28
- h2o.cbind, 29
- h2o.ceiling, 29
- h2o.centers, 30, 109
- h2o.centersSTD, 30, 109
- h2o.centroid_stats, 30
- h2o.clearLog, 31, 136, 170, 171
- h2o.cluster_sizes, 33, 109
- h2o.clusterInfo, 31
- h2o.clusterIsUp, 32
- h2o.clusterStatus, 32
- h2o.coef, 33
- h2o.coef_norm, 34
- h2o.colnames, 34
- h2o.columns_by_type, 35
- h2o.computeGram, 35
- h2o.confusionMatrix, 36, 87
- h2o.confusionMatrix, H2OModel-method (h2o.confusionMatrix), 36
- h2o.confusionMatrix, H2OModelMetrics-method (h2o.confusionMatrix), 36
- h2o.connect, 37
- h2o.cor, 38
- h2o.cos, 39
- h2o.cosh, 39
- h2o.coxph, 40
- h2o.createFrame, 41
- h2o.cross_validation_fold_assignment, 42
- h2o.cross_validation_holdout_predictions, 43
- h2o.cross_validation_models, 43
- h2o.cross_validation_predictions, 44
- h2o.cummax, 44
- h2o.cummin, 45
- h2o.cumprod, 45
- h2o.cumsum, 46
- h2o.cut, 46
- h2o.day, 47, 48, 96
- h2o.dayOfWeek, 48
- h2o.dct, 48
- h2o.ddply, 49
- h2o.decryptionSetup, 50, 97, 137, 138
- h2o.deepfeatures, 51
- h2o.deeplearning, 20, 52, 210, 213
- h2o.deepwater, 58
- h2o.deepwater.available, 62
- h2o.describe, 62
- h2o.diffflag1, 63
- h2o.dim, 63
- h2o.dimnames, 64
- h2o.distance, 64
- h2o.download_mojo, 66
- h2o.download_pojo, 67
- h2o.downloadAllLogs, 65
- h2o.downloadCSV, 65
- h2o.entropy, 68
- h2o.error (h2o.metric), 124
- h2o.exp, 68
- h2o.exportFile, 69
- h2o.exportHDFS, 70
- h2o.F0point5 (h2o.metric), 124
- h2o.F1 (h2o.metric), 124
- h2o.F2 (h2o.metric), 124
- h2o.fallout (h2o.metric), 124
- h2o.fillna, 70
- h2o.filterNACols, 71
- h2o.find_row_by_threshold, 72
- h2o.find_threshold_by_max_metric, 72
- h2o.findSynonyms, 71
- h2o.floor, 73
- h2o.flow, 73
- h2o.fnr (h2o.metric), 124
- h2o.fpr (h2o.metric), 124
- h2o.gainsLift, 73
- h2o.gainsLift, H2OModel-method (h2o.gainsLift), 73

- h2o.gainsLift, H2OModelMetrics-method
(h2o.gainsLift), 73
- h2o.gbm, 74, 210, 213, 214
- h2o.getConnection, 78
- h2o.getFrame, 79
- h2o.getFutureModel, 79
- h2o.getGLMFullRegularizationPath, 79
- h2o.getGrid, 80
- h2o.getId, 80
- h2o.getModel, 81
- h2o.getTimezone, 81
- h2o.getTypes, 82
- h2o.getVersion, 82
- h2o.giniCoef, 25, 82, 83, 87, 125
- h2o.glm, 7, 83, 210, 213
- h2o.glm, 87, 142, 145, 152
- h2o.grep, 90
- h2o.grid, 91
- h2o.group_by, 92
- h2o.gsub, 93
- h2o.head, 94
- h2o.hist, 94
- h2o.hit_ratio_table, 95
- h2o.hour, 95
- h2o.ifelse, 96
- h2o.import_sql_select, 98, 98
- h2o.import_sql_table, 98, 99
- h2o.importFile, 50, 97, 137
- h2o.importFolder (h2o.importFile), 97
- h2o.importHDFS (h2o.importFile), 97
- h2o.impute, 100
- h2o.init, 32, 101, 165
- h2o.insertMissingValues, 103
- h2o.interaction, 104
- h2o.is_client, 107
- h2o.isax, 105
- h2o.ischaracter, 106
- h2o.isfactor, 106
- h2o.isnumeric, 107
- h2o.kfold_column, 107
- h2o.killMinus3, 108
- h2o.kmeans, 89, 108
- h2o.kurtosis, 110
- h2o.length (Ops.H2OFrame), 208
- h2o.levels, 110
- h2o.list_all_extensions, 111
- h2o.list_api_extensions, 111
- h2o.list_core_extensions, 112
- h2o.listTimezones, 111
- h2o.loadModel, 112, 160
- h2o.log, 113
- h2o.log10, 113
- h2o.log1p, 114
- h2o.log2, 114
- h2o.logAndEcho, 115
- h2o.logloss, 87, 115
- h2o.ls, 116, 156
- h2o.lstrip, 116
- h2o.mae, 117
- h2o.make_metrics, 118
- h2o.makeGLMModel, 117
- h2o.match, 118
- h2o.max, 119
- h2o.maxPerClassError (h2o.metric), 124
- h2o.mcc (h2o.metric), 124
- h2o.mean, 120
- h2o.mean_per_class_accuracy
(h2o.metric), 124
- h2o.mean_per_class_error, 121
- h2o.mean_residual_deviance, 122
- h2o.median, 122
- h2o.merge, 123
- h2o.metric, 25, 83, 121, 124, 128, 156
- h2o.min, 126
- h2o.missrate (h2o.metric), 124
- h2o.mktime, 126
- h2o.month, 47, 48, 127, 190, 198
- h2o.mse, 25, 87, 121, 125, 127, 128, 156
- h2o.na_omit, 131
- h2o.nacnt, 128
- h2o.naiveBayes, 129
- h2o.names, 131
- h2o.nchar, 132
- h2o.ncol, 132
- h2o.networkTest, 133
- h2o.nlevels, 133
- h2o.no_progress, 133
- h2o.nrow, 134
- h2o.null_deviance, 134
- h2o.null_dof, 135
- h2o.num_iterations, 109, 135
- h2o.num_valid_substrings, 136
- h2o.openLog, 31, 136, 170, 171
- h2o.parseRaw, 97, 98, 137, 138
- h2o.parseSetup, 50, 137, 138
- h2o.partialPlot, 139
- h2o.performance, 25, 37, 74, 83, 87, 121,
125, 128, 140, 156
- h2o.pivot, 141
- h2o.prcomp, 89, 141
- h2o.precision (h2o.metric), 124
- h2o.predict (predict.H2OModel), 212
- h2o.predict_json, 143
- h2o.predict_leaf_node_assignment

- (predict_leaf_node_assignment.H2OModel), 213
- h2o.print, 144
- h2o.prod, 144
- h2o.proj_archetypes, 145
- h2o.quantile, 146
- h2o.r2, 147
- h2o.randomForest, 147, 210, 213, 214
- h2o.range, 151
- h2o.rbind, 151
- h2o.recall (h2o.metric), 124
- h2o.reconstruct, 152
- h2o.relevel, 153
- h2o.removeAll, 153
- h2o.removeVecs, 154
- h2o.rep_len, 154
- h2o.residual_deviance, 155
- h2o.residual_dof, 155
- h2o.rm, 153, 156
- h2o.rmse, 156
- h2o.rmsle, 157
- h2o.round, 158
- h2o.rstrip, 158
- h2o.runif, 159
- h2o.saveModel, 112, 159, 161
- h2o.saveModelDetails, 160
- h2o.saveMojo, 161
- h2o.scale, 162
- h2o.scoreHistory, 87, 162
- h2o.sd, 163, 189
- h2o.sdev, 163
- h2o.sensitivity (h2o.metric), 124
- h2o.setLevels, 164
- h2o.setTimezone, 164
- h2o.show_progress, 165
- h2o.shutdown, 103, 165
- h2o.signif, 166
- h2o.sin, 166
- h2o.skewness, 167
- h2o.specificity (h2o.metric), 124
- h2o.splitFrame, 167
- h2o.sqrt, 168
- h2o.stackedEnsemble, 169
- h2o.startLogging, 31, 136, 170, 171
- h2o.std_coef_plot, 171, 189
- h2o.stopLogging, 31, 136, 170, 171
- h2o.str, 172
- h2o.stringdist, 172
- h2o.strsplit, 173
- h2o.sub, 173
- h2o.substr (h2o.substring), 174
- h2o.substring, 174
- h2o.sum, 175
- h2o.summary, 175
- h2o.svd, 89, 142, 176
- h2o.table, 178
- h2o.tabulate, 178
- h2o.tail (h2o.head), 94
- h2o.tan, 179
- h2o.tanh, 180
- h2o.target_encode_apply, 180, 182
- h2o.target_encode_create, 180, 181, 181
- h2o.tnr (h2o.metric), 124
- h2o.toFrame, 182
- h2o.tokenize, 183
- h2o.tolower, 184
- h2o.topN, 184
- h2o.tot_withinss, 109, 185
- h2o.totss, 109, 185
- h2o.toupper, 186
- h2o.tpr (h2o.metric), 124
- h2o.transform, 186
- h2o.trim, 187
- h2o.trunc, 187
- h2o.unique, 188
- h2o.uploadFile (h2o.importFile), 97
- h2o.var, 163, 188
- h2o.varimp, 87, 189
- h2o.varimp_plot, 171, 189
- h2o.week, 190
- h2o.weights, 191
- h2o.which, 191
- h2o.which_max, 192
- h2o.which_min, 192
- h2o.withinss, 109, 193
- h2o.word2vec, 193
- h2o.xgboost, 194
- h2o.xgboost.available, 197
- h2o.year, 127, 198
- H2OAutoEncoderMetrics-class
 - (H2OModelMetrics-class), 204
- H2OAutoEncoderModel, 20
- H2OAutoEncoderModel-class
 - (H2OModel-class), 203
- H2OAutoML, 27, 212
- H2OAutoML-class, 198
- H2OBinomialMetrics, 25, 36, 74, 82, 83, 115, 121, 125, 128, 156
- H2OBinomialMetrics-class
 - (H2OModelMetrics-class), 204
- H2OBinomialModel, 87, 130
- H2OBinomialModel-class
 - (H2OModel-class), 203
- H2OClusteringMetrics-class

- (H2OModelMetrics-class), 204
- H2OClusteringModel, 17, 28, 30, 33, 109, 135, 185, 193
- H2OClusteringModel-class, 199
- H2OConnection, 32, 79
- H2OConnection (H2OConnection-class), 199
- H2OConnection-class, 199
- H2OConnectionMutableState, 200
- H2OCoxPHMetrics-class
 - (H2OModelMetrics-class), 204
- H2OCoxPHModel (H2OCoxPHModel-class), 200
- H2OCoxPHModel-class, 200
- H2OCoxPHModelSummary, 216
- H2OCoxPHModelSummary
 - (H2OCoxPHModelSummary-class), 201
- H2OCoxPHModelSummary-class, 201
- H2ODimReductionMetrics-class
 - (H2OModelMetrics-class), 204
- H2ODimReductionModel, 89, 142, 145, 152, 163, 177
- H2ODimReductionModel-class
 - (H2OModel-class), 203
- H2OFrame-class, 201
- H2OFrame-Extract, 201
- H2OGrid (H2OGrid-class), 202
- H2OGrid-class, 202
- H2OModel, 19, 28, 33, 34, 36, 42–44, 51, 70, 74, 79, 81, 87, 95, 112, 117, 122, 134, 135, 139, 140, 147, 150, 155, 157, 159–162, 189, 191, 203, 208, 210, 213, 218
- H2OModel (H2OModel-class), 203
- H2OModel-class, 203
- H2OModelFuture-class, 203
- H2OModelMetrics, 19, 28, 36, 37, 74, 115, 118, 125, 127, 134, 135, 140, 155, 156, 191
- H2OModelMetrics
 - (H2OModelMetrics-class), 204
- H2OModelMetrics-class, 204
- H2OMultinomialMetrics, 36, 115, 128, 156
- H2OMultinomialMetrics-class
 - (H2OModelMetrics-class), 204
- H2OMultinomialModel, 130
- H2OMultinomialModel-class
 - (H2OModel-class), 203
- H2OOrdinalMetrics-class
 - (H2OModelMetrics-class), 204
- H2OOrdinalModel-class (H2OModel-class), 203
- H2ORegressionMetrics, 128, 156
- H2ORegressionMetrics-class
 - (H2OModelMetrics-class), 204
- H2ORegressionModel, 87
- H2ORegressionModel-class
 - (H2OModel-class), 203
- H2OUnknownMetrics-class
 - (H2OModelMetrics-class), 204
- H2OUnknownModel-class (H2OModel-class), 203
- H2OWordEmbeddingMetrics-class
 - (H2OModelMetrics-class), 204
- H2OWordEmbeddingModel-class
 - (H2OModel-class), 203
- head.H2OFrame (h2o.head), 94
- hour (h2o.hour), 95
- housevotes, 204
- ifelse (h2o.ifelse), 96
- iris, 205
- is.character, 106, 205
- is.factor, 106, 206
- is.h2o, 206
- is.na.H2OFrame (Ops.H2OFrame), 208
- is.numeric, 107, 206
- kurtosis.H2OFrame (h2o.kurtosis), 110
- length.H2OFrame (Ops.H2OFrame), 208
- levels, 111
- log, 113
- log (Ops.H2OFrame), 208
- log10, 113
- log10 (Ops.H2OFrame), 208
- log1p, 114
- log1p (Ops.H2OFrame), 208
- log2, 114
- log2 (Ops.H2OFrame), 208
- Logical-or, 207
- match, 119
- match.H2OFrame (h2o.match), 118
- Math.H2OFrame (Ops.H2OFrame), 208
- max, 119
- mean, 120
- mean.H2OFrame (h2o.mean), 120
- median.H2OFrame (h2o.median), 122
- min, 126
- ModelAccessors, 207
- month (h2o.month), 127
- names, 131
- names.H2OFrame, 208
- names<- .H2OFrame (Ops.H2OFrame), 208

- ncol, [132](#)
- ncol.H2OFrame (Ops.H2OFrame), [208](#)
- nlevels, [133](#)
- nrow, [134](#)
- nrow.H2OFrame (Ops.H2OFrame), [208](#)
- Ops.H2OFrame, [208](#)
- plot.H2OModel, [210](#)
- plot.H2OTabulate, [211](#)
- predict, [36](#), [37](#), [74](#)
- predict.H2OAutoML, [212](#)
- predict.H2OModel, [57](#), [78](#), [87](#), [151](#), [212](#)
- predict_leaf_node_assignment.H2OModel, [213](#)
- print.H2OFrame, [214](#)
- print.H2OTable, [214](#)
- prod, [144](#)
- prostate, [215](#)
- quantile, [146](#)
- quantile.H2OFrame (h2o.quantile), [146](#)
- range, [151](#)
- range.H2OFrame, [215](#)
- rbind, [151](#)
- round, [158](#)
- round (h2o.round), [158](#)
- rowMeans, [120](#)
- scale.H2OFrame (h2o.scale), [162](#)
- sd, [163](#)
- sd (h2o.sd), [163](#)
- show,H2OAutoEncoderMetrics-method (H2OModelMetrics-class), [204](#)
- show,H2OBinomialMetrics-method (H2OModelMetrics-class), [204](#)
- show,H2OClusteringMetrics-method (H2OModelMetrics-class), [204](#)
- show,H2OConnection-method (H2OConnection-class), [199](#)
- show,H2OCoxPHModel-method (H2OCoxPHModel-class), [200](#)
- show,H2OCoxPHModelSummary-method, [216](#)
- show,H2ODimReductionMetrics-method (H2OModelMetrics-class), [204](#)
- show,H2OGrid-method (H2OGrid-class), [202](#)
- show,H2OModel-method (H2OModel-class), [203](#)
- show,H2OModelMetrics-method (H2OModelMetrics-class), [204](#)
- show,H2OMultinomialMetrics-method (H2OModelMetrics-class), [204](#)
- show,H2OOrdinalMetrics-method (H2OModelMetrics-class), [204](#)
- show,H2ORegressionMetrics-method (H2OModelMetrics-class), [204](#)
- signif, [166](#)
- signif (h2o.signif), [166](#)
- sin, [166](#)
- skewness.H2OFrame (h2o.skewness), [167](#)
- sqrt, [168](#)
- str.H2OFrame, [216](#)
- sum, [175](#)
- summary, [175](#)
- summary,H2OCoxPHModel-method, [217](#)
- summary,H2OGrid-method, [217](#)
- summary,H2OModel-method, [218](#)
- Summary.H2OFrame (Ops.H2OFrame), [208](#)
- summary.H2OFrame (h2o.summary), [175](#)
- t.H2OFrame (Ops.H2OFrame), [208](#)
- table.H2OFrame (h2o.table), [178](#)
- tail.H2OFrame (h2o.head), [94](#)
- tan, [179](#)
- tanh, [180](#)
- trunc, [188](#)
- trunc (Ops.H2OFrame), [208](#)
- use.package, [10](#), [11](#), [218](#)
- var, [189](#)
- var (h2o.var), [188](#)
- walking, [219](#)
- week (h2o.week), [190](#)
- which, [191](#)
- which.max, [192](#)
- which.max.H2OFrame (h2o.which_max), [192](#)
- which.min, [193](#)
- which.min.H2OFrame (h2o.which_max), [192](#)
- year (h2o.year), [198](#)
- zzz, [219](#)